International Conference on Space Optics—ICSO 2012

Ajaccio, Corse

9–12 October 2012

Edited by Bruno Cugny, Errico Armandillo, and Nikos Karafolas

Mission study of up-link laser differential absorption sensing

Yohei Satoh

Yoshikazu Chishiki

Daisuke Sakaizawa

Shiro Yamakawa

International Conference on Space Optics — ICSO 2012, edited by Bruno Cugny, Errico Armandillo, Nikos Karafolas
Proc. of SPIE Vol. 10564, 1056433 · © 2012 ESA and CNES · CCC code: 0277-786X/17/\$18 · doi: 10.1117/12.2309102

Proc. of SPIE Vol. 10564 1056433-1

Mission Study of Up-link Laser Differential Absorption Sensing

Japan Aerospace Exploration Agency, Ibaraki, JAPAN
Yohei Satoh, Yoshikazu Chishiki, Daisuke Sakaizawa and Shiro Yamakawa

1. INTRODUCTION

Up-link Laser Differential Absorption Sensing: ULDAS, shown in Fig.1, is a new method to measure green house gas concentration with earth observation satellites. Although the measurement area is restricted in only small visible area of an optical ground station, ULDAS has outstanding features as followed:

- Faster: Easy to development, small size and small resource requirements to satellite system
- Better: High accuracy (CO₂ observation error of weighted column is <0.3% which corresponds to 1ppm error of atmospheric concentration)
- Cheaper: Simple system, small number of parts and no special parts

The flight segment of the ULDAS is able to be loaded on a marginal resource of green house effect observation satellites, such as Japanese GOSAT-series. In this paper, the feasibility study of the mission concept and field experiments are reported.

2. BASIC PRINCIPLE

Laser differential absorption sensing uses two laser beams as probes. They have slightly

different wavelengths, λ_{on} and λ_{off} as shown in Fig.2.

Fig.1 ULDAS image

Fig.2 λ_{on} and λ_{off}

We considered two methods to discriminate the probe beams. One method utilizes pulse lasers for the probe beams and discrimination between λ_{on}

Table 1 Trading off in laser sensing

Name	DIAL	-	-	ULDAS
Optical path (S: Satellite, G: Ground)	2way		1way	
	S→S	G→S→G	S→G	G→S
Observable Area	Global	Visible area from ground station		
On-board resource	Very big	Very small	Middle class	Small
Scale of Ground Station	Not needed	Very big	Big	Middle class
Cost	Very big	So-so	Nice	Nice
Total Score	Good	So-so	So-so	Good

and λ_{off} is made in time domain, as shown in Fig.3 (Pulse type light source). The receiver identifies λ_{on} and λ_{off} signals using pulse timing information.

In the other method, amplitude modulated (AM) CW beams are utilized as probes, and they are discriminated by difference between modulation frequencies as shown in Fig.4 (AM-CW type light source). The ground station has one type of the light sources. And in both cases, the equipment of ground station is consisted of shelf products.

Fig.3 Pulse type ULDAS light source

Fig.4 AM-CW type ULDAS light source

3. SYSTEM STUDY

Fig. 5 shows a schematic diagram of ULDAS onboard sensor. The sensor consists of optics, electronics of analog circuits and a controller. The sensor is applicable to the both type of light sources (pulse type and AM-CW

type). The required space, weight and power resource for satellite system are estimated to be small, as below:

- Optical system
 - Type: Telecentric optical system
 - Mass: < 1 kg
 - Size: $\phi 40 \times 150$ mm
 - Effective optical diameter: $\phi 3$ mm
 - FOV: ± 5 deg.
- Analog circuit & Controller:
 - Mass : < 2 kg
 - Size : $80 \times 120 \times 180$ mm
 - Power : < 10 W

Since the required resources are small, the ULDAS onboard sensor can be equipped on earth-observation satellites as piggy back payload.

Fig.5 Schematic diagram of ULDAS onboard sensor

Fig.6-1 ULDAS flight segment (BBM, Optical aperture side view)

Fig.6-2 ULDAS flight segment
(BBM, terminal board side view)

4. PROTOTYPING

The developed breadboard model (BBM) of ULDAS onboard sensor is shown in Fig.6. The architecture is the same as shown in Fig.5. This BBM consists of two units, i.e. the main unit and the optical unit. The size of main unit is $175.9 \times 185.2 \times 116.5 \text{ mm}^3$ and the size of optical unit is $\phi 48.0 \times 106.8 \text{ mm}^3$. The total weight is 3.2kg. We plan field experiments to demonstrate CO₂ observation with long optical path such as 10~20km with AM-CW type light source.

5. ESTIMATED ACCURACY OF OBSERVATION

Accuracy of observation with ULDAS is estimated under the following conditions:

- Satellite
 - Altitude: 660km
 - Attitude: Nadia pointing
- ULDAS flight segment
 - Band width(optical filter): 3.3nm
 - Optical transmission: 50%
 - Field of view(FOV): +/-5deg.
 - Integration time: 4s
 - NF at front end: 2.2dB
 - Band width(FFT channel): 30Hz
- Laser output from ground station
 - Type: AM-CW
 - Power: 10W(par one beam)
 - Spread angle: 0.06deg.
- Atmosphere transmission

- λ_{on} : 36%
- λ_{off} : 99%

In the worst case, the ground station is edge of FOV of ULDAS onboard sensor, the maximum distance between satellite and ground station is 662.2km. In this case, the beam diameter from ground station is estimated to be approx $\phi 690\text{m}$ at the position of the satellite. Received signal power fluxes are approx 34pW for λ_{on} and 92pW for λ_{off} , respectively. On the other hands, background light power ($\sim 5\text{nW}$) causes 0.4fW shot noise per one channel of FFT (30Hz band width). SNRs including background shot noise, signal shot noise, thermal noise and quantization noise, are estimated to approx. 640 for λ_{on} and 4700 for λ_{off} in four seconds integration time. Weather parameter: $\sqrt{(\partial N_{CO_2}/\partial T)^2 + (\partial N_{CO_2}/\partial P)^2 + (\partial N_{CO_2}/\partial U)^2}$ and wavelength parameter: $\sqrt{(\partial N_{CO_2}/\partial \lambda)^2}$ are estimated to approx 0.08% and 0.12% based on assumptions as follows:

- Temperature: $T < 2 \text{ K}_{RMS}$
- Atmospheric pressure: $P < 1 \text{ hPa}_{RMS}$
- Humidity: $U < 10 \%_{RMS}$
- Stability of signal light frequency:
 $\Delta \nu < 300 \text{ kHz}_{RMS}$

As a result, the observation accuracy of weighted column CO₂ is estimated to be approx 0.16%, which corresponds to 0.6ppm error of atmospheric concentration.

6. GROUND STATION DESIGN

The portability of the ULDAS ground station in the field is important to spread observable area. As a result, two functions are required for ground station systems.

Star calibration function: The ground station must calibrate its attitude using fixed stars to satisfy required setting accuracy of less than 0.03 degree, which is too strict to point a target satellite without self calibration.

Scanning and detecting function: Beam scanning and acquisition/tracking functions to point the

target satellite are required to the ground station. Because, the beam diameter of approx. $\phi 690\text{m}$ is relatively small in comparison to the accuracy of simple determination of satellite position such as using two line elements (TLE). Even if, there is high accuracy information of the target satellite position, such information is not always available for the field observation. Spiral scan method was studied to search the target satellite. Onboard LDs and corner cube reflectors can be considered to recognize that probe beams of ground station capture the target satellite.

7. CONCLUSION

Small and simple onboard green house gas observation system, ULDAS, has been studied. The feasibility of the onboard system and optical link were shown. The concept study of ground station system is also performed. Star calibration function and Scanning/detecting functions are required for the ground station system. The BBM of onboard system has been developed for field experiments.

In the future, drift of BBM output data and stray light tolerability will be estimated to show that ULDAS is able to work in orbit.

8. REFERENCE

- [1] Sugimoto N., Koga N., Matsui I., Sasano Y., Minato A., Ozawa K., Saito Y., Nomura A., Aoki T., Itabe T., et al. "Earth-satellite-Earth laser long-path absorption experiment using the Retro reflector in Space(RIS) on the Advanced Earth Observing Satellite(ADEOS)," J.Opt.A:Pure Appl.Opt., (1) 201-209, 1999
- [2] Daisuke SAKAIZAWA, Shuji KAWAKAMI, Masakatsu NAKAJIMA, "Initial airborne flight result of a weighted CO₂ column measurement using the 1.57 μm CO₂ LAS-DIAL"