International Conference on Space Optics—ICSO 2000

Toulouse Labège, France

5–7 December 2000

Edited by George Otrio

Three mirror anastigmat optical designs for ISRO's optical payloads

Saji Abraham, Amiya Biswas

International Conference on Space Optics — ICSO 2000, edited by George Otrio, Proc. of SPIE Vol. 10569 105691X · © 2000 ESA and CNES · CCC code: 0277-786X/17/\$18 · doi: 10.1117/12.2307912

Proc. of SPIE Vol. 10569 105691X-1

Three mirror anastigmat optical designs for ISRO's optical payloads

Saji Abraham, Amiya Biswas

*Optical Design and Fabrication Division/OptoMechanical Group/Sensors Development
Area/SPACE APPLICATIONS CENTER/Indian Space Research Organization
Saji_ak@hotmail.com*

The three mirror anastigmat (TMA) optical design consists of a primary mirror, a secondary mirror and a tertiary mirror.

The primary and tertiary mirrors are off axis mirrors. ISRO pioneered the use of this type of optical design for space use, being the first in the world to utilize the TMA for the panchromatic camera flown on board the IRS 1C and 1D satellites. ISRO has gained considerable experience with this type of optical design and will continue to use this design for several of the forthcoming optical payloads. After the successful launch and operationalization of the panchromatic camera payload, the TMA has evoked considerable interest among the leading international space agencies. The main advantages of this type of optical design over the conventional two mirror systems are:

- 1. There is no obscuration of the incoming beam resulting in superior energy collection.
- 2. The image quality is vastly superior, especially at large fields of view
- 3. The field of view of these type of optical systems is much larger
- 4. The reduced sensitivity of alignment of the mirrors.

This paper presents the optical designs of three ISRO satellite payloads which utilize the three mirror anastigmat.