PROCEEDINGS OF SPIE

SPIDigitalLibrary.org/conference-proceedings-of-spie

Front Matter: Volume 11665

, "Front Matter: Volume 11665," Proc. SPIE 11665, Fiber Lasers XVIII:
Technology and Systems, 1166501 (22 April 2021); doi: 10.1117/12.2596598

SPIE.

Event: SPIE LASE, 2021, Online Only

PROCEEDINGS OF SPIE

Fiber Lasers XVIII: Technology and Systems

Michalis N. Zervas
Cesar Jauregui-Misas
Editors

6–11 March 2021
Online Only, United States

Sponsored by
NKT Photonics A/S (Denmark)
Active Fiber Systems GmbH (Germany)

Published by
SPIE

Volume 11665

Proceedings of SPIE 0277-786X, V. 11665

SPIE is an international society advancing an interdisciplinary approach to the science and application of light.

Fiber Lasers XVIII: Technology and Systems, edited by Michalis N. Zervas,
Cesar Jauregui-Misas, Proc. of SPIE Vol. 11665, 1166501 · © 2021 SPIE
CCC code: 0277-786X/21/\$21, doi: 10.1117/12.2596598

Proc. of SPIE Vol. 11665 1166501-1

The papers in this volume were part of the technical conference cited on the cover and title page. Papers were selected and subject to review by the editors and conference program committee. Some conference presentations may not be available for publication. Additional papers and presentation recordings may be available online in the SPIE Digital Library at SPIDigitalLibrary.org.

The papers reflect the work and thoughts of the authors and are published herein as submitted. The publisher is not responsible for the validity of the information or for any outcomes resulting from reliance thereon.

Please use the following format to cite material from these proceedings:

Author(s), "Title of Paper," in *Fiber Lasers XVIII: Technology and Systems*, edited by Michalis N. Zervas, Cesar Jauregui-Misas, Proc. of SPIE 11665, Seven-digit Article CID Number (DD/MM/YYYY); (DOI URL).

ISSN: 0277-786X

ISSN: 1996-756X (electronic)

ISBN: 9781510641655

ISBN: 9781510641662 (electronic)

Published by

SPIE

P.O. Box 10, Bellingham, Washington 98227-0010 USA

Telephone +1 360 676 3290 (Pacific Time)

SPIE.org

Copyright © 2021 Society of Photo-Optical Instrumentation Engineers (SPIE).

Copying of material in this book for internal or personal use, or for the internal or personal use of specific clients, beyond the fair use provisions granted by the U.S. Copyright Law is authorized by SPIE subject to payment of fees. To obtain permission to use and share articles in this volume, visit Copyright Clearance Center at copyright.com. Other copying for republication, resale, advertising or promotion, or any form of systematic or multiple reproduction of any material in this book is prohibited except with permission in writing from the publisher.

Printed in the United States of America by Curran Associates, Inc., under license from SPIE.

Publication of record for individual papers is online in the SPIE Digital Library.

**SPIE. DIGITAL
LIBRARY**

SPIDigitalLibrary.org

Paper Numbering: A unique citation identifier (CID) number is assigned to each article in the Proceedings of SPIE at the time of publication. Utilization of CIDs allows articles to be fully citable as soon as they are published online, and connects the same identifier to all online and print versions of the publication. SPIE uses a seven-digit CID article numbering system structured as follows:

- The first five digits correspond to the SPIE volume number.
- The last two digits indicate publication order within the volume using a Base 36 numbering system employing both numerals and letters. These two-number sets start with 00, 01, 02, 03, 04, 05, 06, 07, 08, 09, 0A, 0B ... 0Z, followed by 10-1Z, 20-2Z, etc. The CID Number appears on each page of the manuscript.

Contents

HIGH POWER FIBER SOURCES

- 11665 05 **Single-mode 3kW Ytterbium fiber amplifier with diffraction-limited divergence in all-fiber format and compact modular package** [11665-1]
- 11665 06 **4 kW single-mode laser output assisted by a double-tapered double-clad fiber** [11665-2]
- 11665 07 **Polarization maintaining, narrow linewidth fiber laser with >1kW output power using a novel dual sine and noise modulation for enhanced SBS suppression** [11665-3]
- 11665 08 **All fiber monolithic highly multimode 4.03 kW fiber laser** [11665-4]
- 11665 09 **High-power/energy large mode area tapered fiber amplifiers** [11665-5]

MID-IR FIBER LASERS

- 11665 0B **1.1 kW, beam-combinable thulium doped all-fiber amplifier** [11665-7]
- 11665 0D **2 μm ultra-low relative intensity noise and frequency noise of single frequency fiber laser for next-generation gravitational wave detectors** [11665-9]
- 11665 0E **A 1720-nm ring-cavity Tm-doped fiber laser with optimized output coupling** [11665-10]
- 11665 0F **Novel highly efficient in-band pump wavelengths for Ho-doped fiber amplifiers** [11665-11]

NONLINEAR EFFECTS IN FIBER LASERS

- 11665 0G **SBS suppression techniques in high-power, narrow-linewidth fiber amplifiers (Invited Paper)** [11665-12]
- 11665 0H **Increasing the SBS threshold in single-mode step-index optical fiber by design of highly multimode acoustic profile** [11665-13]
- 11665 0J **Generation of large optical bistability in a single-frequency Tm-doped fiber laser using saturable absorber** [11665-15]
- 11665 0L **Spatial beam nonlinear control with multimode GRIN fiber amplifiers** [11665-17]

ER-YB AND RAMAN FIBER SOURCES

11665 OM	Single-mode Er/Yb fiber MOPA at 1562nm with 302W power and 56% optical efficiency [11665-18]
11665 OO	Two-stage fully monolithic single-frequency Er:Yb fiber amplifier at 1556 nm for next-generation of gravitational wave detectors [11665-20]
11665 OP	Progress on high power Raman fiber lasers at 1.48 and 1.7 μm [11665-21]
11665 OQ	Tunable random distributed feedback Raman fiber laser with Fourier spectral shaper for feedback control [11665-22]

TRANSVERSE MODAL INSTABILITIES IN FIBER AMPLIFIERS I

11665 OS	STRS in Yb-doped polarisation-maintaining fiber amplifier (Invited Paper) [11665-24]
11665 OT	Low-threshold mode instability in few-mode Yb³⁺-doped fiber amplifiers: an overview of recent results (Invited Paper) [11665-25]
11665 OU	Modal instability in two-mode optical fiber amplifiers [11665-26]
11665 OV	Mitigation of transverse mode instability in polarization maintaining, high-power fiber amplifiers [11665-27]
11665 OW	Mitigation of transverse mode instability through a dynamic modification of the inversion in high-power fiber amplifiers [11665-28]
11665 OX	Backward transverse mode instability? [11665-29]

TRANSVERSE MODAL INSTABILITIES IN FIBER AMPLIFIERS II

11665 OY	Study of seeding mechanisms of TMI with spatially and temporally resolved imaging (Invited Paper) [11665-30]
11665 OZ	Dynamic BPM model for transverse modal instability [11665-31]
11665 10	BPM study of pump modulation effects on mode instability [11665-32]
11665 12	Characterization of transverse mode instability in fiber-laser systems using a position-sensitive detector [11665-34]

ULTRAFAST FIBER LASERS

- 11665 13 **Megawatt single mode femtosecond erbium fiber laser** [11665-35]
- 11665 15 **12 nJ, 250 fs pulses from an all-PM-fiber laser oscillator** [11665-37]
- 11665 17 **Simple design for high energy femtosecond tapered double clad fiber amplifier** [11665-39]
- 11665 18 **Optimization of Mamyshev regenerator for ultrafast pulse generation** [11665-40]

PULSED FIBER LASERS AND LASER DYNAMICS

- 11665 19 **Characterization of the dynamics of an FDML laser during closed-loop cavity length control** [11665-41]
- 11665 1A **A detailed analysis of the coherence and field properties of an FDML laser by time resolved beat signal measurements** [11665-42]
- 11665 1B **High-power single-frequency narrow-linewidth nanosecond pulsed fiber laser based on triangle-shaped pulse** [11665-43]
- 11665 1D **High-power and pulse energy picosecond narrow linewidth laser system based on tapered fiber amplifier for second harmonic generation** [11665-45]

COHERENT BEAM COMBINATION FIBER LASERS

- 11665 1G **100 fs pulses directly from a kW-class mJ-level ytterbium-doped fiber CPA laser system (Best Student Paper Award)** [11665-48]
- 11665 1H **61 channels coherent beam combining femtosecond digital laser** [11665-49]
- 11665 1I **Target-in-the-loop frequency-tagging coherent combining of 7 fiber lasers up to 1 km range** [11665-50]
- 11665 1K **PISTIL interferometry: a modular, plug-and-play metrology mean for diagnosis of coherently combined laser arrays** [11665-52]

NOVEL FIBER SOURCES

- 11665 1L **Low noise spliceless single-frequency chirally-coupled-core all-fiber amplifier** [11665-53]
- 11665 1N **Mode-locked seven-core multicore photonic crystal fiber laser with a saturable absorber** [11665-55]

NOVER FIBERS FOR LASER APPLICATIONS

- 11665 1Q **Optimizing the design of coherently combined multicore fiber amplifiers** [11665-58]
- 11665 1R **Fabrication of silica leakage channel microstructured optical fiber based on 3D printed preforms** [11665-59]
- 11665 1S **Simplified manufacturing of advanced microstructured fibers for laser applications** [11665-60]
- 11665 1T **Large mode area double-clad ytterbium-doped tapered fiber with low birefringence** [11665-61]
- 11665 1U **Spectrally selective fundamental core mode suppression in an optical fiber with absorbing rods** [11665-62]
- 11665 1V **Design of large mode area all-solid anti-resonant fiber** [11665-63]

SPECIAL SESSION II: TMI IN INDUSTRY

- 11665 20 **Materials for TMI mitigation (Invited Paper)** [11665-75]

POSTER SESSION

- 11665 23 **Linewidth-tunable single-frequency triangle-shaped nanosecond-pulsed fiber laser immune to SPM-induced spectral broadening** [11665-64]
- 11665 24 **Multi-watt broadband wavelength tunable polarization maintaining Tm-doped fiber laser module** [11665-65]
- 11665 26 **Effect of the thermal rise time of diode pump modules on the cold-start turn-on time of a Yb-doped fiber amplifier** [11665-67]
- 11665 27 **Femtosecond fiber oscillator with adjustable central wavelength and bandwidth optimized for high power amplification** [11665-68]
- 11665 28 **Dual-bandpass filter for self-starting mode-locking in all-PM NALM-based fiber laser** [11665-69]
- 11665 29 **High performance +23 dBm miniature PM Ho-doped fiber amplifier at 2100 nm** [11665-70]