PROCEEDINGS OF SPIE

SPIDigitalLibrary.org/conference-proceedings-of-spie

Front Matter: Volume 6651

, "Front Matter: Volume 6651," Proc. SPIE 6651, Photovoltaic Cell and Module Technologies, 665101 (16 October 2007); doi: 10.1117/12.773730

SPIE.

Event: Solar Energy + Applications, 2007, San Diego, California, United States

PROCEEDINGS OF SPIE

Photovoltaic Cell and Module Technologies

Bolko von Roedern
Alan E. Delahoy
Editors

27–28 August 2007
San Diego, California, USA

Sponsored and Published by
SPIE

Volume 6651

Proceedings of SPIE, 0277-786X, v. 6651

SPIE is an international society advancing an interdisciplinary approach to the science and application of light.

The papers included in this volume were part of the technical conference cited on the cover and title page. Papers were selected and subject to review by the editors and conference program committee. Some conference presentations may not be available for publication. The papers published in these proceedings reflect the work and thoughts of the authors and are published herein as submitted. The publisher is not responsible for the validity of the information or for any outcomes resulting from reliance thereon.

Please use the following format to cite material from this book:

Author(s), "Title of Paper," in *Photovoltaic Cell and Module Technologies*, edited by Bolko von Roedern, Alan E. Delahoy, Proceedings of SPIE Vol. 6651 (SPIE, Bellingham, WA, 2007) Article CID Number.

ISSN 0277-786X
ISBN 9780819467997

Published by

SPIE

P.O. Box 10, Bellingham, Washington 98227-0010 USA
Telephone +1 360 676 3290 (Pacific Time) · Fax +1 360 647 1445
SPIE.org

Copyright © 2007, Society of Photo-Optical Instrumentation Engineers

Copying of material in this book for internal or personal use, or for the internal or personal use of specific clients, beyond the fair use provisions granted by the U.S. Copyright Law is authorized by SPIE subject to payment of copying fees. The Transactional Reporting Service base fee for this volume is \$18.00 per article (or portion thereof), which should be paid directly to the Copyright Clearance Center (CCC), 222 Rosewood Drive, Danvers, MA 01923. Payment may also be made electronically through CCC Online at copyright.com. Other copying for republication, resale, advertising or promotion, or any form of systematic or multiple reproduction of any material in this book is prohibited except with permission in writing from the publisher. The CCC fee code is 0277-786X/07/\$18.00.

Printed in the United States of America.

Publication of record for individual papers is online in the SPIE Digital Library.

SPIEDigitalLibrary.org

Paper Numbering: Proceedings of SPIE follow an e-First publication model, with papers published first online and then in print and on CD-ROM. Papers are published as they are submitted and meet publication criteria. A unique, consistent, permanent citation identifier (CID) number is assigned to each article at the time of the first publication. Utilization of CIDs allows articles to be fully citable as soon they are published online, and connects the same identifier to all online, print, and electronic versions of the publication. SPIE uses a six-digit CID article numbering system in which:

- The first four digits correspond to the SPIE volume number.
- The last two digits indicate publication order within the volume using a Base 36 numbering system employing both numerals and letters. These two-number sets start with 00, 01, 02, 03, 04, 05, 06, 07, 08, 09, 0A, 0B ... 0Z, followed by 10-1Z, 20-2Z, etc.

The CID number appears on each page of the manuscript. The complete citation is used on the first page, and an abbreviated version on subsequent pages. Numbers in the index correspond to the last two digits of the six-digit CID number.

Contents

- v Conference Committee
- vii *The solar-hydrogen economy: an analysis (Plenary Paper) [6650-101]*
W. D. Reynolds, Eco-Engineers, Inc. (USA)
- xxix *Solar hydrogen production by tandem cell system composed of metal oxide semiconductor film photoelectrode and dye-sensitized solar cell (Plenary Paper) [6650-102]*
H. Arakawa, C. Shiraishi, M. Tatamoto, H. Kishida, D. Usui, A. Suma, A. Takamisawa, T. Yamaguchi, Tokyo Univ. of Science (Japan)

SESSION 1 SOLAR CELL OPERATION

- 6651 02 **Detailed balance: lifetimes and efficiencies (Invited Paper) [6651-01]**
H. J. Queisser, Max-Planck-Institute for Solids (Germany)
- 6651 03 **Efficiency enhancement in concentrator solar cells by dielectric micro-concentrators [6651-02]**
O. Korech, J. M. Gordon, E. A. Katz, D. Feuermann, Ben-Gurion Univ. of the Negev (Israel); N. Eisenberg, Jerusalem College of Technology (Israel)
- 6651 04 **Performance analysis of $\text{CuIn}_{1-x}\text{Ga}_x\text{S}_2$ (CIGS2) thin film solar cells based on semiconductor properties [6651-03]**
N. G. Dhere, A. H. Jahagirdar, S. R. Ghongadi, Florida Solar Energy Ctr. (USA)
- 6651 05 **Temperature dependence of Si-based thin film solar cells near phase boundary [6651-04]**
K. Sriprapha, I. A. Yunaz, S. Y. Myong, A. Yamada, M. Konagai, Tokyo Institute of Technology (Japan)
- 6651 06 **Diffraction and energy selective photonic crystals for thin-film tandem solar cells [6651-05]**
A. Bielawny, P. T. Miclea, R. B. Wehrspohn, Univ. of Halle-Wittenberg (Germany); A. von Rhein, Univ. of Paderborn (Germany); C. Rockstuhl, M. Lisca, F. L. Lederer, Friedrich-Schiller-Univ. Jena (Germany); B. Lange, R. Zentel, Univ. Mainz (Germany); R. Carius, Research Ctr. Jülich GmbH (Germany)

SESSION 2 SOLAR CELL MATERIAL/PROCESS CHARACTERIZATION

- 6651 07 **Analysis and optimization of thin film photovoltaic materials and device fabrication by real time spectroscopic ellipsometry (Invited Paper) [6651-06]**
J. Li, J. A. Stoke, Univ. of Toledo (USA); N. J. Podraza, Univ. of Toledo (USA) and The Pennsylvania State Univ. (USA); D. Sainju, A. Parikh, X. Cao, H. Khatri, Univ. of Toledo (USA); N. Barreau, LAMP, Univ. of Nantes (France); S. Marsillac, X. Deng, R. W. Collins, Univ. of Toledo (USA)

- 6651 08 **A reliable optical method for in situ process control for deposition of Cu(In,Ga)Se₂ thin layers for photovoltaics** [6651-07]
R. Hesse, R. Caballero, D. Abou-Ras, T. Unold, C. A. Kaufmann, H.-W. Schock, Hahn-Meitner-Institut Berlin (Germany)

SESSION 3 SOLAR CELL MATERIAL/CELL PROCESSING

- 6651 0B **Textured, doped, ZnO thin films produced by a new process for a-Si and CIGS solar cell application** [6651-10]
S. Y. Guo, L. Sahoo, Energy Photovoltaics, Inc. (USA); G. Sosale, McGill Univ. (Canada); A. E. Delahoy, Energy Photovoltaics, Inc. (USA)
- 6651 0C **PECVD deposition of a-Si:H and μ c-Si:H using a linear RF source** [6651-11]
B. B. Van Aken, C. Devilee, M. Dörenkämper, M. Geusebroek, M. Heijna, J. Löffler, W. J. Soppe, ECN Solar Energy (Netherlands)
- 6651 0D **Correlation between the photoconductivity and the nanostructure of hot-wire deposited silicon-germanium alloys analyzed by anomalous small-angle x-ray scattering** [6651-12]
G. Goerigk, Institut für Festkörperforschung, Forschungszentrum Jülich (Germany); D. L. Williamson, Colorado School of Mines (USA)
- 6651 0F **Modeling of Si-based solar cells with V-grooved surface texture by Crosslight APSYS** [6651-14]
Y. G. Xiao, M. Lestrade, Z. Q. Li, Z. M. S. Li, Crosslight Software, Inc. (Canada)

SESSION 4 PV MODULE/MANUFACTURING ISSUES

- 6651 0G **Electrical and photovoltaic properties through a large multicrystalline Si ingot** [6651-15]
S. Martinuzzi, I. Périchaud, O. Palais, D. Barakel, Univ. Paul Cezanne-Aix (France); M. Gauthier, Photowatt Int. SA (France)
- 6651 0H **Influence of the laser parameters on the patterning quality of thin-film silicon modules** [6651-16]
S. Haas, A. Gordijn, G. Schöpe, B. E. Pieters, H. Stiebig, Forschungszentrum Jülich (Germany)

POSTER SESSION

- 6651 0L **Fabrication of Cu(In,Al)Se₂ solar cells by three-stage evaporation process** [6651-20]
T. Hayashi, T. Minemoto, T. Araki, H. Takakura, Ritsumeikan Univ. (Japan)

Author Index

Conference Committee

Symposium Chair

Ravi Durvasula, Lightfleet Corporation (USA)

Conference Chairs

Bolko von Roedern, National Renewable Energy Laboratory (USA)

Alan E. Delahoy, Energy Photovoltaics, Inc. (USA)

Program Committee

Robert W. Collins, Jr., University of Toledo (USA)

Ravi Durvasula, Lightfleet Corporation (USA)

Alan L. Fahrenbruch, Stanford University (USA)

Sheyu Guo, Energy Photovoltaics, Inc. (USA)

Steven G. Hegedus, University of Delaware (USA)

Martha C. Lux-Steiner, Hahn-Meitner-Institut Berlin (Germany)

James R. Sites, Colorado State University (USA)

Session Chairs

- 1 Solar Cell Operation
 Alan E. Delahoy, Energy Photovoltaics, Inc. (USA)
- 2 Solar Cell Material/Process Characterization
 Bolko von Roedern, National Renewable Energy Laboratory (USA)
- 3 Solar Cell Material/Cell Processing
 Robert W. Collins, Jr., University of Toledo (USA)
- 4 PV Module/Manufacturing Issues
 Neelkanth G. Dhere, University of Central Florida (USA)

The Solar-Hydrogen Economy - An Analysis

Warren D. Reynolds CEO, Eco-Engineers, Inc
Suite 87, 2700 E. Valley Pkwy, Escondido, CA 92027

ABSTRACT

The 20th Century was the age of the Petroleum Economy while the 21st Century is certainly the age of the Solar-Hydrogen Economy. The global Solar-Hydrogen Economy that is now emerging follows a different logic. Under this new economic paradigm, new machines and methods are once again being developed while companies are restructuring.

The Petroleum Economy will be briefly explored in relation to oil consumption, Hubbert's curve, and oil reserves with emphasis on the "oil crash". Concerns and criticisms about the Hydrogen Economy will be addressed by debunking some of the "hydrogen myths".

There are three major driving factors for the establishment of the Solar-Hydrogen Economy, i.e. *the environment*, *the economy* with the coming "oil crash", and *national security*.

The New Energy decentralization pathway has developed many progressive features, e.g., reducing the dependence on oil, reducing the air pollution and CO₂. The technical and economic aspects of the various Solar-Hydrogen energy options and combinations will be analyzed.. A proposed 24-hour/day 200 MWe solar-hydrogen power plant for the U.S. with selected energy options will be discussed.

There are fast emerging Solar Hydrogen energy infrastructures in the U.S., Europe, Japan and China. Some of the major infrastructure projects in the transportation and energy sectors will be discussed. The current and projected growth in the Solar-Hydrogen Economy through 2045 will be given.

Table of Contents

INTRODUCTION	2
PETROLEUM ECONOMY.	3
HYDROGEN MYTHS	5
SOLAR-HYDROGEN ECONOMY	5
SOLAR-HYDROGEN POWER PLANTS	7
SOLAR POWER CONVERSION EFFICIENCIES	9
EMERGING U.S. SOLAR-HYDROGEN ENERGY INFRASTRUCTURE. . .	10
EMERGING INTERNATIONAL SOLAR-HYDROGEN INFRASTRUCTURE	14
CURRENT AND PROJECTED GROWTH IN THE SOLAR-HYDROGEN ECONOMY	16
BIBLIOGRAPHY.	18

Key words: Hydrogen Economy, Solar Economy, solar energy, wind power, peak oil, solar PV, solar conversion, energy conversion, solar steam, solar Stirling-engine.

INTRODUCTION

The 20th century was the age of the Petroleum Economy while the 21st century and beyond is certainly the age of the Solar-Hydrogen Economy. The global Solar-Hydrogen Economy that is now emerging follows a different logic where new machines and methods are once again being invented while companies are restructured. A growing number of mainstream energy companies including Shell and GE are adding new divisions and investing in solar-based technologies¹.

There is a wealth of information on the rapidly growing Solar-Hydrogen Economy. The areas that I will cover include:

- Petroleum Economy and Coming “Oil Crash”
- Hydrogen Myths
- Solar-Hydrogen Economy
 - Factors that drive us to the Solar-Hydrogen Economy
- Solar-Hydrogen Power Plants
- Solar Power Conversion Efficiencies
- Emerging U.S. Solar-Hydrogen Energy Infrastructures
- Emerging International Solar-Hydrogen Energy Infrastructure
- U.S. And World Growth in Solar-Hydrogen Economy

We will briefly inspect the Petroleum Economy and expected “oil crash” which is one of the factors that drive us to the Solar-Hydrogen Economy. We will also look at the other factors.

The main section is the New Energy options and how they are serially dependent. A planned 24-hour/day 200 MWe solar hydrogen power plant will be used as an example.

Further, we will look at the emerging New Energy infrastructures in the U.S. and around the world. Just as a note, the U.S. is lagging behind Europe and Japan in converting to the Solar-Hydrogen Economy. Finally, I will inspect an estimated time-line for the U.S. conversion to the new economy. As a reference and starting point, let us ask the question:

What is the world’s total consumption of energy from different sources ?

In 2006, the world’s annual energy consumption grew 4.8% to 431×10^{15} BTUs. This rate of growth is estimated to continue for the next 10 years. Petroleum makes up more than 1/3 of the energy consumed mainly for transportation as shown below. If wind power’s world growth continues as expected, it will surpass nuclear power in three years as we shall see later. The world’s different sources of energy can be broken down as follows^{2,5,14}:

Petroleum	34.3%
Coal	25.1%
Natural gas	20.9%
Nuclear	6.5%
Renewables	4.8%
wind	
solar	
hydroelectric	
geothermal	
tidal	
biomass	

Enormous amounts of carbon-free energy will be required during the coming decades in order to stabilize the atmospheric CO₂ to acceptable levels. Solar energy is by-far the largest source of non-carbonaceous energy, globally, and can be used to produce both electricity and fuels²

PETROLEUM ECONOMY

What effect will “peak oil” have on the U.S. and World Economies ?

In 1957, Dr. M. King Hubbert, a U.S. geophysicist working for Shell Oil, developed a method for predicting the lifetime of an oil field from early oil production data^{12,13,15,16,23}.

Figure 1 illustrates Hubbert’s curve for the oil production output for all of the U.S. oil fields. As you can see, it is a Gaussian-shaped curve. Back in 1957, Dr. Hubbert predicted that the U.S. oil production would peak in 1970. From the Gaussian-curve, U.S. oil production *did peak in 1970*. It has been in decline since that time. Since 1970, we have had to increase our dependence on foreign oil shown by the blue line. The Prudhoe Bay oil discovery in 1985 just showed a small peak and it, too, has declined 45% from 1987 to 2007²⁴.

Figure 1. U. S. Oil Production from 1920-2006

In Figure 2 on the next page, we have another example of Hubbert’s Gaussian curve applied to Norway’s total oil production from 1970 and projected through to 2030. Its oil production *peaked* in 2001 followed by a decline. All the production data up to 2007 are shown as blue points. It follows the Gaussian curve very closely. I believe that this confirms Mr. Hubbert’s theorem²⁵.

Figure 2. Norway's Oil Production and Forecast

In Figure 3 below, the world's oil production also shows a Gaussian curve with peak total production about 2015. This curve is a summary of the oil production of 42 non-OPEC countries and the 7 major OPEC countries. The 42 countries produce 47% of the world's oil while 53% is produced by the OPEC nations. All of the 42 non-OPEC countries oil production have peaked before 2007. China's major oil field peaked in 2000²⁸:

Figure 3. World's Annual Oil Production and Oil Demand

The cross hatch area in Figure 3 is the shortfall between the demand line as represented by the EIA forecast 2006 and the blue production curve. This shows the increasing oil shortage from about 2009 and following years. This world oil shortage ("oil crash") converts into an ever increasing oil price from the current \$62/bbl to more than \$100/bbl by 2010. I would expect the price of gasoline in the U.S. to increase to over \$6/gallon by 2010. In Europe in 2006, it was already \$7/gallon in Amsterdam. Consequently, the "oil crash" would destabilize the economies of the world resulting in a deep recession and create a surge toward the Solar-Hydrogen Economy⁶⁻⁸.

The oil companies' geologists have searched the world over for oil and none has been found to equal the Saudi fields. The recent (2007) oil discoveries in the Gulf and elsewhere are just a drop in the bucket compared to the Saudi fields. Thus, Hubbert's curve shown in blue above will not change³⁰.

HYDROGEN MYTHS

What are some of the concerns and criticisms of the Hydrogen Economy²⁹ ?

MYTH #1

“The Hindenburg disaster was caused by a hydrogen explosion”

Not true. An electrostatic charge accumulated in the silk undercoating and ignited the cotton fabric outer-coating that was composed of a cellulose nitrate polymer mixed with high levels of aluminum powder with iron oxide^{29,47}.

Dr. Addison Bain, a NASA hydrogen expert, has spent six years investigating this disaster. From all his research on the eyewitnesses' accounts, the 1937 newsreel movie, testing a small section of original unburned outer blimp fabric, documents at the Hindenburg museum, and reconstructing a miniature blimp, Dr. Bain was able to re-create the chain-of-events that triggered the fire. This gave proof that the Hindenburg disaster was initiated by electro-static charge and the resulting outer-covering fire followed by the H₂ fire. From the Hindenburg museum documents, he found the laboratory notebook and test results and photos conducted by the German scientists in 1934. The German tests confirmed Dr. Bain's same tests on the Hindenburg fabric material. As a note, a mixture of an aluminum powder and flammable polymer is a recipe for rocket fuel.

MYTH #2

“A whole hydrogen industry would need to be developed from scratch”

Not true. It is already a large mature global industry with hydrogen used in many different industries. About 5% of the U.S. natural gas goes for H₂ production from which 45% of that H₂ is used in oil refineries. The H₂ industry has a >50 year safety record. The current hydrogen usage in the Solar-Hydrogen Economy is now one of local decentralized generation.

MYTH #3

“We lack a safe and affordable way to store H₂ in autos”

Not true. In 2002, GM tested their 3-layer composite 10,000 psi tank. It is extremely rugged that survived crash tests that flatten steel cars and shred gasoline tanks. These tanks met strict European and U.S. safety standards. The 10-gallon tank holds 12 kg H₂ for 300 miles

MYTH #4

“Compressing H₂ for auto storage tanks takes too much energy”

Not true. Current water electrolyzers generate H₂ directly at 10,000 psi without compressors

SOLAR-HYDROGEN ECONOMY

What are the factors driving us to the Solar-Hydrogen Economy¹ ?

- *Our Environment*, i.e., global warming and air pollution
- *Our Economy*, i.e., coming “Oil Crash”
- *Our National Security*, i.e., geopolitical problems in Middle East

The global warming debate is over due to the 2007 report from the International Panel on Climate Change. Global warming is caused by several factors among which is mankind’s generation of carbon dioxide. Since the 1990's, the high levels of air pollution in the U.S. and Europe have caused more than 30,000 deaths per year to those who were already throat and lung impaired. The U.S. and Europeans’ dependence on foreign oil is a growing concern due to the conflicts in the Middle East¹.

There are a number of methods for converting and using solar energy. What are some of the Solar-Hydrogen Energy conversion options ?

- Wind power
- Solar-steam
- PV cells
- Solar Stirling engine
- Solar-thermoelectric
- Fuel cell
- Tidal - thermal and motion
- Solar-Compressed air
- Direct H₂ Combustion
- Biomass ?
- Nuclear power ?

As shown above, in the New Solar Economy, we have a number of options for generating, storing and conversion of electricity. As far as biomass and nuclear power is concerned, some solar energy advocates have included them in their list. We will explore these two energy options in detail^{3,19,31}.

Since biomass is a renewable energy source, why shouldn't it be included in the Solar-Hydrogen Options ?

The advantage that advocates cite is the fact that whether it is burned directly or converted to fuel ethanol all the CO₂ generated is taken up by new growing plants with a net zero accumulation. However, what they don't tell you is the fact that the CO₂ has a long atmospheric half-life of greater than 10 years and there is a net secular accumulation of CO₂ that adds to the global warming. The other disadvantage is that the U.S. does not have sufficient crop-land to generate all the needed bioethanol for all of our 250 million autos⁵.

Why shouldn't nuclear power be included in the Solar-Hydrogen Energy options ?

As recently as the 1970's, it was universally agreed that nuclear power was the energy source for the future. It was anticipated in the 70's that thousands of these would be built with capacities as high as 4,000 MW according to the International Atomic Energy Agency^{1,17,18}.

The previous 10 years (1970-1980) had been marked by frequent technical mishaps, serious accidents, huge cost escalations and a rapid decline in public acceptance of nuclear power.

Since 1978, over 18 European countries have voted to oppose, phase-out or stop nuclear programs. Today, nuclear power has fallen far short of expectations. Just 343 gigawatts of nuclear power are actually in use, which is <1/10th of the amount expected¹.

In the late 1980s-early 90s, the Three-Mile Island, Chernobyl and Monju breeder (Japan) nuclear accidents testify that the use of nuclear power is not a viable option for the future. In addition, the high cost of nuclear generation of electricity and today’s high cost of nuclear plant construction are no longer economically attractive^{11,17}.

The many reasons for the collapse of nuclear power systems include¹:

- safety problems
- inability to dispose of nuclear waste
- potential uncontrolled proliferation of nuclear materials in the hands of terrorists
- highest cost for generating electricity (11.4-14.5 cents/kWhr) of all fossil fuels and most all of the renewable energy sources.
- during the period 1985-2007, there was a huge cost escalation from \$1 billion to more than \$9 billion for the same size nuclear plant

SOLAR-HYDROGEN POWER PLANTS

What is the general lay out of a 24-hour/day solar-hydrogen power plant ?

The structuring of a 24-hour/day solar-hydrogen power plant for the conversion of the sun’s energy into electric power for both day and night use encompasses three consecutive sections or units. These three phases or units can be designated as “A-B-C”. The “A” component or unit is used to convert the sun’s energy into electric power either directly or indirectly, i.e., thermally. The “B” unit is the storage of some of the sun’s converted electric energy for night time use. The “C” unit is the conversion of the stored energy back into electric power for night time use for the power grid.

TABLE I. Solar Energy Options

<u>“A” OPTIONS</u>	<u>“B” OPTIONS</u>	<u>“C” OPTIONS</u>
Energy Conversion	Energy Storage	Stored Energy Conversion
<ul style="list-style-type: none">• PV cell• Solar Stirling engine• Solar-steam• Wind power• Thermoelectric• Solar-air compression	<ul style="list-style-type: none">• Hydrogen• Compressed air• Batteries• Capacitors• Flywheel	<ul style="list-style-type: none">• Hydrogen-HICE co-gen-Fuel cell-Combustion co-gen• Compressed air turbine co-gen.

How are the combinations selected for structuring a 24-hour/day solar power plant ?

As shown above, there are many options for each of the consecutive A-B-C units. For example, we could select *PV cell - compressed air - air turbine* as the three units. Another example would be *solar Stirling engine - hydrogen -*

combustion co-generation. However, selection of each correct separate unit and its compatibility, i.e., sizing, with each of the succeeding units must be taken into account. The overall efficiency of the selected consecutive A-B-C units must also be maximized while the economic viability of these same three units must be minimized. Thus, the pathway for achieving the maximum efficiency at minimum cost is a complex task under current technology. However, as technology improves, new innovations develop, and price reductions occur over time then it becomes even more obvious what that pathway will be in the future.

There are a number of “A” options for the conversion of the sun’s energy either directly or indirectly into electric power. For the direct conversion of solar energy into electric power, there are only two major methods. The indirect conversion of solar energy can also be accomplished by at least three methods. Some of these methods are commercially available with prices falling.

Once the electricity is generated from the sun then some of that energy can be used for the grid electric power while the balance of that energy is stored and reclaimed for night time use from the “B” unit. The “B” unit can be configured by three major different approaches. The storage of electric energy can be done as either chemical or physical potential energy. For large solar power plants, the most useful form for energy storage is hydrogen.

For the “C” unit or conversion of stored power back into electricity can be accomplished by a number of commercially available systems. Stationary hydrogen fuel cells have been used in a number of small <5 MWe applications. GE is developing a hydrogen-turbine power generator.

What is the estimated cost and land area for the different 24-hour/day 200 MWe solar-hydrogen power plants using the solar options ?

Table II. Estimated Costs for Various 24-hr/day 200 MWe Solar-Hydrogen Power Plant^{22,31-33,38,44,50}

TOTAL A-B-C SOLAR POWER SYSTEM	Estimated Cost (2010) without land cost	Required Land Area
Wind Farm*	\$ 333.86 million	85 Acres
Concentrated Solar-Stirling Engine*	\$370.06	1,200
Concentrated Solar-Compressed Air (no hydrogen)	\$340.26	1,100
Solar-Steam/Tesla turbine*	\$343.86	1,200
Concentrated Solar-PV Cells*	\$734.90	1,500

* Includes B and C units for hydrogen electrolysis production, storage, and combustion back to electric power (\$133.86 million). The concentrated solar-compressed air does not require H₂ for energy storage as the compressed air can be stored in caverns below ground and retrieved at night to generate electricity for the grid^{32,35}

The first four 24-hr/day solar-hydrogen systems costs are approximately *1/6th the cost* of a 200 MWe nuclear plant³².

SOLAR POWER CONVERSION EFFICIENCIES

Solar conversion efficiency is important. Selection of a group of energy conversion units for an A-B-C combination to make a total system is based on the conversion efficiency of each unit whether it is solar-into-electricity or hydrogen-into-electricity.

Which of the different solar power converters has the highest efficiency ?

From the previous A-B-C options list of solar power converters, stored power generation and conversion, a number of these solar power converters, their conversion efficiencies (2007) and their theoretical conversion efficiencies' limits, are included in the table below:

Table III. Solar Energy Conversion Efficiencies^{4,20,21, 41,42,53,64,65,67,69}

SOLAR UNIT	UNIT EFFICIENCY (2007)	THEORETICAL LIMIT
Reflective solar - Stirling engine (no combined heat and power)	38%	Carnot $\frac{(T_2-T_1)}{T_2}$ (80%)
Fresnel lens(200x)-solar steam (no combined heat and power)	35%	Carnot $\frac{(T_2-T_1)}{T_2}$ (52%)
Wind power	15-25%	Betz Law (59%)
Thermoelectric (Seebeck effect)	5-6%	lim $\frac{(T_2-T_1)}{T_2}$ (30%)
Hydrogen - Fuel Cell	72%	Nernst Law (95%)
PV Cells - pure Si	18%	S-Q Theory (31%)
-Fresnel lens (200x) - pure Si	30%	-----
-2 junction	-----	lab 30%; theory 43%
In _{1-x} Ga _x N full spectrum	-----	lab 30%; Theory 80%

Of the currently available indirect solar conversion methods, both the solar-steam and solar-Stirling engine have about the same efficiency. Choice becomes a matter of economics. The InGa_xN method is a new approach to solar energy conversion. It is not an alloy but a "sea" of InN with homogeneous amounts of GaN. Figure 4 on the next page shows a full spectrum of this mixed compound energy converter. In Figure 4, the point at 2.0 eV (0% Ga) was the original literature band-gap value for InN. The Lawrence Berkeley lab group re-measured the band-gap and found a different level of around 0.4 eV. The group tested various mixtures of InN mixed with GaN together and found a range of band-gap values from 0.4 to 3.3 eV, or covering the full visible spectrum^{39,49}.

Figure 4. Full Spectrum of Nitrides

This new approach shows promise for solar energy conversion.

EMERGING U.S. SOLAR HYDROGEN ENERGY INFRASTRUCTURE

What is the total U.S. energy consumption ?

In 2006, the U.S. consumed 102.7×10^{15} BTUs of energy. This represents 23.8% of world's energy consumption. The U.S. population of 300 million people spent slightly more than 1 trillion dollars on energy alone which is more than 8 % of the gross national product. Currently, only 4% of this \$1 trillion was spent on renewable energy^{1,14}.

What are some of the newer solar energy projects in the U.S. ?

A few of the March 2007 U.S. solar energy projects are listed below^{54,57,87}:

- Arizona: 5 MWe PV project completed near Phoenix
- Texas: USAF issues RFP for 1 MWe PV system
- Florida: Dana City plans \$1.08 million PV system for streetlights
- California: Lennar Homes starts to build largest PV solar homes project in the U.S.
- California: Google, Inc. completes 1.6 MWe PV array system on it's headquarters building
- Plus 20 other project
- California - 75% of U.S. solar market

In 2007, there are a lot of small solar energy projects ongoing. This is just the March 2007 summary of projects in the U.S.¹⁰⁰

In the past three years, there were three notable solar projects. The first is the totally designed solar-hydrogen home completed in 2006 in Scottsdale Arizona. Also in 2006, the ISE Corporation (California) received Government funding to build 15 H₂ fuel cell buses. In 2004, the Palm Desert California SunLine Transit company uses the first H₂ internal-combustion-engine bus^{1,56,90}.

Are there any large-scale solar projects being planned for the U.S. ?

Yes, there is a large-scale solar energy project completed and others are under construction in Nevada and California.

In early 2007, a 64 MWe solar-thermal power plant was completed near Boulder City, Nevada. Figure 5 below shows the construction of the 64 MWe solar power plant during 2006^{9,10}:

Figure 5. 64 MWe Solar-Thermal Power Plant Project Under Construction

The 64 MWe system is composed of aluminum trough reflectors focused on pipes that contain high boiling point oil. The oil is heated to over 300° C and pumped to the boiler unit where steam is generated

In California there are two solar-thermal projects planned with one under construction that are the largest in the world. Both of these projects are reflective solar Stirling engine projects to be located in Los Angeles and San Diego. In 2005, the Stirling Energy Systems Corporation signed contracts with two California electric power companies. One with Southern California Edison Electric and the other with San Diego Gas & Electric. The first phase of the San Diego project is partially completed. The details are^{34,36,40,43,55}:

Stirling Energy Systems, Inc. - San Diego Gas & Electric

- 300 MWe w/option to 900 MWe
- 12,000 x 25 kWe reflector dish array - 2,700 acres
- under construction: 2006-2009
- \$0.06/kWhr

Stirling Energy Systems, Inc. - So. California Edison Electric

- 500 MWe w/option to 850 MWe
- 20,000 X 25 kWe reflector dish array - 4,500 acres
- 2009 - 2012
- \$0.06 /kWhr

Figure 6 on the next page shows many of the reflective solar-Stirling engines already installed during Phase I at the San Diego Gas & Electric solar power plant⁵⁵:

Figure 6. A group of reflective solar-Stirling engines (Phase I) at the San Diego Gas & Electric solar power plant area

All of these previous solar power plants are for daytime energy generation. Will there be any full 24-hour/day solar hydrogen power plants built in the U.S. ?

Yes, there are several full 24-hour solar-hydrogen power plants planned for the U.S. A typical example is shown:

Table IV. 200 MWe 24-Hour/day Solar-Hydrogen Power Plant^{32,36,37,48,71,72}

Components A-B-C	Cost 2009 (est.) \$ million	Required Land area
Combined 150 MWe wind farm and	283.86	64 acres
50 MWe Concentrated Solar Stirling Engine	192.91	450 acres
Total 200 MWe Solar-Hydrogen System*	476.77	514 acres

* Day time output: total 200 MWe with 150 MWe to power grid and 50 MWe goes to the electrolyzer for H₂ production and stored.

What is the U.S. installed wind power capacity ?

A study has shown that cost of electricity drops with wind speed to as low as \$0.026 at 30.1 miles/hr. In addition, improvements in wind turbine design also bring down the costs. Some of the newer developments have been in vertical wind turbines^{51,72}.

A number of studies have been done on converting wind power electricity directly to H₂. A large wind-to-H₂ facility has been completed and in operation for the North Dakota Basin Electric Power Cooperative. The generated H₂ cost is about \$2.42/kg. Wind power has an advantage since North Dakota has fairly good wind speeds at all hours^{1,45,70}.

Figure 7 on the next page shows a State-by-State summary of the total installed wind capacity as of 2006⁵⁹

Figure 7. U.S. State-by-State Total Installed Wind Capacity - 2006

The U.S. wind power has grown fourfold since 2000 and now has a total capacity of 11,603. Texas leads the U.S. in windpower production with California a close second. California obtains 2% of its electrical needs from windpower.

How extensive is the U.S. conversion to H_2 transportation infrastructure ?

Both the H_2 fueling stations and the hydrogen auto infrastructure projects are rapidly moving forward into commercialization. California leads the nation in moving toward having H_2 fueling stations in large cities and major roads.⁶²

In 2004, Governor Schwarzenegger signed into law a “Hydrogen Highway” program. Its goal is having 200 fueling stations located every 20 miles along four major north-south highways, i.e., Interstate 5, 10, 15, and 80. In 2006, there were already 21 H_2 fueling stations in Los Angeles with 10 more planned with local H_2 production. In San Francisco and Sacramento, there are 11 with 10 more planned. All with local H_2 production.^{1,60}

“Big Oil” and the automotive industries are actively engaged in providing a foundation for the H_2 infrastructure. In 2006, Rick Zalesky, Chevron’s Hydrogen Boss, stated that “Hydrogen is not like petroleum or natural gas, or anything else we’ve done before.” “Old ways do not work”, i.e. a centralized fueling network. Thus, “Big Oil” will have to dismantle its fuels’ distribution network.¹

In 1996, Ford had the right idea for introducing hydrogen to the consumer by building a small 2.4 liter 4- cylinder hydrogen internal combustion engine (HICE). In 2004, Ford further developed and built more than fifty 235 hp 6.8-liter V-10 cylinder H_2 engines and put some of these in shuttle buses. These engines were 25% more fuel efficient than the gasoline type.⁶³ In 2006, thirty of these buses were lent for testing in Florida and California.^{58,63}

In 1995, GM threw out its “automotive thinking” and has built several different prototype fuel cell autos. During 2002-2007, GM developed and tested several more different FC autos. One was the “Hy-Wire” that was radically new in driver functional controls with no pedals and no dashboard. It has a lever-type steering wheel, i.e., airplane type “joy stick”. All the control components, fuel cell and electric motor systems are in a 11-inch “skate board” sized chassis between the wheels. The body shell can be mounted in about 3 hours over the chassis. In 2007, GM developed “Equinox” with same FC system as “HydroGen3”. GM built 15 of these and is currently testing these FC autos in New York City.^{61,97}

All the other major auto manufacturers such as Daimler, Honda, Hyundai and Toyota all have fuel cell autos with more

than 100 being road tested. Honda has targeted to have 50,000 of their fuel cell auto, FCX-3, on the road by 2012.⁹⁷

In comparing the different auto propulsion systems, what are the various auto “well-to-wheel” efficiencies ?

AUTO “WELL-TO-WHEEL” EFFICIENCIES

- Oil well-to-wheels (internal combustion engine) 14%
- Oil well-to-wheels (hybrid) 22%
- Natural gas well-to-hydrogen-wheels (fuel cell auto) 42%
- Water-well-to-hydrogen-wheels (fuel cell auto) 44%

The water-to-hydrogen auto efficiency is better than our current petroleum-based autos. Not only is the fuel cell auto more environmentally helpful but it is also more also more fuel efficient.¹

EMERGING INTERNATIONAL SOLAR-HYDROGEN INFRASTRUCTURE

Iceland

Will Iceland adapt to the Hydrogen Economy ?

Yes, even though Iceland has plenty of low cost geothermal electric power, in 2000, Iceland was the first country to commit totally to hydrogen power. Iceland’s President Grimsson stated: “*The whole nation is converting to hydrogen power*”. “*We are making Iceland a trial base to see what can develop for our global society.*”^{1,94}

By 2006, four Mercedes-Benz fuel cell buses in Reykjavik had traveled over 90,000 km in all types of weather. The engineers were surprised at how well the fuel cell performed with very little maintenance. They are planning for seven more H₂ fueling stations and more buses. At Iceland’s DeFlavik airport, a Plug Power Company “GenCore” stationary H₂ fuel cell is being used as back-up power supply.¹

Denmark

Denmark has been a pioneer in developing wind power since the 1970s. In 2003, Denmark built the world’s largest offshore wind farm of 166 MWE at Lolland. In 2005, they added an additional 916 MWe wind power capacity. By the end of 2006, they had a total of 3,136 MWe total installed. Currently, their total wind power meets 29% of their electrical needs. Today, 90% of the wind turbines manufactured in Denmark are sold to international markets capturing 43% of the world’s wind turbine market.^{84,95,96}

Europe

A lot more progress has been made in Europe over the past 20 years than in the U.S. in converting to the New Energy. Starting in 1977, the International Energy Agency established a H₂ program with 15 European member nations. The mission was to accelerate H₂ implementation and widespread use of H₂. By 2001, Europe already had more than 6% of its energy economy invested in solar energy.^{78,}

What are some of the major changes and the current status of Europe’s Solar-Hydrogen infrastructure ?

In 2006 alone, there were 70 ongoing R & D projects as well as designating two billion euros for the “H₂ Vision Program” (\$2.4 bn.). Today, Europe produces 3.3% of its electricity by wind power. A target of 22% of electricity consumption from solar energy sources by 2010 was set by the European Commission for its 15 members.^{82,98}

Germany has become Europe's leader in converting to the Solar-Hydrogen Economy. This is due to the German Renewable Energy Law that takes subsidies away from fossil fuels toward solar energy.

Europe's Wind Market - 2006

The global wind market grew 32% over 2005 with 15,197 MWe added in 70 countries making the total global installed wind power of 74,223 MWe. Europe's wind energy market continued their rapid growth by adding 50% of the previous 15,197 MWe making 2006 another record year.^{80,82}

In 2006, there was a total of 7,588 MWe of additional wind power installed in eighteen European countries which is a 23% increase over 2005. Germany alone installed 2,233 MWe bringing their total now over 20,621 MWe. This latter amount is twice that of the total installed U.S. wind power. England had added 168 MW to bring their total to 2,000 MW while Poland's goal is to have a 1,100 MWe wind farm by 2010.^{85,86}

Europe Photovoltaic (PV) Market - 2006

The global PV market grew 19% with 1,744 MWe added worldwide Europe continues to lead the world in PV array installations.⁸⁰

In early 2006, Germany added 960 MWe PV power to the grid which is a 16% growth over the previous year. A U.S. company, First Solar, Inc. has started a 30-month contract (\$171 million) with completion in 2009 to provide 40 MWe of PV panels for installation near Brandis, Germany which will be the world's largest PV solar plant. Spain has started construction of a 6.5 MWe PV array with completion by 2008. In 2006, the Czech Republic's 0.6 MWe PV array went on-line.^{92,93}

Europe's Hydrogen Bus Programs

Since 2003, five European cities have had nine hydrogen buses in operation. Amsterdam has had three fuel cell buses in operation with the hydrogen produced by electrolysis at the station. Bus passengers have become H₂ advocates.^{1,78}

In 2006, the European Commission started the "Hydrogen for Transport" program as a total European effort.⁸⁸ The program's goal is 47 hydrogen buses in 10 cities. Both hydrogen ICE and fuel cell buses are planned. As part of this program, a Luxembourg fuel cell bus built by Mercedes-Benz has experienced 5,000 hours of street operation by the end of 2006.⁹¹ In addition, Berlin placed two hydrogen internal combustion engine (HICE) buses in service:⁸⁹

Figure 8. Two Hydrogen Internal Combustion Engine Buses in Berlin, Germany

In summary, as a result of all the solar projects in Europe, 15 of these countries, mainly Germany, Finland and Netherlands, have brought their total greenhouse gas emissions, CO₂, to 1.5% below 1990 levels. In addition, with the increasing economic growth in Europe in 2007, the previously planned and new Solar-Hydrogen energy projects will keep ahead of the future energy demand.

Japan

What is the status of the PV market in Japan ?

Due to Japan's lack of major fossil fuel sources, they started early in solar energy use. The Japanese home owners started 15 years ago to install PV cell systems and today over 80% of existing homes have installed PV arrays. In 1997, the Government PV rebate program started with \$3,400/kW with a limit of 10 kw installed. During the period 1997-2005, the rebate was gradually reduced to \$200/kW and, finally, replaced with low interest rate loans.⁷⁹

In 2004, their total sales of manufactured PV units were \$3.07 billion with about 50% of this amount was exported. Today, Japan is the largest PV cell producer and the second largest user worldwide (Germany is the first). There is a forecast of 2.35 gigawatt PV sales in 2008 which are 360% more than 2004.⁷⁷

By 2006, 65% of the Japanese municipal Governments had already installed PV systems with another 24% who will install them during 2007-2009 for schools, municipal office buildings, street lights and other Government projects.⁷⁹

Honda Motor built a new PV factory in 2006 and began mass production of the CIGS type PVcells for home use. These sell for 25% less than the silicon PV cell but are only 12% efficient.⁸¹

Japan was also early in wind power use. Due to their large PV usage, the wind power installed capacity was small. In 1999, they only had 43.4 MWe of installed wind capacity. By 2006, it had grown to 102 MWe. Their goal is to have more than 300 MWe by 2010.⁶⁶

China

China now consumes 14.7% of the world's energy. Over the past three years this has grown by 65%. China has some of the most polluted cities in the world and will shortly become the largest greenhouse gas emitter by 2010.⁷⁴

In 2006, The Chines Government's Renewable Energy Law was established with a goal of 10% solar energy by 2020. This 10% is an almost impossible goal; however, with their current 103 million square meters of installed solar-heat panels and growing it may be achievable. In addition, China's solar power generation was only 10 MWe, a tiny fraction of the 2.83 billion megawatts (10¹⁵ watts) total demand. China's immediate goal is to have 300 MWe solar energy by 2010. Two-thirds of China's land area receives annually more than 2,000 hours of sunlight which is more than other regions of same latitude including Europe and Japan.⁷³⁻⁷⁵ China is fast becoming a leader in wind technology.⁶⁸

China has 150 PV manufacturers accounting for 1/3 of the world's silicon PV production. Because of the low in-country demand, 90% of that production was exported. These PV manufacturers are ramping up production to meet China's internal demand.⁷⁵

CURRENT AND PROJECTED GROWTH IN SOLAR HYDROGEN ECONOMY

What has been the largest growth areas in the Solar-Hydrogen Economy ?

2006

World's wind energy market grew 25.6% over 2005 valued at \$13.4 billion representing 15,197 MWe added for a total of 73,900 MWe installed.^{52,83}

World's solar PV market grew 19% over 2005 valued at \$10.6 billion representing 1,738 MWe added for a total of 3,689 MWe installed.⁹⁹

World's solar Stirling engine market grew 40-fold valued at \$1.3 billion representing 800 MWe added.³⁴

The combined MWe of these three markets *added in one year* is equal to 35 each 500 MWe nuclear power plants. However, the world wide Solar-Hydrogen Economy is at a critical turning point and is accelerating rapidly showing that substitution of nuclear and fossil energy is possible and necessary. This growing shift to this New Economy is profound. The world will be freed from its dependence on oil and its geopolitical problems of the last 50 years. Thus, the time is long past to set aside the multiple political and structural barriers against the Solar-Hydrogen Economy and to move quickly into this New Economy.

How long will it take to the U.S. to restructure the Petroleum Economy into the Solar-Hydrogen Economy ?

This is a difficult question. The transition to the Solar-Hydrogen Economy is dependent on how fast we can mobilize industry and Government to restructure the Petroleum Economy and how many dollars are put into the transition.

There is a way to estimate the length of time. Interestingly, there is a general curve that governs change in many processes both in science and human phenomenons. It is called the "logistic" or sigmoid curve. For example, the total U.S. energy expenditures would be a good measuring tool for the transition time. Our total energy expenditures were \$1,008 billion (2006) and represents about 8% of our GNP. For discussion, this logistic model can be developed as a time vs. Solar-Hydrogen Economy growth. Figure 9, shown below, illustrates a possible time line for the transition:¹

Figure 9. Estimated Time-Line for Conversion to the Solar-Hydrogen Economy

Currently in the U.S., we are at the 3.5% renewable energy expenditure level which is just at the “toe” of the exponential growth on the Solar-Hydrogen Economy curve. I would expect the linear portion to start at 8% (2012) and continue until 93% is reached. At that point, it will level off asymptotically until we reach a maximum. You will notice that the Petroleum Economy curve finally levels off at \$100 billion. We will still need some petroleum products such as lubricants and plastic monomers until the renewables can overtake these areas. For the Solar-Hydrogen curve, a 3% per year linear growth would take 28 years (then 2040) to reach the 93%. I believe a 3% growth is realistic.

Subsequently, Honda has announced that it will have 50,000 fuel cell cars on the road starting in 2012. This confirms my earlier estimate of 2012 for reaching the 8% growth.

There is one key obstacle that will delay the Solar-Hydrogen economy from reaching the 8% point and that is the cost of the fuel cell for autos. Figure 8 assumes that the fuel cell cost will be economically viable by 2012 and the linear growth would start. But, if the recent developments in fuel cells, i.e., polymers, take 8 years to be translated into fuel cells at a lower price, then it would be 2015 before we reach the 8% mark. Thus, it would be 2048 before the 93% is achieved.

In summary, I believe the U.S. \$12.8 trillion dollar economy will suffer a decrease with a possible heavy recession during this transition. What we need is for the Government to take a strong lead, like the European Governments in this transition. In any event, the Solar-Hydrogen Economy is the greatest financial opportunity in our history. The past computer growth will pale by comparison.

BIBLIOGRAPHY

1. W. D. Reynolds, “Why we need the solar-hydrogen economy *now*” see: www.hydrogennow.org “The next step: conversion to the solar-hydrogen economy” Parts I and II see www.energypulse.net
2. World Council for Renewable Energy: World renewable energy agenda
3. Solar Energy Technologies Program: Solar FAQs see: www.eere.energy.gov
4. A. J. Nozik, PhysChem Paper #87, ACS National meeting March 2007 Chicago
5. J. Johnson, “Farm Energy”, see www.cen-online.org
6. A. McKillop, “Peak oil to peak gas is a short ride”, www.energypulse.net
7. M.D. Savinor, “Life after the oil crash” see www.lifeaftertheoilcrash.net rev. 4/07
8. L. de Sousa, “Natural gas: how big is the problem ?” and “How to address contrarian arguments - part II” see www.theoildrum.com
9. M. Kanellos, “Full steam ahead for Nevada solar project” C|net News see: <http://news.com.com>
10. Photos, Nevada solar project courtesy of C|net News see: <http://i.n.com.com>
11. PESWIKI “Directory: cents per kilowatt-hour” <http://peswiki.com>
12. S. Cox “Goodbye to all that oil” see www.alternet.org
13. R. C. Duncan and W. Youngquist “The world petroleum life-cycle” see <http://dieoff.org>
14. Chapter 1. “World energy and economic outlook” see: www.eia.doe.gov
15. K. Kohl, “Is oil’s ride almost over ?” see www.energyandcapital.com
16. Exxon Mobil Corp. “The outlook for energy - a view to 2030” see www.exxonmobile.com
17. Email to W. D. Reynolds from Albert Opdenaker, Asst. Dir., Office of Science, DOE
29 November 2006 on nuclear fusion budget.
18. J. Bell, “Nuclear power - one of humankind’s biggest mistakes” see: www.energypulse.net
17 November 2006
19. W. D. Reynolds: Compressed air calculations, see also: The concept of PV work in chemistry
<http://dbhs.wvusd.k12.ca.us> section on Thermochemistry.
20. “Terrestrial solar cell surpasses 40% efficiency” see www.gizmag.com
21. V. Garboushian “World record efficiency” see. <http://72.14.235.104> and www.solar.unlv.edu

22. "Cost of PV concentrators falling fast" see: www.terraily.com
23. Dr. Hubbert's general curve see: <http://en.wikipedia.org> figure 20.
24. "US Oil Production and Imports 1920-2005" see: <http://en.wikipedia.org>
25. "Image: Norway Hubbert" see: <http://en.wikipedia.org>
26. "Image: Hubbert World 2004" see: <http://en.wikipedia.org>
27. Middle east annual production 1960-2040 see: <http://dieoff.org> Page 133
28. World's annual liquids production 1900-2100 see: www.oildrum.com J. Laherrere'
29. A. B. Lovins "Twenty Hydrogen Myths" Rocky Mountain Institute 17 Feb 2005 update
see: www.rmi.org
30. "Energy Innovations: A prosperous path to a clean environment" see: www.environmentalexpert.com ;
G. Dauncy "Getting back on track: can we phase out fossil fuels by 2025" Climates of Change Congress,
Canada 2000 and updates.
31. NREL report "Hydrogen Economy: Opportunities, Costs, Barriers and R&D Needs" M. Rampage, Chair, 2004
and Calif. Energy Commission report :Distributed Energy Resource" Jan 2002 and updated see:
www.energy.ca.gov
32. W. D. Reynolds cost calculations and updates from ref. 31.
33. S. Brooks "New bladeless design for turbines could dramatically lower the cost of energy production"
see:www.iaus.com/turbine
34. D. Karmann "World's largest solar power plant" see: <http://news.com.com>
35. Pacific Power cost table summary for various electric generators Oct. 2006
36. Stirling Energy Systems see: www.stirlingenergy.com also email to W. D. Reynolds:ses@stirlingenergy.com
37. S. W. White, et.al., "Life cycle energy cost of wind and gas-turbine power" see:
www.neep.wisc.edu/FTI and calculations
38. D. Lakey "130 MW gas turbine combined cycle power plant" SP Newsprint Co. and
K. Darrow, Energy and Environmental Analysis, Inc. Bellevue, WA
39. "Full solar spectrum nitrides" see: www.lbl.gov/science-articles/archive
40. "6 cents per kWh: world's largest solar project unveiled" see: <http://i.treehugger.com.files>
41. "Chapter Two: Fundamentals" wind power see: www.ece.unb.ca
42. "Estimating output" windpower see: www.solareco.com
43. California PUC approves Stirling Energy System's solar energy contract with Southern California Edison
see: www.stirlingenergy.com
44. CHP fuel cell costs see: www.energy.ca.gov and NREL report 2004 "Hydrogen Economy"
45. "A boost for hydrogen fuel cell research" 26 Jan 2007 see: www.sciencedaily.com
46. "EU posts drop in greenhouse gas" see: www.cen-online.org
47. "Hydrogen safety - The Hindenburg accident" see: www.humboldt.edu Schatz Energy
Research Center
48. J. I. Levene "Economic analysis of hydrogen production from wind" presented at the
Windpower Conference, 15-18 May, 2005, Denver; see: www.osti.gov
49. W. Walukiewicz , et.al., "Effects of the narrow band gap on the properties on InN" J. Physical Review B,
15 Nov 2002; see also: www.lbl.gov/Science-Articles/Archive
50. Email to W.D. Reynolds from V. Garboushian, Amonix Corp. 5 Mar 2007 on costs of PV arrays and
land area.
51. "Lessons learned from the U.S. PV industry" report NREL/PR-500-40099; Presented at
AWEA Windpower Conf. 4-7 June 2006.
52. "New world record in wind power capacity in 2006" 29 Jan 2007 see: www.windea.org
53. G. W. Crabtree and N. S. Lewis "Solar energy conversion" Physics Today 60(3)37-42 Mar. 2007 see:
www.aip.org
54. See: www.solarbuzz.com March 2007 and later issues
55. Stirling energy systems signs second largest solar deal in California" see: www.stirlingenergy.com

56. "Chevron Energy completes solar project for US Postal Service" see: www.fnlink.com
57. "Google plans largest US solar-powered office" see: www.planetark.com
58. "Governor Bush breaks ground on Florida's "hydrogen highway" see: www.chevron.com
59. "Wind energy projects throughout the U.S.A." www.awea.org/projects
60. "AQMD celebrates grand opening of first "hydrogen highway" network" see: www.aqmd.gov/news
61. "Next generation fuel cell system propels GM's Sequel" see: www.evworld.com
62. "The future of transportation" see: www.forbesautos.com/news
63. "Fuel-cell fleet : Ford producing hydrogen-powered V10 for use in shuttle busses" see:
www.autonews.com ; www.media.ford.com ; <http://thefraserdomain.typepad.com>
64. "Solar power breakthrough: IAUS hits milestone previously thought to be impossible" see:
www.electricnet.com
65. M.S. Ryan and J.-P. Fleurial "Thermal to electric power conversion using thermoelectric microconverters" see: The Electrochemical Society *Interface*, summer 2002
66. "RPS caps Japan wind growth" see: www.emerging-energy.com
67. "Betz Law" see: www.windpower.org
68. "China makes huge breakthrough in wind power technology" see: www.worldwatch.org
69. "Energy recovery turbine" see: www.centripetal-dynamics.com
70. "Workshop in electrolysis production of hydrogen from wind and hydro power" Proceedings
www1.eere.energy.gov/hydrogenandfuelcells/wkshop_wind_hydro.html
71. L. Fingersh, M. Hand and A. Laxson "Wind turbine design cost and scaling model" Technical report
NREL/TP-500-40566 Dec. 2006
72. "The economics of wind energy" Feb 2005 see: www.awea.org
73. "China aims to clean up in solar power" 11 April 2007 see: www.businessweek.com
74. Speech by China's Z. Guobao, Deputy Director of National Development and Reform Commission at the
International Renewable Energy Conference, 7 Nov 2005
75. Z. Li "Solar energy booming in China" 23 Sep 2005 see: www.worldwatch.org
76. "What will happen next" page 2-3 see: www.solarplaza.com
77. "Japanese solar market to grow 30-40% a year until FY 2008" 12 April 2006 see:
<http://climatechangenews.blogspot.com>
78. "Hydrogen on the road" see: www.h2euro.org
79. "Japanese PV market - solar energy" May 2005 see: www.solarbuzz.com/fastfactsjapan
80. "Solar energy solutions group" pgs3-5 see: <http://74.14.253.104>
81. "Honda entering solar cell market for homes and vehicles" see: www.greencarcongress.com
82. "European market for wind turbines grows 23% in 2006" 1 Feb 2007 see: www.ewea.org
83. "Global wind energy markets continue to boom - 2006 another record year" see:
www.gwec.net
84. "The world's leader in wind power" see: www.scandinavica.com/culture/wind.htm
85. "Developers look to unlock Poland wind potential" see: www.energyin-energy.com
86. "Mega contracts tighten W.G. competition in Spain" see: www.energying-energy.com
87. "Solar energy sales projects/green power - USA - 3 months summary" see: www.solarbuzz.com
88. "Hyfleet:cute FAQs" see: www.global-hydrogen-bus-platform.com
89. Tech corner- Hydrogen bus source "Berlin to launch Hyfleet HICE bus fleet to follow CUTE program" see
www.weststart.org
90. "Sunline transit agency" see: <http://72.14.253.104>
91. "Fuel cell bus passes 5,000 hours of operation" 2 Jan 2007 see:
www.global-hydrogen-bus-platform.com
92. "Phase one of 40 MW German solar park begun" 23 Jan 2007 see:
www.renewableaccessenergy.com

93. "More on German green energy" see: www.worldchanging.com
94. "Iceland hots up towards hydrogen" The Fuel Cell Review, June/July 2006
95. "The hydrogen train: feasibility study 2005-2006" see: www.hydrogentrain.eu
96. "Scandianian hydrogen highway partnership formed" 26 June 2006 see: www.h2euro.org
97. J.Glowicki "Industry insider: dropping the fossil-fuel habit" 7 Sept 2005 see:
<http://consumerguideauto.howstuffworks.com/articles>
98. "Renewable energy: Commission calls for a stronger commitment of member states to achieve the 2010 targets" 26 May 2004 see: <http://europa.eu/rapid>
99. "2007 world PV industry report highlights" 19 Mar 2007 see: <http://register.solarbuzz.com>
100. "US grid connect PV market report 2006" 19 June 2006 see: <http://register.solarbuzz.com>

Solar Hydrogen Production by Tandem Cell System Composed of Metal Oxide Semiconductor Film Photoelectrode and Dye-Sensitized Solar Cell

H. Arakawa, C. Shiraishi, M. Tatemoto, H. Kishida, D. Usui, A. Suma, A. Takamisawa
and T. Yamaguchi

Tokyo University of Science, 12-1 Ichigaya-Funagawara, Shinjuku, Tokyo, 162-0826, Japan

ABSTRACT

Photocatalytic and photoelectrochemical approaches to solar hydrogen production in our group were introduced. In photocatalytic water splitting system using $\text{NiO}_x/\text{TiO}_2$ powder photocatalyst with concentrated Na_2CO_3 aqueous solution, solar energy conversion efficiency to H_2 and O_2 production (STH efficiency) was 0.016%. In addition, STH efficiency of visible light responding photocatalyst, NiO_x / promoted $\text{In}_{0.9}\text{Ni}_{0.1}\text{TaO}_4$, was estimated at 0.03%. In photoelectrochemical system using an oxide semiconductor film photoelectrode, STH efficiencies of mesoporous TiO_2 (Anatase), mesoporous visible light responding S-doped TiO_2 (Anatase) and WO_3 film were 0.32-0.44% at applied potential of 0.35 V vs NHE, 0.14% at 0.55 V and 0.44% at 0.9 V, respectively. Finally, solar hydrogen production by tandem cell system composed of an oxide semiconductor photoelectrode, a Pt wire counter electrode and a dye-sensitized solar cell (DSC) was investigated. As photoelectrodes, mesoporous TiO_2 (Anatase), mesoporous S-doped TiO_2 (Anatase), WO_3 , BiVO_4 and Fe_2O_3 film were tested. STH efficiency of tandem cell system composed of a WO_3 film photoelectrode, and a two-series-connected DSC ($V_{oc} = 1.4$ V) was 2.5-2.8%. In conclusion, it is speculated that more than 5% STH efficiency will be obtained by tandem cell system composed of an oxide semiconductor photoelectrode and a two-series-connected DSC in near future. This suggests a cost-effective and practical application of this system for solar hydrogen production.

Keywords: Solar hydrogen production, Tandem cell system, Mesoporous oxide semiconductor film photoelectrode, TiO_2 , S-doped TiO_2 , WO_3 , BiVO_4 , Fe_2O_3 , Dye-sensitized solar cell,

1. INTRODUCTION

As one of countermeasures against global warming issue, development of new cost-effective technologies utilizing renewable energy is strongly requested. Solar light energy, which is inexhaustible and free energy, might be a main target to be utilized. In addition to photovoltaic cell system, solar hydrogen production is very attractive way to harvest and store solar energy. It is well known that a combination process of photovoltaic cell and water electrolysis is a practical way to solar hydrogen production. However, solar cell system is still expensive for solar hydrogen production. It is requested to develop a cost-effective process. Direct water splitting into H_2 and O_2 using oxide semiconductor powder photocatalyst is one of the alternatives. This system is relatively costless and robust. However, STH efficiency is quite low at present. Therefore, we need to develop new materials which can utilize abundant visible light effectively for water splitting. In addition to new materials for effective light harvest, suppression of unwanted reactions, such as backward reaction of water splitting over photocatalyst and charge recombination reaction between excited electrons on the conduction band and positive charge holes on valence band of semiconductor, are subjects for improving efficiency. The other alternative way is photoelectrochemical water splitting system composed of an oxide semiconductor photoelectrode and a metal counter electrode. This system can suppress not only charge recombination process but also backward reaction by applying potential. Therefore it might result in an increase of efficiency. However, we need electricity for applied potential. This is a weak point of photoelectrochemical approach of solar hydrogen production. In order to compensating this weak point of photoelectrochemical system, a tandem cell system composed of an oxide semiconductor film photoelectrode and a dye-sensitized solar cell (DSC) was proposed by Augustynski and Graetzel.¹⁾ This system might be relatively cost-effective process because DSC is recognized cheaper one third to one fifth than silicon solar cell. In this presentation, our approach to solar hydrogen production is introduced.

*h.arakawa@ci.kagu.tus.ac.jp; phone+91-3-5228-8311; fax +81-3-3235-2214

2. SOLAR HYDROGEN PRODUCTION BY OXIDE SEMICONDUCTOR POWDER PHOTOCATALYSTS

Since photoelectrochemical water splitting into H_2 and O_2 using a TiO_2 (Rutile) single crystal photoelectrode and a Pt counter electrode was reported by Honda and Fujishima in 1972,²⁾ extensive studies in photocatalytic water splitting using a metal promoted oxide semiconductor powders such as Pt/TiO_2 (Anatase) have been reported so far. Figure 1 shows conceptual mechanisms of photocatalytic water splitting. The one is for one-step water splitting using one powder photocatalyst composed of metal promoted oxide semiconductor. The other is for two-step water splitting using two different powder photocatalysts composed of metal promoted semiconductors for H_2 and O_2 evolution, respectively. In this system, a redox mediator such as Fe^{3+}/Fe^{2+} is essential in order to carry electrons between two different photocatalysts. Two-step water splitting system is similar to The Z-scheme of natural photosynthetic process, which is a two-photon exciting system. Therefore, STH efficiency of this system might be lower than that of one-step water splitting system. However, this system has a merit for wide selection of photocatalysts for two half reactions of water splitting. A redox mediator is also able to be selected.

Principle of water splitting by solid photocatalyst

Fig. 1. Water splitting mechanisms using powder photocatalysts of metal promoted oxide semiconductor

2.1. Solar hydrogen production using UV light responding oxide semiconductor photocatalysts

So far, many powder photocatalysts of oxide semiconductors are reported for one-step water splitting.³⁾ However most of them are active under only UV light irradiation for a stoichiometric water splitting into H_2 and O_2 . Figure 2 shows water splitting performance of typical powder photocatalysts of UV light responding under irradiation by full arc of 400W high-pressure Hg lamp. The most active photocatalyst among them was $NaTaO_3$ photocatalyst (B.G.= 4.1 eV), which was active under irradiation of light shorter than 302 nm⁴⁾ This photocatalyst produced both H_2 of 448ml and O_2 per of 220ml for one hour and per 0.5g-cat. Unfortunately, the light shorter than 302 nm does not include in AM1.5 solar light. Therefore we can not utilize this photocatalyst for solar hydrogen production. We found a significant promoting effect of aqueous Na_2CO_3 solution on stoichiometric water splitting over Pt/TiO_2 (Anatase) photocatalysts.⁵⁾ Hydrogen of 85 ml and O_2 of 43 ml were produced for one hour and per 0.5g of Pt/TiO_2 photocatalyst under the same irradiation conditions. There are few reports, which describes STH efficiency of powder photocatalysts of oxide semiconductor. Therefore, we tested solar hydrogen production using an aqueous suspension of Na_2CO_3 and NiO_x/TiO_2 (Anatase) powder photocatalyst. Under 6-hour irradiation of natural solar light in July at Tsukuba, Japan, H_2 of 400ml/m² and O_2 of 200ml/m² were produced. STH efficiency of this experiment was only 0.016%.⁶⁾

400 W - High pressure Hg lamp equipped with quartz water jacket ($\lambda > 200$ nm), H₂O: 400 ml

Fig. 2. Stoichiometric water splitting using typical UV light responding powder photocatalysts

2.2. Solar hydrogen production using visible light responding oxide semiconductor photocatalysts

In order to improve water splitting efficiency of photocatalysts, it is very important to develop visible light responding photocatalysts. One of approaches to realize visible light responding photocatalysts is a doping of wide band gap semiconductors. Typical examples are N-doped TiO₂ (Anatase)⁷⁾ and S-doped TiO₂ (Anatase).¹⁷⁾ These photocatalysts are active for decomposition of organic compounds and organic contaminants. However, water splitting ability of these compounds is quite low even compared with those of non-doped TiO₂ (Anatase) photocatalysts. Charge-recombination process might be accelerated by the presence of doping level. The other approach is to develop and find new materials for visible light responding. We have screened various kinds of mixed oxide semiconductor materials. As a result, we found InTaO₄ and InNbO₄ could split water under visible light irradiation.^{8,9)} Furthermore, water splitting activity increased 4 times higher by NiO_x/In_{0.9}Ni_{0.1}TaO₄ photocatalyst.¹⁰⁾ Hydrogen and oxygen were produced with the rate of 0.672ml/h·g-cat and 0.336ml/h·g-cat, respectively, under visible light irradiation ($\lambda > 420$ nm, 300W-Xe lamp). Water splitting lasted steadily for more than 400hrs under visible light irradiation. The estimated STH efficiency of this powder photocatalyst was 0.03%. Recently, new oxy-nitride photocatalysts such as ZnO:GaN were reported for visible light water splitting by Domen et al.¹¹⁾ We speculate STH efficiency of this photocatalyst is below 0.1%.

2.3. Solar hydrogen production using a two-step water splitting system

Screening of photocatalysts was conducted for a two-step water splitting system under visible light irradiation. As a result, the combination of Pt/WO₃ photocatalyst for O₂ evolution, Pt/Cr,Ta-co-doped SrTiO₃ photocatalyst for H₂ evolution and I⁻/IO₃⁻ redox mediator has proved to be active for visible light water splitting.¹²⁾ This system is the first

example of a two-step visible light water splitting system. The gas evolution rates of H_2 and O_2 were $0.179 \text{ ml/h} \cdot \text{g-cat.}$ and $0.089 \text{ ml/h} \cdot \text{g-cat.}$ respectively. The estimated STH efficiency of this photocatalyst system is only 0.005%.

3. SOLAR HYDROGEN PRODUCTION BY PHOTOELECTROCHEMICAL CELLS COMPOSED OF OXIDE SEMICONDUCTOR PHOTOELECTRODE AND PT WIRE COUNTER ELECTRODE

Photocatalytic water splitting system is very simple and cost-effective. However, as we see, STH efficiencies of this system is very low at this moment. The reason for low efficiency is ascribed to have unwanted reactions such as backward reaction of water splitting, water formation, and charge recombination reaction between photoexcited electrons on the conduction band and positive charge holes on valence band of semiconductor. In a photoelectrochemical cell, both unwanted reactions might be suppressed by applied potential as well as separation of gas evolution by two different electrodes. Therefore, efficiency of water splitting is speculated to be improved, though this system is relatively expensive compared with photocatalyst system.

Figure 3 shows a photoelectrochemical cell set up for water splitting. Transparent, thin and/or mesoporous oxide semiconductor film photoelectrodes were prepared onto FTO conducting glass by screen print, spin coat and Doctor-blade methods. Transparent film is also used by a tandem cell system. Recently, transparent oxide semiconductor photoelectrodes receive much attention in terms of efficient water splitting. For example, a high photocurrent of water splitting over transparent WO_3 and Fe_2O_3 photoelectrodes under simulated solar light was reported by Augustynski¹³⁾ and Graetzel¹⁴⁾ et al.

Fig. 3. Photoelectrochemical cell set up

Three-electrode cell (W.E.= photoelectrode, C.E.= Pt wire, R.E.= Ag/AgCl). Irradiation source= Solar simulator (AM1.5, 100 mw/cm^2).

3.1. Solar hydrogen production using mesoporous TiO_2 (Anatase) photoelectrode

First of all, we decided to fabricate TiO_2 (Anatase) film photoelectrode, because TiO_2 photoelectrode is well known as an active water splitting photoelectrode.²⁾ We would like to know how efficiently TiO_2 thin film photoelectrode could split water compared with TiO_2 powder photocatalyst. We prepared mesoporous TiO_2 film photoelectrode. It is speculated that mesoporous thin film photoelectrode has a larger surface area than that of non-porous sintered or single crystal photoelectrode. Therefore, interface area between electrolyte solution and photoelectrode surface might be much increased, resulting a higher efficiency. TiO_2 photoelectrode was fabricated by screen printing of TiO_2 paste onto FTO conducting glass, followed by drying and then calcination at $600\text{--}700^\circ\text{C}$.¹⁵⁾ TiO_2 paste was composed of TiO_2 nano-crystal particles of 20 nm in diameter, organic binder and ethanol solvent. Optimum thickness of TiO_2 film was 3-10 μm . The size of TiO_2 photoelectrode was a 1cm-by-1cm. As an electrolyte solution, NaOH aqueous solution was used. Concentration of NaOH was changed from 0.1 M to 1.0 M. TiO_2 photoelectrode, Pt wire counter electrode and Ag/AgCl reference electrode were connected to the potentiostat. Water splitting ability of oxide semiconductor photoelectrode was estimated by measuring photocurrent under irradiation. A very good relationship between measured photocurrent and produced amount of H_2 was obtained. Hydrogen of 0.008ml was produced by 1mA current flow for one minute. Under irradiation by a solar simulator (AM1.5, 100 mw/cm^2 , one sun), an I-V curve was measured. Steady photocurrent of $0.4\text{--}0.6 \text{ mA/cm}^2$ was obtained. Then STH efficiency was calculated from the following equation (1),

$$\eta(\%) = \frac{J(1.23 - E)}{I} \times 100 \quad (1)$$

where $\eta(\%)$ is solar energy conversion efficiency (STH efficiency) in %. J denotes produced photocurrent in mA/cm^2 at E . E denotes applied potential in voltage. I denotes solar irradiance, that is, one sun, $100\text{mW}/\text{cm}^2$, AM1.5. Calculated STH efficiency changed with applied potential. The maximum STH efficiency was 0.32-0.44% at 0.35V vs NHE for mesoporous TiO_2 photoelectrode.

3.2. Solar hydrogen production using mesoporous visible light responding S-doped TiO_2 (Anatase) photoelectrode

Recently, various kinds of visible light responding doped TiO_2 materials, such as nitrogen doped TiO_2 (N-doped TiO_2),⁷⁾ carbon doped TiO_2 (C-doped TiO_2)¹⁶⁾ and sulfur doped TiO_2 (S-doped TiO_2),¹⁷⁾ are reported and their photocatalytic performance for organic contaminants decomposition are studied. Therefore, we investigated photoelectrochemical water splitting using visible light responding S-doped TiO_2 photoelectrode.¹⁵⁾ S-doped TiO_2 powder was prepared from Titanium (IV) iso-propoxide ($\text{Ti}(\text{OC}_3\text{H}_7\text{O})_4$) and Thiourea ($\text{H}_2\text{NC}=\text{SNH}_2$). Ethanol mixture of two compounds was well mixed and then dried. White residue was calcined at 500°C for 3 hours. Crystallographic structure of prepared S-doped TiO_2 powder was Anatase phase. Light absorption edge of this powder expanded broadly up to 500 nm. A paste preparation and screen printing process was the same as that of non-doped TiO_2 photoelectrode. S-doped TiO_2 photoelectrode was calcined at 500°C . Photocurrents of $0.2\text{mA}/\text{cm}^2$ and $0.3\text{mA}/\text{cm}^2$ were obtained at applied potential of 0.5 V and 1.5V vs NHE, respectively, under irradiation by solar simulator. Maximum STH efficiency was 0.12-0.14% at applied potential of 0.55 V vs NHE. STH efficiency of S-doped TiO_2 photoelectrode was lower than that of non-doped TiO_2 photoelectrode though light absorption area is fairly wider than that of non-doped TiO_2 photoelectrode. Sulfur doping n band gap might accelerate charge recombination process.

3.3. Solar hydrogen production using a mesoporous WO_3 photoelectrode

WO_3 powder photocatalyst can split water efficiently and produce O_2 evolution in the presence of sacrificial reagent such as AgNO_3 aqueous solution under visible light irradiation. Light absorption edge of WO_3 is about 470 nm. Therefore, WO_3 is one of attractive materials for O_2 evolution photoelectrode. Augustynski and co-workers have extensively investigated WO_3 photoelectrodes for water splitting^{13,18,19,20)} and they obtained relatively higher photocurrent such as $3.5\text{mA}/\text{cm}^2$. We also investigated water splitting using WO_3 photoelectrode. Our WO_3 paste was composed of H_2WO_4 , PEG300, hydroxypropylcellulose and small amount of ethanol solvent. WO_3 paste was coated onto FTO glass by Doctor-blade method and calcined at 500°C for one hour. This process was repeated for increasing film thickness to obtain the maximum photocurrent. A steady state photocurrent of $2.25\text{mA}/\text{cm}^2$ was obtained in $0.1\text{N}-\text{H}_2\text{SO}_4$ solution under solar simulated light. STH efficiency of our system was 0.44% at applied potential of 0.9V vs NHE. Recently Miller and co-worker/ reported a higher photocurrent such as $3.5\text{mA}/\text{cm}^2$ using WO_3 photoelectrode prepared by low temperature reactive sputtered process.²¹⁾

3.4. Solar hydrogen production using BiVO_4 and Fe_2O_3 photoelectrodes

It is reported that BiVO_4 powder photocatalyst can also split water to O_2 evolution in the presence of sacrificial reagent such as AgNO_3 aqueous solution under visible light irradiation.²²⁾ Light absorption edge of BiVO_4 is about 550 nm. Sayama and co-worker reported STH efficiency of BiVO_4 photoelectrode system.²³⁾ It was 0.2% under 2.6 sun. We prepared BiVO_4 film photoelectrode by spin coating of concentrated precursor solution. A precursor solution of BiVO_4 was produced by polymerized complex method using $\text{BiNO}_3 \cdot 5\text{H}_2\text{O}$ and NH_4VO_3 . At applied potential of 1.5V, $0.7\text{mA}/\text{cm}^2$ of photocurrent was obtained under one sun irradiation. STH efficiency of BiVO_4 photoelectrode was 0.08% at applied potential of 0.95V.

Recently, Fe_2O_3 photoelectrode for water splitting has been becoming popular. Because a high photocurrent over $2\text{mA}/\text{cm}^2$ was reported by Graetzel and co-workers.²⁴⁾ We prepared Fe_2O_3 photoelectrode film by spin coating of solution including $\text{FeCl}_3 \cdot 6\text{H}_2\text{O}$ and organic binder in ethanol solvent. Spin coated Fe_2O_3 film on FTO glass was dried and then

calcined at 500°C for 1 hour. Obtained photocurrent was 0.4mA/cm² at applied potential of 1.5V vs NHE and STH efficiency was 0.0023% at applied potential of 1.0V.

4. FABRICATION OF EFFICIENT DYE-SENSITIZED SOLAR CELLS

In solar hydrogen production using oxide semiconductor film electrodes, STH efficiency seems to be increased significantly under the applied potential at around 1.5 V vs NHE. Such applied potential might be supplied by DSC, which is one of candidates of cost-effective photoelectrochemical solar cell developed by Graetzel.²⁵⁾ Therefore, we have been trying to improve solar cell efficiency of DSC and to fabricate a DSC sub-module with high efficiency. Recently, we could obtain 10-11% efficiency in a small black dye sensitized TiO₂ solar cell with a 5mm-by-5mm size.^{26, 27)} Furthermore, we could fabricate a 10cm-by-10cm DSC sub-module with efficiency of 8.4-9.0%.²⁸⁾ Fig. 4 shows such a sub-module of a black-dye-sensitized solar cell.

Solar cell performance of a current collecting Black dye-sensitized TiO₂ solar cell

Cell size: 10cm square
Active area of solar cell: 67.5cm²
Aperture area: 81cm²
Measuring condition: AM1.5, 100 mW/cm² (one sun)
Cell efficiency based on active area (η_{ac}): 9.0%
(I_{sc}: 1.35A, J_{sc}: 20.0mA/cm², Voc: 0.68, ff: 0.66)
Cell efficiency based on aperture area ($\eta_{aperture}$): 7.5%

Fig.4. A 10cm-by-10cm sub-module of black-dye-sensitized solar cell and its solar cell performance

We fabricated tiny black-dye-sensitized solar cells for solar hydrogen production using a tandem cell system. The one is a single cell with a 1cm-by-1cm size. A solar cell performance of single cell is η_{ac} =7.5%, J_{sc}=20.1mA/cm², Voc=0.68V and ff=0.59. The other is a two-series-connected cell with a 1cm-by-1cm size. A solar cell performance of a two-series-connected cell is η_{ac} = 6.1%, J_{sc}=8.4mA/cm², Voc= 1.4V and ff=0.52. Fig. 5. shows pictures of prepared cells.

Picture A : a single with a 1cm-by-1cm size
(η =7.5% J_{sc}=20.1mA/ cm², Voc=0.68V, ff=0.59)
Picture B : a two-series-connected cell with a 1cm-by-1cm size
(η =6.1% J_{sc}=8.4mA/ cm², Voc=1.39V, ff=0.52)

Fig. 5. Pictures of tiny black-dye-sensitized solar cells for solar hydrogen production using a tandem cell system

5. SOLAR HYDROGEN PRODUCTION BY TANDEM CELL SYSTEM USING OXIDE SEMICONDUCTOR FILM AND DYE-SENSITIZED SOLAR CELL

In order to improve STH efficiency of oxide semiconductor film photoelectrode, the tandem cell system was proposed by Swiss research group.¹⁾ DSC supplies an additional potential up to about 1.5 V to oxide semiconductor film photoelectrode in order to obtain efficient water splitting into H_2 and O_2 . This concept is shown in Figure 6. Photo-induced electron transfer mechanism of this concept is quite similar to the Z-scheme of photosynthesis. Their tandem cell is composed of a thin and transparent film oxide semiconductor photoelectrode for O_2 evolution, Pt wire counter electrode for H_2 evolution and a dye-sensitized solar cell connected to both electrodes. Figure 7 shows the structure of tandem cell system. In case of TiO_2 photoelectrode, both TiO_2 transparent thin film/FTO glass photoelectrode and Pt wire counter electrode were inserted into 0.1M-1.0M-NaOH aqueous solution and they were connected each other through DSC.

Recently, Hydrogen Solar Ltd. in London announced that they developed the tandem cell system for water splitting with STH of 7% efficiency.²⁹⁾ This efficiency is significantly high, therefore it is very interesting to study tandem cell system in detail. First of all, we studied TiO_2 system. Figure 8 shows I-V curves of three different systems under simulated solar light irradiation (AM1.5, $100\text{mW}/\text{cm}^2$, one sun). These I-V curves were measured using a two-electrode system in place of a three-electrode system using a Ag/AgCl reference electrode. Red curve shows I-V curve of mesoporous TiO_2 photoelectrode composed of TiO_2 particles with 20nm in diameter, which was already described in section 3.1. Film thickness of this mesoporous TiO_2 photoelectrode was 3μ , which was thinner than that of mesoporous TiO_2 photoelectrode used in section 3.1, that is, 10μ thickness. The onset of photocurrent of this system was 0.23V vs counter electrode. To obtain a steady state photocurrent, $0.5\text{mA}/\text{cm}^2$, at least 0.5V of applied potential is requested in this system. Blue curve shows I-V curve of a tandem cell composed of mesoporous TiO_2 photoelectrode and a single cell of black-dye-sensitized solar cell (BDSC). The onset of photocurrent of this system shifted negatively about 0.7V, which is almost the same value of the photovoltage (V_{oc}) of a single cell of BDSC, and it was -0.45V. It is clear that about $0.47\text{mA}/\text{cm}^2$ of photocurrent is able to be obtained without any applied potential in this system. Obtained photocurrent was slightly smaller than

Fig. 6. A conceptual scheme of tandem cell composed of oxide semiconductor film and DSC

Fig. 7. Structure of tandem cell system composed of oxide semiconductor photoelectrode and DSC

that of Red curve. Some increase of resistivity in tandem cell system might occur. Green curve shows I-V curve of the other tandem cell system composed of a mesoporous TiO_2 photoelectrode and a two-series connected cell of BDSC. The onset of photocurrent of this system shifted again negatively further to -1.2V. However photocurrent was not improved. This means a tandem cell system composed of a two-series-connected BDSC, which has a photovoltage of 1.4V, is not necessary to use for improving photocurrent. STH efficiency of this tandem cell system using a single cell was 0.53%, which was 2 times higher than that, 0.32%, of mesoporous TiO_2 photoelectrode with 10 μ thickness at the applied potential of 0.35 V vs RHE.

Figure 9 shows I-V curves of three different systems under simulated solar light irradiation (AM1.5, 100mW/cm² one sun). As the case of TiO_2 photoelectrode systems, I-V curves of WO_3 photoelectrode systems were also measured using a two-electrode system. Red curve shows I-V curve of mesoporous WO_3 photoelectrode, which was already described in section 3.3. Film thickness of this mesoporous WO_3 photoelectrode was about 1.5 μ . The onset of photocurrent of this system was about 0.7V vs counter electrode. To obtain a steady state photocurrent, 2.25mA/cm², at least 1.2 V of applied potential is requested in this system. Blue curve shows I-V curve of a tandem cell system composed of a mesoporous WO_3 photoelectrode and a single cell of BDSC. The onset of photocurrent of this system shifted negatively about 0.7V, which is almost the same value of the photovoltage (V_{oc}) of a single cell of BDSC, and it was about 0.05V. About 0.2 mA/cm² of photocurrent was obtained without any applied potential in this system. The improvement of photocurrent was not significant. This means a single cell tandem system is not useful for WO_3 photoelectrode system. Green curve shows I-V curve of the other tandem cell system composed of a mesoporous WO_3 photoelectrode and a two-series connected cell of BDSC, which has a photovoltage of 1.4V. The onset of photocurrent of this system shifted about 0.7 V again negatively down to -0.7 V. In this case, photocurrent at 0 V applied potential was 2.1mA/cm². STH efficiency of this tandem cell system using a two-series connected cell of BDSC was 2.58%, which was about 6 times higher than that, 0.44 % , of mesoporous WO_3 photoelectrode only at the applied potential of 0.9 V vs RHE. A significant improvement of STH efficiency was observed by a tandem cell system composed of a mesoporous WO_3 photoelectrode and a two-series connected cell of BDSC. At applied potential of 1.4 vs counter electrode, 2.25mA/cm of steady state photocurrent was obtained. Therefore, an ideal STH efficiency obtained from this WO_3 photoelectrode will become 2.76%.

Fig. 8 Three I-V curves of TiO_2 photoelectrode systems under simulated solar light irradiation (AM1.5, 100mW/cm², one sun).

Electrolyte solution used: 0.1N-NaOH aqueous solution, Red curve: a mesoporous TiO_2 photoelectrode system (TiO_2 photoelectrode only), Blue curve: a tandem cell system composed of a mesoporous TiO_2 photoelectrode and a single BDSC, Green curve: a tandem cell system composed of a mesoporous TiO_2 photoelectrode and a two-series-connected BDSC.

Fig. 9 Three I-V curves of WO_3 photoelectrode systems under simulated solar light irradiation (AM1.5, 100mW/cm² one sun).

Electrolyte solution used: 0.1N- H_2SO_4 aqueous solution, Red curve: a mesoporous WO_3 photoelectrode system (WO_3 photoelectrode only), Blue curve: a tandem cell system composed of a mesoporous WO_3 photoelectrode and a single BDSC, Green curve: a tandem cell system composed of a mesoporous WO_3 photoelectrode and a two-series-connected BDSC.

Table 1 summarizes performance of solar hydrogen production over various kinds of oxide semiconductor photoelectrodes conducted by our group and data obtained from current publications. As to WO₃ photoelectrode, our result is not the best datum among them. Photocurrent at 1.5 V applied potential changes from 2.2mA/cm² to 3.6mA/cm². It depends on preparation condition of WO₃ photoelectrode and measuring condition such as electrolyte species (H₂SO₄, HClO₄, H₃PO₄) and its concentration. Miller and co-workers prepared WO₃ film by low temperature reactive sputter process.²¹⁾ On the other hand, Augustynski group and our group prepared WO₃ film using wet process. It is speculated that more than 4.0 mA/cm² will be obtained by optimization of preparation and reaction conditions. This means about 5% of STH efficiency might be possible using tandem cell system. It is also possible to fabricate monolithic tandem cells without external wiring to connect oxide semiconductor film photoelectrode and DSC. This has a great advantage to simple production of solar hydrogen. One of examples was prepared by Park and Bard.³⁰⁾ STH efficiency of our Fe₂O₃ tandem cell system was about 0.5%. This is almost the same efficiency of our TiO₂ photoelectrode at this moment. However, Graetzel and co-workers reported such a high photocurrent as 2.0-3.0 mA/cm² at applied potential of 1.5 V by changing the morphology of Fe₂O₃ and modification of surface by other element ions.^{14,24)} Therefore Fe₂O₃ photoelectrode might be also promising. In addition, Fe₂O₃ is abundant, low-cost and robust materials. Further efficiency improvement is requested. BiVO₄ has absorption edge at 550nm, which is located at the middle between that of Fe₂O₃, 600 nm, and that of WO₃, 470 nm. Therefore BiVO₄ is also attractive material as oxygen evolution photoelectrode. Obtained photocurrent at 1.5V was 0.7mA/cm² and STH efficiency of tandem cell system was 0.86% at this moment. However, further improvement is strongly anticipated by process optimization.

Table 1 Performance of solar hydrogen production over oxide semiconductor photoelectrodes

Photoelectrode	Electrolyte	Onset of I-V curve	Photocurrent at 1V	Photocurrent at 1.5V	$\eta_{p.e.}$	η_{tandem}
		V vs NHE	mA/ cm ²	mA/ cm ²	%	%
TiO ₂ (Anatase)	0.1M-NaOH	0.16	0.44	0.44	0.31 at 0.35V	0.54
TiO ₂ (Anatase)	1.0M-NaOH	0.17	0.58	0.58	0.44 at 0.35V	0.71
S-doped TiO ₂	0.1M-NaOH	0.19	0.20	0.30	0.12 at 0.55V	0.37
WO ₃	0.1M-H ₂ SO ₄	0.70	1.80	2.25	0.44 at 0.90V	2.77
BiVO ₄	0.1M-NaOH	0.40	0.30	0.70	0.08 at 0.95V	0.86
Fe ₂ O ₃	0.1M-NaOH	0.95	0.01	0.40	0.003 at 1.0V	0.49
<hr/>						
WO ₃	1.0M-HClO ₄			2.4-2.5	J. Augustynski et al. ¹³⁾	
WO ₃	3.0M-H ₂ SO ₄			3.5-3.6	J. Augustynski et al. ¹⁹⁾	
WO ₃	0.33M-H ₃ PO ₄			3.4 *	E. L. Miller et al. ²¹⁾	
Fe ₂ O ₃	1.0M-NaOH			2.5 * *	M. Graetzel et al. ²⁴⁾	
Fe ₂ O ₃	1.0M-NaOH			1.9	M. Graetzel et al. ¹⁴⁾	

$\eta_{p.e.}$: STH efficiency of oxide semiconductor photoelectrode at the applied potential of 0.35-0.90 V

η_{tandem} : STH efficiency of tandem cell system composed of a oxide photoelectrode and a two-series-connected DSC (Voc = 1.5 V)

Irradiation source: Solar simulator (AM1.5, 100mw/ cm², one sun)

Size of photoelectrode: 1cm-by-1cm

*: Sputtered film

** : 130mw/ cm² (1.3 sun)

6. CONCLUSION

Solar hydrogen production using tandem cell system composed of an oxide semiconductor photoelectrode and a two-series-connected dye-sensitized solar cell is very promising. At present, STH efficiency is around 3-4%. However, much improvement of STH efficiency is anticipated by optimization of photoelectrode preparation and water splitting reaction conditions. New oxide semiconductor materials as photoelectrodes are also expected to be developed. It is speculated that more than 5% STH efficiency will be obtained by tandem cell system in near future. This suggests a cost-effective and practical solar hydrogen production process might be brought by this tandem cell system.

ACKNOWLEDGEMENT

Authors would like to thank The Nissan Science Foundation for their financial support to this research.

REFERENCES

1. J. Augustynski, G. Calzaferri, J. C. Courvoisier, M. Graetzel, Hydrogen Energy Progress XI, Proceedings of the World Hydrogen Energy Conference, **3**, 2379-2387(1996).
2. A. Fujishima, K. Honda, *Nature*, **238**, 37-38(1972).
3. "Photocatalysis" edited by M. Kaneko and I. Okura, Kodansha-Springer,(2002).
4. A. Kudo and H. Kato, *Chem. Phys. Lett.*, **331**, 337(2000).
5. K. Sayama and H. Arakawa, *J. Chem. Soc., Faraday Trans.*, **93**, 1647-1654(1996).
6. H. Arakawa and K. Sayama, *Catalysis Surveys from Japan*, **4**, 75-80(2000).
7. R. Asahi, T. Morikawa, T. Ohwaki, K. Aoki, Y. Taga, *Science*, **293**, 269(2001).
8. Z. Zou, J. Ye, H. Arakawa, *Chem. Phys. Lett.*, **343**, 303(2001).
9. Z. Zou, J. Ye, H. Arakawa, *Catal. Lett.*, **75**, 209(2001).
10. Z. Zou, J. Ye, K. Sayama, H. Arakawa, *Nature*, **414**, 625-627(2001).
11. K. Maeda, T. Takata, M. Hara, N. Saito, Y. Inoue, H. Kobayashi, K. Domen, *J. Am. Chem. Soc.*, **127**, 8286(2005).
12. K. Sayama, K. Mukasa, R. Abe, Y. Abe, H. Arakawa, *Chem. Commun.*, **2001**, 2416.
13. C. Santato, M. Ulman, J. Augustynski, *J. Phys. Chem.*, **105**, 936(2001).
14. I. Caser, A. Kay, J. A. Gonzalez, M. Graetzel, *J. Am. Chem. Soc.*, **128**, 4582-4583(2006).
15. H. Arakawa, C. Shiraishi, A. Takeuchi, T. Yamaguchi, *Proc. of SPIE*, **6340**, 63400G(2006).
16. S. U. M. Khan, M. Al-Shahny, W. B. Jr. Ingler, *Science*, **297**, 2243-2245(2002).
17. T. Ohno, M. Akiyoshi, T. Umebayashi, K. Asai, T. Mitsui, M. Matsumura, *Applied. Catal. A: General*, **265**, 115-121(2004).
18. C. Santato, M. Odziemkowski, M. Ulman, J. Augustynski, *J. Am. Chem. Soc.*, **123**, 10639(2001).
19. R. Solaraska, C. Santato, C. Jorand-Sartoretti, M. Ulmann, J. Augustynski, *J. Appl. Electrochem.*, **35**, 715(2005).
20. J. Augustynski, R. Solaraska, H. Hageman, C. Santato, *Proc. of SPIE*, **6340**, 63400J(2006).
21. E. L. Miller, B. Marsen, B. Cole, M. Lum, *Electrochemical and Solid-State Letters*, **9**, G248(2006).
22. A. Kudo, K. Omori, H. Kato, *J. Am. Chem. Soc.*, **121**, 11459(1999).
23. K. Sayama, A. Nomura, T. Arai, T. Sugita, R. Abe, M. Yanagida, T. Oi, Y. Iwasaki, Y. Abe, H. Sugihara, *J. Phys. Chem.*, **110**, 11352(2006).
24. A. Duret, M. Graetzel, *J. Phys. Chem.*, **109**, 17184(2005).
25. M. Graetzel, *Nature*, **414**, 338-334(2001).
26. Z.-S. Wang, H. Kawauchi, T. Kashima, H. Arakawa, *Coordination Chemistry Review*, **248**, 1381(2004).
27. Z.-S. Wang, T. Yamaguchi, H. Sugihara, H. Arakawa, *Langmuir*, **21**, 4272(2005).
28. H. Arakawa, T. Yamaguchi, A. Takeuchi, S. Agatsuma, *2006 IEEE 4th World Conference on Photovoltaic Energy Conversion*, **1**, 36(2006).
29. Hydrogen Solar Ltd., <http://www.hydrogensolar.com>
30. J. H. Park, A. J. Bard, *Electrochemical and Solid-State Letters*, **9**, E5(2006).