PROCEEDINGS OF SPIE

SPIDigitalLibrary.org/conference-proceedings-of-spie

Front Matter: Volume 7103

, "Front Matter: Volume 7103," Proc. SPIE 7103, Illumination Optics, 710301
(15 October 2008); doi: 10.1117/12.817251

SPIE.

Event: Optical Systems Design, 2008, Glasgow, Scotland, United Kingdom

PROCEEDINGS OF SPIE

Illumination Optics

Tina E. Kidger
Stuart R. David
Editors

2–3 September 2008
Glasgow, United Kingdom

Sponsored by
SPIE Europe

Cosponsored by
Scottish Optoelectronic Association (United Kingdom)

Cooperating Organisations
EFDS—Europäische Forschungsgesellschaft Dünne Schichten e.V. (Germany)
Institute of Photonics (United Kingdom)
OpTIC Technium (United Kingdom)
WOF—Welsh Optoelectronics Forum (United Kingdom)

Published by
SPIE

Volume 7103

Proceedings of SPIE, 0277-786X, v. 7103

SPIE is an international society advancing an interdisciplinary approach to the science and application of light.

The papers included in this volume were part of the technical conference cited on the cover and title page. Papers were selected and subject to review by the editors and conference program committee. Some conference presentations may not be available for publication. The papers published in these proceedings reflect the work and thoughts of the authors and are published herein as submitted. The publisher is not responsible for the validity of the information or for any outcomes resulting from reliance thereon.

Please use the following format to cite material from this book:

Author(s), "Title of Paper," in *Illumination Optics*, edited by Tina E. Kidger, Stuart R. David, Proceedings of SPIE Vol. 7103 (SPIE, Bellingham, WA, 2008) Article CID Number.

ISSN 0277-786X

ISBN 9780819473332

Published by

SPIE

P.O. Box 10, Bellingham, Washington 98227-0010 USA

Telephone +1 360 676 3290 (Pacific Time) · Fax +1 360 647 1445

SPIE.org

Copyright © 2008, Society of Photo-Optical Instrumentation Engineers

Copying of material in this book for internal or personal use, or for the internal or personal use of specific clients, beyond the fair use provisions granted by the U.S. Copyright Law is authorized by SPIE subject to payment of copying fees. The Transactional Reporting Service base fee for this volume is \$18.00 per article (or portion thereof), which should be paid directly to the Copyright Clearance Center (CCC), 222 Rosewood Drive, Danvers, MA 01923. Payment may also be made electronically through CCC Online at copyright.com. Other copying for republication, resale, advertising or promotion, or any form of systematic or multiple reproduction of any material in this book is prohibited except with permission in writing from the publisher. The CCC fee code is 0277-786X/08/\$18.00.

Printed in the United States of America.

Publication of record for individual papers is online in the SPIE Digital Library.

SPIDigitalLibrary.org

Paper Numbering: Proceedings of SPIE follow an e-First publication model, with papers published first online and then in print and on CD-ROM. Papers are published as they are submitted and meet publication criteria. A unique, consistent, permanent citation identifier (CID) number is assigned to each article at the time of the first publication. Utilization of CIDs allows articles to be fully citable as soon they are published online, and connects the same identifier to all online, print, and electronic versions of the publication. SPIE uses a six-digit CID article numbering system in which:

- The first four digits correspond to the SPIE volume number.
- The last two digits indicate publication order within the volume using a Base 36 numbering system employing both numerals and letters. These two-number sets start with 00, 01, 02, 03, 04, 05, 06, 07, 08, 09, 0A, 0B ... 0Z, followed by 10-1Z, 20-2Z, etc.

The CID number appears on each page of the manuscript. The complete citation is used on the first page, and an abbreviated version on subsequent pages. Numbers in the index correspond to the last two digits of the six-digit CID number.

Contents

vii	<i>Conference Committee</i>
ix	<i>Introduction</i>
xi	<i>Optical system design reliance on technology development (Plenary Presentation)</i> <i>I. A. Neil, ScotOptix (Switzerland)</i>
xxxiii	<i>A perspective on the design of head-worn displays (Plenary Presentation)</i> <i>J. Rolland, O. Cakmakci, F. Fournier, S. Vo, CREOL, The College of Optics and Photonics, Univ. of Central Florida (United States)</i>

SESSION 1 OPTIMISATION

7103 02	Optimization, sensitivity analysis, and robust design using response surface modeling (Keynote Paper) [7103-01] E. Lenderink, Philips Lighting (Netherlands); P. Stehouwer, Ctr. for Quantitative Methods (Netherlands)
7103 03	SSL design with LED binning tolerances [7103-02] R. J. Koschel, Photon Engineering, LLC (United States) and College of Optical, The Univ. of Arizona (United States)
7103 04	TIR optics for non-rotationally symmetric illumination design [7103-03] A. Domhardt, S. Weingaertner, Univ. of Karlsruhe (Germany); U. Rohlfing, Univ. of Applied Sciences, Darmstadt (Germany); U. Lemmer, Univ. of Karlsruhe (Germany)
7103 05	Illumination design with virtually reflecting/refracting surfaces [7103-05] U. Rohlfing, Univ. of Applied Sciences Darmstadt (Germany); A. Domhardt, Univ. of Karlsruhe (Germany)

SESSION 2 SOURCES AND COUPLING

7103 06	A new method for designing, improving, and measuring hollow light guides (Invited Paper) [7103-07] P. Belloni, Univ. of Applied Sciences (Germany); D. Vazquez-Molini, A. A. Fernandez-Balbuena, E. Bernabeu, Univ. Complutense de Madrid (Spain)
7103 07	Recent advances in mixing rods [7103-08] W. J. Cassarly, Optical Research Associates (United States)
7103 08	An LED multiplexer with improved efficiency [7103-09] J. Cobb, Corning Inc. (United States)

- 7103 09 **Predicting solutions toward improved high power white LED light sources: a combined theoretical and experimental study** [7103-12]
C. Sommer, F. P. Wenzl, L. Kuna, E. Zinterl, J. R. Krenn, Joanneum Research Jorschungsges.mbH (Austria); P. Hartmann, P. Pachler, M. Schweighart, S. Tasch, TridonicAtco Optoelectronics GmbH (Austria)

SESSION 3 APPLICATIONS I

- 7103 0A **High-efficiency free-form nonimaging condenser overcoming rotational symmetry limitations (Keynote Paper)** [7103-13]
J. C. Miñano, P. Benítez, Univ. Politécnica de Madrid (Spain) and LPI (United States); J. Blen, LPI (United States); A. Santamaría, Univ. Politécnica de Madrid (Spain)
- 7103 0B **Modeling EUVL illumination systems** [7103-14]
D. G. Smith, Nikon Research Corp. of America (United States)
- 7103 0C **Sensitivity of an illumination system to lamp flicker** [7103-15]
H. Rehn, OSRAM Display/Optic (Germany)
- 7103 0D **Novel technique for solar power illumination using plastic optical fibres** [7103-16]
J. Munisami, D. Kalymnios, London Metropolitan Univ. (United Kingdom)
- 7103 0E **Highly efficient photometrics tailoring by means of optimized bell-shaped lens arrays** [7103-27]
M. Manca, Univ. di Formazione, Univ. del Salento (Italy); F. Quercetti, M. Gattari, iGuzzini Illuminazione spa (Italy); R. Cingolani, G. Gigli, Univ. di Formazione, Univ. del Salento (Italy)
- 7103 0F **Unconventional single element optical designs for complex illumination systems** [7103-04]
N. McGee, Global Display Solutions SpA (Italy)

SESSION 4 APPLICATIONS II

- 7103 0G **Köhler integrators embedded into illumination optics add functionality (Invited Paper)** [7103-19]
O. Dross, R. Mohedano, M. Hernández, Light Prescriptions Innovators Europe (Spain); A. Cvetkovic, Univ. Politécnica de Madrid (Spain); J. C. Miñano, P. Benítez, Univ. Politécnica de Madrid (Spain) and LPI (United States)
- 7103 0H **Street-lighting with LEDs** [7103-20]
A. Timinger, Optics and Energy Concepts AG (Germany); H. Ries, Optics and Energy Concepts AG (Germany) and Philipps-Univ. Marburg (Germany)
- 7103 0I **Optimization of single reflectors for extended sources** [7103-21]
F. R. Fournier, College of Optics and Photonics, Univ. of Central Florida (United States); W. J. Cassarly, Optical Research Associates (United States); J. P. Rolland, College of Optics and Photonics, Univ. of Central Florida (United States)
- 7103 0J **Modelling of a laser-pumped light source for endoscopic surgery** [7103-23]
V. J. Nadeau, D. S. Elson, G. B. Hanna, M. A. A. Neil, Imperial College London (United Kingdom)

- 7103 0K **Secondary optical design for LED illumination using freeform lens** [7103-24]
Y. Ding, X. Liu, Z. Zheng, P. Gu, State Key Lab. of Modern Optical Instrumentation (China)

POSTER SESSION

- 7103 0L **Neural network implementation for an optical model of LCD backlight module** [7103-26]
C.-J. Li, Y.-C. Fang, M.-C. Cheng, National Kaohsiung First Univ. of Science and Technology (Taiwan)

Author Index

Conference Committee

Symposium Chair

David M. Williamson, West Malvern (United Kingdom); NRCA Fellow,
Nikon Research Corporation of America (USA)

Symposium Co-Chairs

Andreas Tünnermann, Fraunhofer-Institut für Angewandte Optik und
Feinmechanik (Germany)

Jean-Louis Meyzonnette, Institut d'Optique, Ecole Supérieure
d'Optique (France)

Conference Chairs

Tina E. Kidger, Kidger Optics Associates (United Kingdom)

Stuart R. David, Optical Research Associates (United States)

Program Committee

Pablo Benítez, Universidad Politécnica de Madrid (Spain)

William J. Cassarly, Optical Research Associates (United States)

Joshua M. Cobb, Corning Inc. (United States)

R. John Koshel, College of Optical Sciences, University of Arizona
(United States)

Juan C. Miñano, Universidad Politécnica de Madrid (Spain)

Andreas L. Timinger, Optics and Energy Concepts AG (Germany)

Teus W. Tukker, Philips Lighting B.V. (Netherlands)

Session Chairs

- 1 Optimisation
Andreas L. Timinger, Optics and Energy Concepts AG (Germany)
- 2 Sources and Coupling
Stuart R. David, Optical Research Associates (United States)
- 3 Applications I
Joshua M. Cobb, Corning Inc. (United States)
- 4 Applications II
R. John Koshel, College of Optical Sciences, University of Arizona
(United States)

Introduction

I would like to invite you all to enjoy the state-of-the-art material presented in these proceedings of the first European Illumination Optics Conference.

When I was asked at SPIE Europe Optical Systems Design, Jena (2005) to chair a conference at Glasgow, Scotland in 2008, I agreed and suggested that we should have an Illumination optics conference. Illumination optics, although it has been around for many centuries as an engineering skill, has recently become of much more interest to many engineers and lighting practitioners especially due to the advances in light emitting diodes as illumination sources. The fairly recent development of both CAD and illumination design software, along with hollow, flexible and solid light transmitting waveguides and solid state illumination sources, has added new and exciting interest to illumination design. This excitement is embodied in the material you will find presented in this proceedings volume. The conference and session chairpersons, have received many compliments about the quality and value of the technical content of these presentations and I hope you will find the same to be true for you.

It is my great pleasure to have brought this conference together along with my co-chair, session chairs and committee members and to have so many excellent speakers taking part. I would like to take this opportunity to thank my co-chair, Stuart David, and also the session chairs, John Koshel, Joshua Cobb, and Andreas Timinger, for their work in bringing together such a prestigious group of authors for this conference and hence for this volume.

I wish you every success in understanding, further developing, and creatively utilizing the material in these proceedings for the enhancement it may bring to our global society, your particular area of vocational endeavour, and possibly yourself.

Tina E. Kidger
Stuart R. David

Optical system design reliance on technology development

Iain A. Neil

ScotOptix

Via Miravalle 25A, CH-6900 Massagno, Switzerland

++41 (0)91 950 0158 (voice & fax)

++41 (0)79 398 5524 (mobile)

scotoptix@aol.com

WELCOME

**Firstly, thanks goes to SPIE,
the organizing committee, Chairs
and Co-Chairs of the Conference
for acceptance of this presentation**

INTRODUCTION

Before commencing with an outline of the presentation an explanation of the the definitions used throughout is given

DEFINITIONS

- ① **Technology development is the progression over time of manufactured optical components:**
 - **Materials $\approx$ optical substrates**
 - **Coatings $\approx$ multi-layer thin films**
 - **Surfaces $\approx$ optical surface profiles**
- ② **Optical design software is a tool to apply technology**
- ③ **Optical designer 'creates' the optics portion of the of the optical system design utilizing optical design software to apply technology**
- ④ **FOV is Field of View & NA is Numerical Aperture**

DEFINITIONS (Cont'd)

- ⑤ Object is to the left and Image is to the right unless otherwise shown
- ⑥ Three wavebands discussed:
 - Infrared $\approx 0.7\text{-}1.5, 3\text{-}5$ & $8\text{-}13\mu\text{m}$
(700-1500, 3000-5000 & 8000-13000nm)
 - Visible $\approx 0.435\text{-}0.656\mu\text{m}$
(435-656nm)
 - Ultraviolet $\approx 0.434\text{-}0.013\mu\text{m}$
(434.4-13.4nm)

OUTLINE

- By way of mainly the US Patent database, examples are given to illustrate the reliance of optical system design on key technology
- The examples are categorized by waveband of operation and partly chronologically
- Performance characteristics are not discussed but all examples may be considered high performance for their intended applications

WAVEBAND 1
INFRARED

EXAMPLE 1.1
PETZVAL OBJECTIVE – SECURITY

Passively Athermalized System
EFL=51mm F/1.5 FOVØ=5° Waveband=8-13µm

KEY TECHNOLOGY	
✓	MATERIAL
	COATING
	SURFACE
BENEFITS	
	SOLID STATE
	ROBUST
ISSUES	
	TOXIC MATERIAL
	MATERIAL QUALITY

US Pat. No. 4,505,535 A1 I.A.Neil Mar. 19, 1985

EXAMPLE 1.2a
ZOOM TELESCOPE – SECURITY

EXAMPLE 1.2b
ZOOM TELESCOPE – SECURITY

Compact Mechanically Compensated Zoom System
Zoom Ratio=5x Exit Pupil Ø=10mm & FOVØ=72° Waveband=8-13µm

KEY TECHNOLOGY	
	MATERIAL
✓	COATING
	SURFACE
BENEFITS	
COMPACT	
ISSUES	
NONE	

US Pat. No. US4,659,171 A1 I.A.Neil Apr. 21, 1987

EXAMPLE 1.3a
ZOOM TELESCOPE – SECURITY

SPIE Europe
Optical Systems Design

Glasgow, Scotland, United Kingdom – 2nd September 2008

EXAMPLE 1.3b
ZOOM TELESCOPE – SECURITY

Compact Optically Compensated Zoom System
Zoom Ratio=9x Exit Pupil Ø=14.4mm & FOVØ=60° Waveband=8-13µm

US Pat. No. 4,632,498 A1 I.A.Neil Dec. 30, 1986

KEY TECHNOLOGY	
	MATERIAL
✓	COATING
✓	SURFACE
BENEFITS	
COMPACT	
SIMPLE MECHANICS	
ISSUES	
FOCUS DRIFT THROUGH ZOOM	
ASPHERE COST	

SPIE Europe
Optical Systems Design

Glasgow, Scotland, United Kingdom – 2nd September 2008

EXAMPLE 1.4
OBJECTIVE – SECURITY

Passively Athermalized & Color Corrected Air Spaced Doublet
with Diffractive Surface
Waveband=8-13µm (possibly 3-5µm depending on materials)

US Pat. No. 5,504,628 A1 J.F.Borchard Apr. 2, 1996

KEY TECHNOLOGY	
✓	MATERIAL
	COATING
✓	SURFACE
BENEFITS	
	SOLID STATE
	ROBUST
ISSUES	
	SECONDARY COLOR
	LONG LENGTH

EXAMPLE 1.5a
ZOOM OBJECTIVE – SECURITY

EXAMPLE 1.5b
ZOOM OBJECTIVE – SECURITY

Compound Zoom System
Zoom Ratio=180x EFL=6.7-1201mm F/2-5.84 FOVØ=64.5-0.4°
Wavebands=3-5µm or 8-13µm

KEY TECHNOLOGY	
	MATERIAL
✓	COATING
✓	SURFACE
BENEFITS	
HIGH ZOOM RATIO	
ISSUES	
COMPLEX MECHANICS	
IMAGE F/NO VARIES	
ASPHERE COST	

US Pat. No. 7,224,535 B2 I.A.Neil May 29, 2007

WAVEBAND 2
VISIBLE

EXAMPLE 2.1

COMPACT CAMERA ZOOM OBJECTIVE – PHOTOGRAPHIC CONSUMER

Zoom Objective System with 2x Zoom Ratio
EFL=35.7-68.5mm F/3.5-6.8 ImageØ=43.2mm Waveband=Visible

KEY TECHNOLOGY	
	MATERIAL
	COATING
✓	SURFACE
BENEFITS	
	SIMPLE
	COMPACT
	LOW COST
ISSUES	
	MOLDED ASPHERES

US Pat. No. 4,936,661 A1 E.I.Betensky, M.H.Kreitzer & J.Moskovich Jun. 26, 1990

EXAMPLE 2.2a

TELEPHOTO OBJECTIVE – PHOTOGRAPHIC CINE

Passively Athermalized & Color Corrected System with Liquid Elements
EFL=693mm F/2.75 ImageØ=28.9mm Waveband=435-656nm

KEY TECHNOLOGY	
✓	MATERIAL
✓	COATING
	SURFACE
BENEFITS	
	LOW COST GLASSES
	COMPACT
ISSUES	
	LIQUID DISCOLORATION
	LOW TEMPERATURE

US Pat. No. 5,638,215 A1 I.A.Neil Jun. 10, 1997

EXAMPLE 2.2b

TELEPHOTO OBJECTIVE – PHOTOGRAPHIC CINE

EXAMPLE 2.3a

MACRO FOCUS ZOOM OBJECTIVE – PHOTOGRAPHIC CINE

EXAMPLE 2.3b
MACRO FOCUS ZOOM OBJECTIVE
– PHOTOGRAPHIC CINE

Close Focus Object/Image Height Ratio = 2.5:1 (At Long Focal Length)

EXAMPLE 2.3c
ZOOM OBJECTIVE – PHOTOGRAPHIC CINE

Macro Focus Zoom System with 3.5x Zoom Ratio
EFL=14.5-50mm F/2.2 ImageØ=28.9mm Waveband=455-644nm

KEY TECHNOLOGY	
	MATERIAL
✓	COATING
✓	SURFACE
BENEFITS	
VERSATILE	
FIXED FOCAL LENGTH OPTION	
ISSUES	
COMPLEX MECHANICS	
ASPHERE COST	

EXAMPLE 2.4a
ZOOM OBJECTIVE – PHOTOGRAPHIC CINE

EXAMPLE 2.4b
ZOOM OBJECTIVE – PHOTOGRAPHIC CINE

Compact Zoom Objective System with 4.7x Zoom Ratio
EFL=19-90mm F/2.7 ImageØ=27.8mm Waveband=455-644nm

US Pat. No. 7,123,421 B1 J.Moskovich, I.A.Neil & T.Yamanashi Oct. 17, 2006

KEY TECHNOLOGY	
✓	MATERIAL
✓	COATING
✓	SURFACE
BENEFITS	
COMPACT	
VERSATILE	
FIXED FOCAL LENGTH OPTION	
ISSUES	
COMPLEX MECHANICS	
ASPHERE COST	

EXAMPLE 2.5

OBJECTIVE – PHOTOGRAPHIC PROSUMER

Telephoto System with Diffractive Surface
EFL=780mm F/5.8 ImageØ=43.2mm Waveband=435-656nm

KEY TECHNOLOGY	
✓	MATERIAL
	COATING
✓	SURFACE
BENEFITS	
	COMPACT
	COLOR CORRECTED
	REDUCED NO. OF EXOTIC GLASSES
ISSUES	
	FLARE

US Pat. Pub. No. 2008/0088950 A1 H.Endo Apr. 17, 2008

EXAMPLE 2.6a

ZOOM OBJECTIVE – PHOTOGRAPHIC HDTV

THROUGH ZOOM
(INFINITY FOCUS)

EXAMPLE 2.6b

ZOOM OBJECTIVE – PHOTOGRAPHIC HDTV

EXAMPLE 2.6c

ZOOM OBJECTIVE – PHOTOGRAPHIC HDTV

Compound Zoom System with 300x Zoom Ratio
EFL=7-2100mm F/2-13 ImageØ=11mm Waveband=Visible

US Pat. No. 6,691,188 B2 E.I.Betensky, J.B.Caldwell, I.A.Neil & T.Yamanashi Nov. 1, 2005

KEY TECHNOLOGY	
✓	MATERIAL
✓	COATING
✓	SURFACE
BENEFITS	
LARGE ZOOM RATIO	
VERSATILE	
ISSUES	
COMPLEX MECHANICS	
ASPHERE COST	

WAVEBAND 3
ULTRAVIOLET

EXAMPLE 3.1

PROJECTION RELAY LENS – MICROLITHOGRAPHIC

All Refractive Projection System
RELAY=5:1 NA=0.57 ImageØ=31.2mm Wavelengths=193, 248 & 365nm

KEY TECHNOLOGY	
	MATERIAL
✓	COATING
✓	SURFACE
BENEFITS	
RESOLUTION	
ISSUES	
INHOMOGENEITY & BIREFRINGENCE	
SURFACE QUALITY	
ALIGNMENT	

US Reissued Pat. No. RE 37,846E H.Matsuzawa, M.Kobayashi, K.Endo & Y.Suenaga Sep. 17, 2002

EXAMPLE 3.2

PROJECTION RELAY LENS – MICROLITHOGRAPHIC

Refractive/Reflective Projection System
RELAY=4:1 NA=0.45 ImageØ=30mm Wavelengths=240-256nm

KEY TECHNOLOGY	
✓	MATERIAL
✓	COATING
	SURFACE
BENEFITS	
RESOLUTION	
ISSUES	
ALIGNMENT	

US Pat. No. 4,953,960 A1 D.M.Williamson Sep. 4, 1990

SPIE Europe
Optical Systems Design

Glasgow, Scotland, United Kingdom – 2nd September 2008

31

EXAMPLE 3.3

PROJECTION RELAY OPTICS – MICROLITHOGRAPHIC

All Reflective Projection System
RELAY=4:1 NA=0.25 ImageØ=31mm Wavelengths=13.4nm & <200nm

KEY TECHNOLOGY	
	MATERIAL
✓	COATING
✓	SURFACE
BENEFITS	
HIGH RESOLUTION	
ISSUES	
@13.4nm <10% TRANSMISSION WITH COATINGS	
ASPHERE COST	
ALIGNMENT	

US Pat. No. 5,815,310 A1 D.M.Williamson Sep. 29, 1998

SPIE Europe
Optical Systems Design

Glasgow, Scotland, United Kingdom – 2nd September 2008

32

WAVEBAND 4 MULTIPLE

EXAMPLE 4.1 OBJECTIVE – SECURITY

Dual Waveband System

F/4.5(elev), F/1.5(azim) & F/2.3(average) FOV $\varnothing$ =40°(elev.) & 53°(azim.)

Wavebands=Visible & 8-13 μ m

KEY TECHNOLOGY	
	MATERIAL
✓	COATING
✓	SURFACE
BENEFITS	
	COMPACT
	SOLID STATE
	ROBUST
ISSUES	
	ASPHERE COST

US Pat. No. 5,847,879 A1 L.G.Cook Dec. 8, 1998

EXAMPLE 4.2a

OBJECTIVE – SURVEILLANCE

Compact Multi-waveband Wide Angle Objective

FOV 15°- 80° x 360°

Wavebands=Visible, 0.7-1.5µm & 3-5µm

SINGLE SYSTEM

SPIE Europe
Optical Systems Design

Glasgow, Scotland, United Kingdom – 2nd September 2008

35

EXAMPLE 4.2b

OBJECTIVE – SURVEILLANCE

SPIE Europe
Optical Systems Design

Glasgow, Scotland, United Kingdom – 2nd September 2008

36

EXAMPLE 4.2c

OBJECTIVE – SURVEILLANCE

EXAMPLE 4.2d

OBJECTIVE – SURVEILLANCE

KEY TECHNOLOGY SUMMARY

	WAVE BAND															
	INFRARED					VISIBLE						ULTRAVIOLET			MULTI	
EXAMPLE	1.1	1.2	1.3	1.4	1.5	2.1	2.2	2.3	2.4	2.5	2.6	3.1	3.2	3.3	4.1	4.2
CIRCA	80's	80's	80's	90's	00's	90's	90's	00's	00's	00's	00's	90's	90's	90's	90's	00's
MATERIAL	✓			✓			✓		✓	✓	✓		✓			✓
COATING		✓	✓		✓		✓	✓	✓		✓	✓	✓	✓	✓	✓
SURFACE			✓	✓	✓	✓		✓	✓	✓	✓	✓		✓	✓	✓

CONCLUSION

- Usually technology provides 'improvements' but occasionally it is 'disruptive' in that it dramatically changes the optical system design such as enabling a new form of design
- In the specific case of disruptive technology this usually appears to happen separately in either materials, coatings or surfaces
- No apparent trend in technology development except:

"Necessity is the mother of invention"

Plato c. 400 BC

ACKNOWLEDGEMENTS

**Thanks goes to the following individuals
for contributions to this presentation**

David W. Samuelson

David M. Williamson

Andy Wood

A Perspective on the Design of Head-Worn Displays

Jannick Rolland with

Ozan Cakmakci, Florian Fournier, and Sophie Vo

CREOL, The College of Optics and Photonics
the University of Central Florida

<http://odalab.ucf.edu>
jannick@odalab.ucf.edu

Highlights

Introduction

Applications

Prior Work

Early work at ODALab

Current Technologies under Development

Head-mounted Projection Displays (HMPD)

Eyeglass Head-Worn Displays (HWD)

Why Head-Worn Displays?

Assuming HWDs can be designed aesthetically (which is not a given) to meet with social acceptance:

- **Mobility**

- **Privacy**

- **Constancy:** Provides the basis for novel user interfaces that are available constantly (on a demand basis) to the user

Science Fiction Sets Expectations of Where we Aim to Be Going!

* Goldsman, A. (1998). *Lost in Space*. New Line Cinema

Medical Rooms of the Future

Telemedicine: Face to Face Teleportal

Fig 1. Vision of "see-thru-my-eyes" capability. (1) Doctor in local control room guides (2) remote treatment via stereoscopic see-thru headset worn by emergency technician.

Fig.2. Vision of mobile "Face-to-Face" interaction (1) remote team member wearing 3D face recording system talk in to (2) team leader in control center.

Courtesy of Frank Biocca, MSU

Courtesy of ORA
Room 823, 1:30pm

Wearable Displays: **A Range of Possibilities**

Their future lies in large part in their “seamless”
integration with tangible interfaces around us

**Augmented Reality
/ Mixed Reality
Vs. Virtual Reality (full immersion)**

Augmented/Mixed Reality

Optical See-through

Video See-through

Historical Notes

First graphics-driven HWD was developed by Ivan Sutherland in the 1960s.

Augmented Reality Displays

Early (first?) stereoscopic VST-HMD

- HMD-mounted stereo cameras with custom-designed lenses compensate for display distortion (Biocca & Rolland, Presence 1998)

Some applications call for
optical see-through
capability

Highlights from Past Development

- U.S. Army first to fly a helmet-mounted sighting system on the Cobra helicopter.
- IHADSS (Integrated Helmet and Display Sighting System) was then deployed by the U.S. Army for the AH-64 Apache Helicopter.

IHADSS, while monocular, greatly contributed to the proliferation of all types of HMDs.

The success of HWD design is most likely to occur when developed

- In the context of the users and
- Targeted at specific applications

A Main Design Trade-off

FOV vs. Resolution - Currently limited by microdisplays

Angle subtended by a pixel = $\frac{FOV}{\# \text{ of pixels}}$ **Human eye 1 arcmin**

Approaches:

- 1) High-resolution area of interest or inset
- 2) Partial binocular overlap ("Luning")
- 3) Optical tiling (Kaiser, Sensics)

Recent developments by Sensics.

Driven by Medical Visualization: VRDA Tool “Virtual Reality Dynamic Anatomy”

NIH - First Award 1997-2002

Methods Optics, Computer Vision, and Graphics

Development of a Kinematic Model of Joint Motion ([Baillot](#), Rolland et al., 2000)

Early Feasibility Experiments

First results in dynamic optical superimposition on an optical bench system

Featured in *Scientific American*, April 2002

Baillet et al., *Presence* 2000; Argotti et al., *Computers & Graphics* 2002

Visualization (Head-Worn Displays)

Cakmakci Ozan, and Jannick Rolland, Head-worn displays, *IEEE/OSA Journal of Display Technology*, 2(3) (September 2006).

C. Fidopiastis, L. Davis, J. Covelli, L. Nguyen, R. Martins, O. Cakmakci

Students: F. Hamza-Lup, A. Santhanam

Fig. 5 HMPD in use in a deployable Augmented Reality Center (ARC): (A) Schematic of the HMPD optics; (B) user wearing a HMPD; (C) the ARC; and (D) user interacting with 3D models in the ARC. (View this art in color at www.dekker.com.)

Eyepiece versus Projection HMDs

Eyepiece Optics (HWD)

- Advantage**
 - Simple/Robust
 - Color
- Challenge**
 - Optical weight scales with FOV
 - Distortion (electronic comp)
 - Illumination limited (miniature display)

Head Mounted Projection Display

- Advantage**
 - Simple/Robust
 - Color
 - Optics size does not scale with FOV
 - Lightweight
 - Distortion free
 - Lower aberrations than eyepiece design
- Challenge**
 - Illumination limited by microdisplays
 - Screen type and location

Review of “Large FOV” Eyepiece Optics Design

Rolland and Hua, 2005
Encyclopedia of Optical
Engineering (Marcel Dekker)

Picture	Specification	Lens Form	Specification
	FOV 70 EFL 100 H. Erfle 1478704		FOV 70 EFL 100 Michael D. Missig 5446588
	FOV 33 EFL 34 J. D. Robinson C. M. Schor P. H. Muller W. A. Yankee eyepiece 5696521		B. S. Fritz HMD using Mangin Mirror combiner 5638490
	FOV 40-60 EFL 100 Takayoshi Togino Eyepiece with DOE 6181475 5959780		FOV 40 15.2x12.3 MicroDisplay F#1.7 J. G. Droessler Honeywell Inc. Morristown, NJ 6147807
	FOV 50x60 J. G. Droessler D. J. Rotier Tilted Cat Ocular 1989		FOV 120 G. Anier Jean-Blaise Migozzi Holographic Binocular Helmet Visor 5124821
	FOV 50-60 color Helmet visor display B. Chen Off-axis Design 5526183		FOV 60 color 1.3" diagonal CRT J. P. Rolland Off-axis Design 10DC94, OE 2000

Direct View

See-through

Related Work

Kasai. Int. Symp. Wearable Computers '00.

Resolution ~2 arcmins
FOV ~30 degrees
10 mm pupil [Lumus]

H. Mukawa et al. In Proc.
Society of Information
Display, 2008.

SONY

AHMD (Advanced HMD) Ultrawide FOV, off-axis design

Courtesy of LINK/ZYGO and
Optical Research Associates
Early 2000

AHMD Specifications	
Helmet compatibility	HGU-56P, HGU-55P all sizes
Center of gravity	Balanced
Eye relief	> 50 mm
Exit pupil	15 mm
Transmissivity	> 60%
Field-of-view	100° H x 50° V
Binocular overlap	30°
Resolution	1280 x 1024 per eye

Spatial Uniformity Behavior with Freeform Bezier Shapes

Fournier et al., Appl. Opt. 47 (2008) & OL 33(11) (2008)

Changing the concavity of the shape can improve uniformity
without sacrificing efficiency

Deployable Technology 1st Generation HMPD

with VGA LCD microdisplays
Hua, Ha, and Rolland, Appl. Opt. 42 2003

Fisher, 96 Patent

Miniaturization of
the Optics

Deployable Rooms

3D Visualization of the Upper Airway for Training Medics in Emergency Intubation Procedures

Augmented Reality Visualization

Lung Dynamics

Anand Santhanam, PhD 06

Imaging: Extended Depth of Focus Needed in Catheters

PSF through Working Range

Meemon et al., AO 2008

Target → Strehl ratio > 0.8

Bessel Beam vs. Conventional

First Images of biological tissue acquired with a microlens axicon in a double pass OCT : Images of African frog (*Xenopus Laevis*) tadpole located at relative axial distances d from each medial position of its depth of focus.

K. Lee and J. Rolland *Optics Letters* 33 (2008)

52 deg. Lens / 8g per eye

Teleportal Display UCF/MSU

Fig. 2. Vision of mobile "Face-to-Face" interaction (1) remote team member wearing 3D face recording system talk in to (2) team leader in control center.

Reddy et al., CVPR'04

42° FOV HMPD

Lightweight 595 grams - 2nd Generation HMPD using 800x600 OLED

Optical Design done in the ODALab and
HMPD Optomechanical design done by Nvis Corporation
under SBIR program 2004-2005 with the US ARMY

M-HMPD - Fabric-free, Mobile

Martins, Optics Express 15(22), 2007

See-through, Outdoor
42° FOV

A recent experiment with the MD
Anderson Cancer Center Orlando
to appear in JDT, Dec08

Comparison of the ARC system with the 2D display system

To appear in Special Issue of JDT, Dec 08

Subject	Average time (sec) Experiment 1		Average time (sec) Experiment 2		Average time (sec) Experiment 3	
	ARC	2D monitor	ARC	2D monitor	ARC	2D monitor
Expert 1	0	2.55	0.75	11.05	1.05	13.05
Expert 2	0	0.95	1.05	8.95	0.95	11.0
Expert 3	0.45	4.05	0.95	12.05	1.55	15.05
Expert 4	0	3.95	0.55	14.95	1.05	14.05
Expert 5	0.55	2.55	1.45	8.0	0.9	16.0
Expert 6	0	3.45	1.40	9.0	1.55	13.0
Average	0.2	2.9	1.0	10.7	1.2	13.7

The individual dose beams are delivered to a patient in 30-40 seconds, Thus, a 10 second delay in decision making is highly significant

Visualization (Head-Worn Displays)

Cakmakci Ozan, and Jannick Rolland, Head-worn displays, IEEE/OSA *Journal of Display Technology*, 2(3) (September 2006).

C. Fidopiastis, L. Davis, J. Covelli, L. Nguyen, R. Martins, O. Cakmakci

Students: F. Hamza-Lup, A. Santhanam

Fig. 5 HMPD in use in a deployable Augmented Reality Center (ARC): (A) Schematic of the HMPD optics; (B) user wearing a HMPD; (C) the ARC; and (D) user interacting with 3D models in the ARC. (View this art in color at www.dekker.com.)

FREE FORM OPTICS

Eyeglass Display

Ozan Cakmakci, Kidger Scholarship 05

Cakmakci & Rolland, *Journal of Display Technology*, (2006).

40 cycles/mm

Dual-element Solution

Cakmakci & Rolland, OL 32(11), 2007

Field of view: up to 25 FOV diagonal
Resolution: ~1.5 arcminutes
Exit pupil size: up to 12mm
Eye clearance: >15 mm
Distortion: <4%
Wavelengths: 450-650nm

(a)

(b)

Fig. 2. (Color online) Photograph through the fabricated dual-element system of (a) a color target and (b) a black and white target.

We Propose to Design Freeform Optical Surfaces whose Representations use **Local Basis Functions** (as Opposed to Global Polynomials)

- An optical surface can be represented as a sum of basis functions

$$z(x, y) = \sum \phi_i(x, y)w_i$$

- In matrix form

$$z = \Phi w$$

- To be invertible, Φ must be positive definite. equivalent to having positive eigenvalues.

Results

Surface type	Average MTF	Max. Distortion
Anamorphic asphere	26.5%	3.8%
X-Y polynomial	43.6%	2.65%
Zernike polynomial	42%	3.74%
Lin. Comb. of Gaussians	60.5%	3.6%

40 cycles/mm

Cakmakci et al., Optics Express 16(3) (2008)

Revisiting the Dual-Element Design: Pupil Size Expansion

Cakmakci et al. OL (April 2008)

Using a 16x16 set of basis functions.

Acknowledgements

- National Institute of Health (NIH/NLM) First Award (5years)
- National Science Foundation
 - EIA 99-86051, IIS/ITR00-82016, IIS/HCI 03-07189
- Office of Naval Research
 - N00014-02-1-0261, N00014-02-1-0927, N00014-03-1-0677 ...
- US Army STRICOM, US Army Medical Res., US AirForce
- NASA
- Florida Photonics Center of Excellence
- Industry Partners: METI Corporation, NVIS Corporation, Optical Research Associates