PROCEEDINGS OF SPIE

SPIDigitalLibrary.org/conference-proceedings-of-spie

Front Matter: Volume 8474

, "Front Matter: Volume 8474," Proc. SPIE 8474, Optical Processes in Organic Materials and Nanostructures, 847401 (13 November 2012); doi: 10.1117/12.2011791

SPIE.

Event: SPIE Organic Photonics + Electronics, 2012, San Diego, California, United States

PROCEEDINGS OF SPIE

Optical Processes in Organic Materials and Nanostructures

**Rachel Jakubiak
Manfred Eich
Jean-Michel Nunzi**
Editors

**12–15 August 2012
San Diego, California, United States**

Sponsored and Published by
SPIE

Volume 8474

Proceedings of SPIE 0277-786X, V.8474

SPIE is an international society advancing an interdisciplinary approach to the science and application of light.

Optical Processes in Organic Materials and Nanostructures, edited by Rachel Jakubiak,
Manfred Eich, Jean-Michel Nunzi, Proc. of SPIE Vol. 8474, 847401 · © 2012 SPIE
CCC code: 0277-786/12/\$18 · doi: 10.1117/12.2011791

Proc. of SPIE Vol. 8474 847401-1

The papers included in this volume were part of the technical conference cited on the cover and title page. Papers were selected and subject to review by the editors and conference program committee. Some conference presentations may not be available for publication. The papers published in these proceedings reflect the work and thoughts of the authors and are published herein as submitted. The publisher is not responsible for the validity of the information or for any outcomes resulting from reliance thereon.

Please use the following format to cite material from this book:

Author(s), "Title of Paper," in *Optical Processes in Organic Materials and Nanostructures*, edited by Rachel Jakubiak, Manfred Eich, Jean-Michel Nunzi, Proceedings of SPIE Vol. 8474 (SPIE, Bellingham, WA, 2012) Article CID Number.

ISSN: 0277-786X

ISBN: 9780819491916

Published by

SPIE

P.O. Box 10, Bellingham, Washington 98227-0010 USA

Telephone +1 360 676 3290 (Pacific Time) · Fax +1 360 647 1445

SPIE.org

Copyright © 2012, Society of Photo-Optical Instrumentation Engineers.

Copying of material in this book for internal or personal use, or for the internal or personal use of specific clients, beyond the fair use provisions granted by the U.S. Copyright Law is authorized by SPIE subject to payment of copying fees. The Transactional Reporting Service base fee for this volume is \$18.00 per article (or portion thereof), which should be paid directly to the Copyright Clearance Center (CCC), 222 Rosewood Drive, Danvers, MA 01923. Payment may also be made electronically through CCC Online at copyright.com. Other copying for republication, resale, advertising or promotion, or any form of systematic or multiple reproduction of any material in this book is prohibited except with permission in writing from the publisher. The CCC fee code is 0277-786X/12/\$18.00.

Printed in the United States of America.

Publication of record for individual papers is online in the SPIE Digital Library.

SPIDigitalLibrary.org

Paper Numbering: Proceedings of SPIE follow an e-First publication model, with papers published first online and then in print and on CD-ROM. Papers are published as they are submitted and meet publication criteria. A unique, consistent, permanent citation identifier (CID) number is assigned to each article at the time of the first publication. Utilization of CIDs allows articles to be fully citable as soon as they are published online, and connects the same identifier to all online, print, and electronic versions of the publication. SPIE uses a six-digit CID article numbering system in which:

- The first four digits correspond to the SPIE volume number.
- The last two digits indicate publication order within the volume using a Base 36 numbering system employing both numerals and letters. These two-number sets start with 00, 01, 02, 03, 04, 05, 06, 07, 08, 09, 0A, 0B ... 0Z, followed by 10-1Z, 20-2Z, etc.

The CID Number appears on each page of the manuscript. The complete citation is used on the first page, and an abbreviated version on subsequent pages. Numbers in the index correspond to the last two digits of the six-digit CID Number.

Contents

- vii Conference Committee
- ix *Plastic solar cells: breaking the 10% commercialization barrier (Plenary Paper) [8477-103]*
L. Dou, J. You, C.-C. Chen, G. Li, Y. Yang, Univ. of California, Los Angeles (United States)

SESSION 1 OPTICAL PROCESSES IN NLO MATERIALS

- 8474 04 **Measurement of excited-state absorption cross sections of a novel platinum complex in picosecond top-hat Z-scan experiments employing partially coherent beams [8474-3]**
T. M. Pritchett, M. J. Ferry, W. Shensky III, A. G. Mott, U.S. Army Research Lab. (United States);
R. Liu, W. Sun, North Dakota State Univ. (United States)
- 8474 05 **SHG/2PF microscopy of single and multi-layer graphene [8474-4]**
A. V. Klekachev, I. Asselberghs, IMEC (Belgium) and Katholieke Univ. Leuven (Belgium);
C. Huyghebaert, IMEC (Belgium); M. Vanbel, M. A. Van der Veen, A. L. Stesmans,
Katholieke Univ. Leuven (Belgium); M. M. Heyns, S. De Gendt, IMEC (Belgium) and
Katholieke Univ. Leuven (Belgium); T. Verbiest, Katholieke Univ. Leuven (Belgium)

SESSION 2 NONLINEAR OPTICAL MATERIALS

- 8474 07 **Exciplex formation in solid state blends of charge-transfer type AFX dyes and bisimide compounds [8474-6]**
M. J. Dalton, D. J. Stewart, Air Force Research Lab. (United States) and General Dynamics
Information Technology (United States); R. Kannan, Air Force Research Lab. (United States)
and AT&T Government Solutions, Inc (United States); R. N. Swiger, Air Force Research Lab.
(United States) and Southwestern Ohio Council for Higher Education (United States);
D. L. Orseno, Air Force Research Lab. (United States) and UES, Inc. (United States);
J. E. Haley, T. M. Cooper, L.-S. Tan, Air Force Research Lab. (United States)
- 8474 09 **Synthesis, crystal growth, and second-order nonlinear optical properties of new pyridinium salts [8474-8]**
J. Tan, L. Li, J. Yin, X. Zhang, Univ. of Science and Technology Beijing (China); X. Tao,
Shandong Univ. (China); Z. Yang, Univ. of Science and Technology Beijing (China)

SESSION 3 NANOPHOTONIC MATERIALS AND APPLICATIONS

- 8474 0A **Towards understanding the photomechanical effect in polymeric fibers: analysis of free volume in a model polymeric matrix (Invited Paper)** [8474-9]
G. Pawlik, Wroclaw Univ. of Technology (Poland); R. Orlik, Orlik Software (Poland);
W. Radosz, A. C. Mitus, Wroclaw Univ. of Technology (Poland); M. G. Kuzyk, Washington State Univ. (United States)

SESSION 5 BIOLOGICAL IMAGING

- 8474 0J **Stochastic photon transport model in multilayer skin tissue: using reflectance spectroscopy measurements to model normal and bruised skins** [8474-18]
C. Lines, O. Kim, Univ. of Notre Dame (United States); J. McMurdy, Brown Univ (United States); S. Duffy, Hasbro Children's Hospital (United States); M. Alber, G. P. Crawford, Univ. of Notre Dame (United States)
- 8474 0K **Determination of chromophore distribution in skin by spectral imaging** [8474-20]
I. Saknite, Univ. of Latvia (Latvia); M. Lange, Riga Technical Univ (Latvia); D. Jakovels, J. Spigulis, Univ. of Latvia (Latvia)

SESSION 6 NONLINEAR OPTICAL DEVICES AND MECHANISMS

- 8474 0M **From universal properties to cascading: using sum rules for developing broad principles and understanding phenomena** [8474-22]
M. G. Kuzyk, D. S. Watkins, Washington State Univ. (United States); N. J. Dawson, Washington State Univ. (United States) and Youngstown State Univ. (United States); B. R. Anderson, Washington State Univ. (United States); J. L. Schei, Washington State Univ. (United States) and Los Alamos National Lab. (United States)
- 8474 0O **Nonlinear optics of quantum graphs** [8474-24]
R. Lytel, S. Shafei, M. G. Kuzyk, Washington State Univ. (United States)
- 8474 0P **Using geometry to enhance the nonlinear response of quantum confined systems** [8474-25]
S. Shafei, R. Lytel, M. G. Kuzyk, Washington State Univ. (United States)

SESSION 8 PHOTOREFRACTIVE MATERIALS AND APPLICATIONS

- 8474 0S **Real-time formation of dynamic hologram in photorefractive ferroelectric liquid crystals** [8474-28]
T. Sasaki, M. Ikegami, S. Kajikawa, Y. Naka, Tokyo Univ. of Science (Japan)
- 8474 0T **Dynamic holographic images using polyvinylcarbazole-based photorefractive composites** [8474-29]
K. Kinashi, Y. Wang, A. Nonomura, W. Sakai, N. Tsutsumi, Kyoto Institute of Technology (Japan)

- 8474 0U **Formation of photo-induced index grating in azo-carbazole dye-doped polymer** [8474-30]
Y. Kawabe, K. Fukuzawa, T. Uemura, K. Matsuura, T. Yoshikawa, J. Nishide, H. Sasabe,
Chitose Institute of Science and Technology (Japan)

SESSION 9 POLYMER MATERIALS FOR OPTICS AND PHOTONICS

- 8474 0V **Small-molecule amine compound as electron-injection layer for organic light-emitting diodes (Invited Paper)** [8474-31]
G. Liu, Y.-H. Li, W.-Y. Tan, Q.-D. Li, X.-H. Zhu, J. Peng, Y. Cao, South China Univ. of
Technology (China)
- 8474 0Y **Studies of mechanisms of decay and recovery in organic dye-doped polymers using spatially-resolved white light interferometry** [8474-34]
B. Anderson, E. Bernhardt, M. Kuzyk, Washington State Univ. (United States)

POSTER SESSION

- 8474 0Z **Photorefractivity of triphenylamine polymers** [8474-35]
S. Tsujimura, K. Kinashi, W. Sakai, N. Tsutsumi, Kyoto Institute of Technology (Japan)
- 8474 10 **Photorefractive composite based on monolithic polymer** [8474-36]
H. N. Giang, K. Kinashi, W. Sakai, N. Tsutsumi, Kyoto Institute of Technology (Japan)
- 8474 11 **Bistable optical transmission properties of polyethylene-glycol** [8474-37]
M. Saito, Y. Nishimura, Ryukoku Univ. (Japan)
- 8474 12 **Synthesis and optical properties of a crosslinkable polymer system containing TCF and TCP chromophores with excellent electro-optic activity and thermal stability** [8474-38]
Z. Chen, S. Bo, Z. Zhen, X. Liu, Technical Institute of Physics and Chemistry (China)
- 8474 13 **The synthesis of branched TCP chromophores and the research on their electro-optical properties** [8474-39]
S. Bo, Z. Chen, W. Gao, Z. Zhen, X. Liu, Technical Institute of Physics and Chemistry (China)
- 8474 14 **Photoisomerization of azobenzene moiety in crosslinking polymer materials** [8474-40]
H. Wang, Technical Institute of Physics and Chemistry (China) and Graduate Univ. of the
Chinese Academy of Sciences (China); W.-Q. Chen, F. Jin, X.-Z. Dong, Z.-S. Zhao,
X.-M. Duan, Technical Institute of Physics and Chemistry (China)
- 8474 16 **Photo-reduction of silver ion by two-photon excitation using femtosecond laser** [8474-42]
R. Nakamura, K. Kinashi, W. Sakai, N. Tsutsumi, Kyoto Institute of Technology, Kyoto (Japan)

- 8474 1A **The role of the polymer host on reversible photodegradation in Disperse Orange 11 dye**
[8474-47]
S.-T. Hung, Washington State Univ. (United States) and Katholieke Univ. Leuven (Belgium);
S. K. Ramini, D. G. Wyrick, Washington State Univ. (United States); K. Clays, Washington
State Univ. (United States) and Katholieke Univ. Leuven (Belgium); M. G. Kuzyk, Washington
State Univ. (United States)

Author Index

Conference Committee

Symposium Chair

Zakya H. Kafafi, National Science Foundation (United States)

Conference Chair

Rachel Jakubiak, Air Force Research Laboratory (United States)

Conference Cochairs

Manfred Eich, Technische Universität Hamburg-Harburg (Germany)

Jean-Michel Nunzi, Queen's University (Canada)

Conference Program Committee

Kevin D. Belfield, University of Central Florida (United States)

Antao Chen, University of Washington (United States)

Koen Clays, Katholieke Universiteit Leuven (Belgium)

Alain F. Fort, Institut de Physique et Chimie des Matériaux de
Strasbourg (France)

Theodore G. Goodson III, University of Michigan (United States)

François Kajzar, Polytechnical Universitatea of Bucharest (Romania)

Satoshi Kawata, Osaka University (Japan)

Mark G. Kuzyk, Washington State University (United States)

Charles Y. C. Lee, Air Force Office of Scientific Research
(United States)

Kwang-Sup Lee, Hannam University (Korea, Republic of)

Geoffrey A. Lindsay, Naval Air Warfare Center, Aircraft Division
(United States)

Aristides Marciano, Delaware State University (United States)

Robert A. Norwood, College of Optical Sciences, The University of
Arizona (United States)

André P. Persoons, Katholieke Universiteit Leuven (Belgium)

Joy E. Rogers-Haley, Air Force Research Laboratory (United States)

Jayan Thomas, University of Central Florida (United States)

Session Chairs

- 1 Optical Processes in NLO Materials

Neil R. Murphy, Air Force Research Laboratory (United States)

- 2 Nonlinear Optical Materials
Jayan Thomas, CREOL, The College of Optics and Photonics,
University of Central Florida (United States)
- 3 Nanophotonic Materials and Applications
Robert A. Norwood, College of Optical Sciences, The University of
Arizona (United States)
- 4 Plasmonic Materials and Applications
Antoni C. Mitus, Wroclaw University of Technology (Poland)
- 5 Biological Imaging
Aleksander K. Rebane, Montana State University (United States)
- 6 Nonlinear Optical Devices and Mechanisms
Dean R. Evans, Air Force Research Laboratory (United States)
- 7 Nanobiosystems and Optical Processes in Organic Materials and
Nanostructures: Joint Session with Conference 8464 and 8474
James G. Grote, Air Force Research Laboratory (United States)
Rachel Jakubiak, Air Force Research Laboratory (United States)
- 8 Photorefractive Materials and Applications
Mark G. Kuzyk, Washington State University (United States)
- 9 Polymer Materials for Optics and Photonics
Rachel Jakubiak, Air Force Research Laboratory (United States)

Plastic Solar Cells: Breaking the 10% Commercialization Barrier

Letian Dou^a, Jingbi You^a, Chun-Chao Chen^a, Gang Li^a, Yang Yang^{a,b,*}

^aDepartment of Materials Science and Engineering, University of California, Los Angeles, Los Angeles, California USA 90095; ^bCalifornia NanoSystems Institute, University of California, Los Angeles, Los Angeles, 90095, California USA.

ABSTRACT

Tandem solar cells provide an effective way to harvest a broader spectrum of solar radiation by combining two or more solar cells with different absorption ranges. However, for polymer solar cells (PSCs), the performance of tandem devices lags behind single-layer cells mainly due to the lack of a high-performance low-bandgap polymer with appropriate spectral response range. Here, we demonstrate a novel low bandgap conjugated polymer (~1.44 eV) specifically suitable for tandem structure. In the single-layer device, power conversion efficiency (PCE) of 6.5% was achieved. When the polymer was applied to tandem solar cells, we demonstrated a NREL certified PCE of 8.62%^[1]. Further optimization on materials and devices of this system has lead to record breaking efficiency of 10.6%. Furthermore, the tandem devices show excellent stability due both to the intrinsic stability of the polymer and the advanced device structure.

Keywords: Low bandgap polymer, polymer solar cell, tandem polymer solar cell

1. INTRODUCTION

Organic photovoltaic (OPV) devices are promising for low-cost, flexible, lightweight, large-area energy generation applications, and much work on designing new materials, device structures, and processing techniques has been carried out to improve the power conversion efficiency (PCE) of OPV devices. So far, polymer solar cells (PSCs) based on conjugated polymers as electron-donor materials blended with [6,6]-phenyl-C71-butyric acid methyl ester (PC71BM) as an electron-acceptor material have achieved around 8% PCE using a bulk heterojunction (BHJ) device structure.^[2-5] Nonetheless, most of these materials suffer from the inherent disadvantages of either lacking a broad absorption range (bandgap [Eg] = 1.6 eV~2.0 eV), or relatively low carrier mobility. This reduces the external quantum efficiency (EQE) and photocurrent of the devices. To use solar radiation more effectively, an effective approach is to stack multiple photoactive layers with complementary absorption spectra in series to make a tandem PSC. Typically, such a tandem structure consists of a front cell with a high-bandgap material, an interconnecting layer (ICL), and a rear cell with a low-bandgap (LBG) material. By using more than one material, each material captures a different range of the solar spectrum and increase the open-circuit voltage (VOC) and thus the efficiency.^[6-7]

The photoactive materials play a critical role in determining the PCE; however, due to the great difficulties, there have been few reports to date on designing photoactive materials specifically for high-efficiency tandem PSCs. To be applied effectively in a tandem structure, sub-cell materials have several requirements, especially for rear-cell LBG polymers. First, a small energy bandgap (<1.5 eV) is critical so that the overlap of absorption spectra between the front and rear cells can be minimized.³⁴ Second, fine-tuning is required of the highest-occupied molecular orbital (HOMO) and lowest-unoccupied molecular orbital (LUMO) levels to achieve high VOC with a small bandgap while maintaining a LUMO level high enough for efficient charge separation. Third, high charge-carrier mobility and fine phase separation with the acceptor are required for high short-circuit current density (JSC) and fill factor (FF) in single-cell devices.²⁷⁻³¹ Therefore, a carefully designed LBG polymer will perform well for tandem cells only if it can achieve high current by efficiently using the low-energy portion of the solar spectrum. Currently, the existing LBG materials (Eg < 1.5 eV) show either low VOC, low JSC, or low FF values, which are far from ideal for the tandem structure. Thus, the PCE of tandem cells reported so far is less than 7%.

2. LOW BANDGAP POLYMER DESIGN

Here, we demonstrate the rational design of a novel LBG conjugated polymer poly{2,6'-4,8-di(5-ethylhexylthienyl)benzo[1,2-b;3,4-b']dithiophene-alt-5-dibutyloctyl-3,6-bis(5-bromothiophen-2-yl)pyrrolo[3,4-c]pyrrole-

1,4-dione} (PBDTT-DPP, Figure 1a) specifically for tandem solar cells. To achieve a small bandgap, a polymer backbone based on the diketopyrrolopyrrole (DPP) unit and benzodithiophene (BDT) unit was chosen. By replacing the oxygen atoms attached to the BDT unit with thiophene moieties to form the thienylbenzodithiophene (BDTT) unit, the HOMO and LUMO levels of PBDTT-DPP are moved deeper to increase VOC without losing the driving force for efficient charge separation, while keeping the bandgap within the ideal range. Furthermore, bulkier 2-ethylhexyl side chains on BDTT and 2-butyloctyl side chains on DPP are used to increase the solubility of the resulting polymers and thus obtain much higher molecular weights. Compared to PBDT-DPP, PBDTT-DPP showcased improved solubility, higher molecular weight, and higher carrier mobility, which leads to a significantly higher JSC in single-cell devices. Finally, we applied this LBG polymer into a newly designed inverted structure of a tandem solar cell, and a PCE of 8.62% was certified by the National Renewable Energy Laboratory (NREL). Further optimization on materials and devices of this system has lead to record breaking efficiency of 10.6%.

3. DEVICES PERFORMANCE

Single-layer BHJ photovoltaic cells based on PBDTT-DPP blended with PC71BM were fabricated with a regular and an inverted configuration. The optimized polymer:PC71BM blend ratio (by weight) was found to be 1:2 and the optimized film thickness was around 100 nm. The single-cell PV performance of PBDTT-DPP is shown in Figure 1. Of the more than 300 devices that we fabricated, the best devices gave values of V_{OC} around 0.74 V, J_{SC} around 13.5 mA/cm², fill factor around 65%, and PCE as high as 6.5% for both the regular and inverted structure.

Figure 1. J-V characteristics of single-cell devices with regular and inverted structures under AM1.5G illumination from a calibrated solar simulator with an irradiation intensity of 100 mWcm².

Inverted tandem solar cells were fabricated using the rear-cell-specific LBG polymer PBDTT-DPP and the new device architecture. The J-V characteristics, EQE of a typical device are shown in Figure 2 (a) and (b), respectively. EQE of individual sub-cells in the tandem structure was measured by using light bias. As shown in Figure 4a, the front cell had photo-response from 300 to 600 nm, showed EQE as high as 60% at 530 nm, and its integrated JSC was 8.2 mA/cm²; the rear cell had broad photo-response from 300 to 850 nm, showed a maximum EQE of 47% at 770 nm, and its integrated JSC was 8.1 mA/cm². The incident light from 300 to 600 nm was strongly absorbed by the front cell and the EQE of the rear cell in this region was much lower than that of its single-cell devices; however, the rear cell can still provide enough photo-current (8.1 mA/cm²) to match the current that the front cell could supply (8.2 mA/cm²) because the new material PBDTT-DPP can very efficiently use the low-energy portion (from 600 to 850 nm) of the solar radiation.

Figure 2 Quantum efficiencies, J–V characteristics and stability of single cells and tandem cells. a, EQEs of the inverted tandem solar cell and absorption spectrum (without metal electrode). b, J–V characteristics of the front cell, rear cell and inverted tandem solar cell, tested at NREL using the OSMSS simulator.

4. CONCLUSION

In summary, we have demonstrated a high-performance LBG conjugated polymer specifically for tandem PSCs by applying three design rules - lowering bandgap for spectral-matching with front cell, controlling HOMO/LUMO levels to enhance VOC, and increasing molecular weight to enhance JSC and FF. The novel polymer (PBDTT-DPP) has a small optical bandgap, deep HOMO level, and high hole mobility. Single-layer BHJ solar cells fabricated from PBDTT-DPP and PC71BM exhibited PCEs of more than 6%. The significance of the PBDTT-DPP polymer is clearly demonstrated in inverted tandem PSCs with 8.62% PCE under AM1.5G one-sun illumination as tested by NREL. This study opens up a new direction for polymer chemists to design new materials for tandem PSCs and also makes an important step forward toward commercialization of PSCs. Further optimization on materials and devices of this system has lead to record breaking efficiency of 10.6%.

REFERENCES

- [1] Dou, L. et al. Tandem polymer solar cells featuring a spectrally matched low-bandgap polymer. *Nature Photon.* 6, 180–185 (2012).
- [2] Chen, H. Y. et al., Polymer solar cells with enhanced open-circuit voltage and efficiency. *Nat. Photon.* 3, 649–653 (2009).
- [3] Liang, Y. Y. et al., For the bright future—bulk heterojunction polymer solar cells with power conversion efficiency of 7.4%. *Adv. Mater.* 22, E135–E138 (2010).
- [4] Chu, T. Y. et al., Bulk heterojunction solar cells using thieno[3,4-c]pyrrole- 4,6-dione and dithieno[3,2-b:2',3'-d]silole copolymer with a power conversion efficiency of 7.3%. *J. Am. Chem. Soc.* 133, 4250–4253 (2011).
- [5] He, Z. et al., Simultaneous enhancement of open-circuit voltage, short-circuit current density and fill factor in polymer solar cells. *Adv. Mater.* 23, 4636–4643 (2011).

- [6] Kim, J. Y. et al., Efficient tandem polymer solar cells fabricated by all-solution processing. *Science* 317, 222-225 (2007).
- [7] Sista, S. et al., Highly efficient tandem polymer photovoltaic cells. *Adv. Mater.* 22, 380-383 (2010).