PROCEEDINGS OF SPIE

SPIDigitalLibrary.org/conference-proceedings-of-spie

Front Matter: Volume 8562

, "Front Matter: Volume 8562," Proc. SPIE 8562, Infrared, Millimeter-Wave, and Terahertz Technologies II, 856201 (19 December 2012); doi: 10.1117/12.2018523

SPIE.

Event: Photonics Asia, 2012, Beijing, China

PROCEEDINGS OF SPIE

Infrared, Millimeter-Wave, and Terahertz Technologies II

Cunlin Zhang
Xi-Cheng Zhang
He Li
Sheng-Cai Shi
Editors

5–7 November 2012
Beijing, China

Sponsored by
SPIE • COS—Chinese Optical Society

Cooperating Organizations
Tsinghua University (China) • Peking University (China) • Zhejiang University (China) • Beijing Institute of Technology (China)
Beijing University of Posts and Telecommunications (China) • University of Science and Technology of China (China)
Tianjin University (China) • Nankai University (China) • Changchun University of Science and Technology (China) • University
of Shanghai for Science and Technology (China) • Capital Normal University (China) • Huazhong University of Science and
Technology (China) • Beijing Jiaotong University (China) • Shanghai Institute of Optics and Fine Mechanics (China)
Changchun Institute of Optics and Fine Mechanics (China) • Institute of Semiconductors (China) • Institute of Optics and
Electronics (China) • National Univ. of Defense Technology (China) • Institute of Physics (China) • Shanghai Institute of
Technical Physics (China) • China Instrument and Control Society (China) • Optoelectronics Technology Committee, COS
(China) • SPIE National Committee in China (China) • Japan Optical Society (Japan) • Korea Optical Society (Korea,
Republic of) • Australia Optical Society (Australia) • Singapore Optical Society (Singapore)

Supporting Organizations
CAST—China Association for Science and Technology (China) • NSFC—National Nature Science Foundation (China)

Published by
SPIE

Volume 8562

Proceedings of SPIE 0277-786X, V.8562

SPIE is an international society advancing an interdisciplinary approach to the science and application of light.

Infrared, Millimeter-Wave, and Terahertz Technologies II, edited by Cunlin Zhang, Xi-Cheng Zhang, He Li,
Sheng-Cai Shi, Proc. of SPIE Vol. 8562, 856201 • © 2012 SPIE • CCC code: 0277-786/12/\$18 • doi: 10.1117/12.2018523

Proc. of SPIE Vol. 8562 856201-1

The papers included in this volume were part of the technical conference cited on the cover and title page. Papers were selected and subject to review by the editors and conference program committee. Some conference presentations may not be available for publication. The papers published in these proceedings reflect the work and thoughts of the authors and are published herein as submitted. The publisher is not responsible for the validity of the information or for any outcomes resulting from reliance thereon.

Please use the following format to cite material from this book:

Author(s), "Title of Paper," in *Infrared, Millimeter-Wave, and Terahertz Technologies II*, edited by Cunlin Zhang, Xi-Cheng Zhang, He Li, Sheng-Cai Shi, Proceedings of SPIE Vol. 8562 (SPIE, Bellingham, WA, 2012) Article CID Number.

ISSN: 0277-786X

ISBN: 9780819493170

Published by

SPIE

P.O. Box 10, Bellingham, Washington 98227-0010 USA

Telephone +1 360 676 3290 (Pacific Time) · Fax +1 360 647 1445

SPIE.org

Copyright © 2012, Society of Photo-Optical Instrumentation Engineers.

Copying of material in this book for internal or personal use, or for the internal or personal use of specific clients, beyond the fair use provisions granted by the U.S. Copyright Law is authorized by SPIE subject to payment of copying fees. The Transactional Reporting Service base fee for this volume is \$18.00 per article (or portion thereof), which should be paid directly to the Copyright Clearance Center (CCC), 222 Rosewood Drive, Danvers, MA 01923. Payment may also be made electronically through CCC Online at copyright.com. Other copying for republication, resale, advertising or promotion, or any form of systematic or multiple reproduction of any material in this book is prohibited except with permission in writing from the publisher. The CCC fee code is 0277-786X/12/\$18.00.

Printed in the United States of America.

Publication of record for individual papers is online in the SPIE Digital Library.

SPIDigitalLibrary.org

Paper Numbering: Proceedings of SPIE follow an e-First publication model, with papers published first online and then in print and on CD-ROM. Papers are published as they are submitted and meet publication criteria. A unique, consistent, permanent citation identifier (CID) number is assigned to each article at the time of the first publication. Utilization of CIDs allows articles to be fully citable as soon as they are published online, and connects the same identifier to all online, print, and electronic versions of the publication. SPIE uses a six-digit CID article numbering system in which:

- The first four digits correspond to the SPIE volume number.
- The last two digits indicate publication order within the volume using a Base 36 numbering system employing both numerals and letters. These two-number sets start with 00, 01, 02, 03, 04, 05, 06, 07, 08, 09, 0A, 0B ... 0Z, followed by 10-1Z, 20-2Z, etc.

The CID Number appears on each page of the manuscript. The complete citation is used on the first page, and an abbreviated version on subsequent pages. Numbers in the index correspond to the last two digits of the six-digit CID Number.

Contents

xi	<i>Symposium Committees</i>
xiii	<i>Conference Committee</i>
xv	<i>Quantum dot lasers and relevant nanoheterostructures (Plenary Paper) [8552-1]</i> A. E. Zhukov, N. V. Kryzhanovskaya, A. V. Savelyev, A. M. Nadtochiy, E. M. Arakcheeva, F. I. Zubov, V. V. Korenev, Saint Petersburg Academic Univ. (Russian Federation); M. V. Maximov, Y. M. Shernyakov, M. M. Kulagina, I. A. Slovinskiy, Ioffe Physical-Technical Institute (Russian Federation); D. A. Livshits, Innolume GmbH (Germany); A. Kapsalis, C. Mesaritis, D. Syvridis, Univ. of Athens (Greece); A. M. Mintairov, Univ. of Notre Dame (United States)

SESSION 1

8562 02	Review of THz wave air photonics (Invited Paper) [8562-1] X. Sun, F. Bucchieri, J. Dai, X.-C. Zhang, The Institute of Optics, Univ. of Rochester (United States)
8562 04	Effects of multiple reflections and low-frequency interferences on measured terahertz Fourier transform spectra [8562-3] S.-L. Li, K.-M. Zhou, Purple Mountain Observatory (China), Key Lab. of Radio Astronomy (China), and the Graduate Univ. of the Chinese Academy of Sciences (China); W.-Y. Duan, Z.-H. Lin, Q.-J. Yao, S.-C. Shi, Purple Mountain Observatory (China) and Key Lab. of Radio Astronomy (China)
8562 05	Design of 800×2 low-noise readout circuit for near-infrared InGaAs focal plane array [8562-4] Z. Huang, S. Huang, J. Fang, Shanghai Institute of Technical Physics (China)
8562 06	Shifting media for terahertz carpet cloak and overlapped effects [8562-5] X. Zang, B. Cai, Y. Zhu, Univ. of Shanghai for Science and Technology (China)

SESSION 2

8562 07	Computer processing of image captured by the passive THz imaging device as an effective tool for its de-noising (Invited Paper) [8562-6] V. A. Trofimov, V. V. Trofimov, I. E. Kuchik, Lomonosov Moscow State Univ. (Russian Federation); C. Zhang, C. Deng, Y. Zhao, X. Zhang, Capital Normal Univ. (China)
8562 08	A new approach of graph cuts based segmentation for thermal IR image analysis (Invited Paper) [8562-7] X. Hu, Nanjing Univ. of Posts and Telecommunications (China); S. Chakravarty, New York Institute of Technology (United States)

- 8562 09 **Research on a project of the new airborne polarization hyperspectral imager** [8562-8]
H. Li, J. Zhao, F. Zhou, X. Lin, H. Zhao, Beijing Institute of Space Mechanics and Electricity (China)
- 8562 0A **Remote measuring system for infrared spectral features using hollow fiber probe** [8562-9]
Y.-J. He, W. Tan, C.-H. Yang, Y.-W. Shi, Fudan Univ. (China)
- 8562 0B **Design of dual-color ROIC with double sharing capacitor** [8562-78]
J. Zhou, Shanghai Institute of Technical Physics (China) and Graduate Univ. of the Chinese Academy of Sciences (China); R. Ding, Shanghai Institute of Technical Physics (China); L. Gao, G. Chen, P. Wang, H. Chen, Shanghai Institute of Technical Physics (China) and Graduate Univ. of the Chinese Academy of Sciences (China)

SESSION 3

- 8562 0D **A scheme format conversion from NRZ-OOK to QPSK/16QAM signal based on XPM in SOA-MZI** [8562-12]
Y. Zhan, M. Zhang, M. Liu, L. Liu, Z. Liu, X. Chen, Beijing Univ. of Posts and Telecommunications (China)

SESSION 4

- 8562 0F **Dimmable VLC demonstration systems based on LED (Invited Paper)** [8562-15]
H.-C. Kim, S.-S. Lee, S.-Y. Jung, Yeungnam Univ. (Korea, Republic of)
- 8562 0H **A photonic approach to microwave/millimeter-wave frequency measurement with extended range based on phase modulation** [8562-17]
X. Han, N. Shi, S. Zhang, M. Wang, Y. Gu, M. Zhao, Dalian Univ. of Technology (China)
- 8562 0I **Signal model and jamming characteristics of a 35GHz millimeter-wave FMCW SAR** [8562-18]
W. Yu, S. Zhao, X. Song, Z. Liu, Beijing Institute of Tracking and Telecommunication Technology (China)

SESSION 5

- 8562 0J **Spatio-temporal characteristics of global atmospheric CO₂ mole fractions (X_{CO2}) retrieved from remotely sensed data (Invited Paper)** [8562-19]
T. Wang, J. Shi, Y. Jing, Y. Xie, State Key Lab. of Remote Sensing Science (China)
- 8562 0K **Development of high efficiency pulse tube cryocoolers for spaceborne infrared applications (Invited Paper)** [8562-20]
H. Dang, Shanghai Institute of Technical Physics (China)

- 8562 OL **Readout system for the terahertz superconducting imaging array (TeSIA)** [8562-21]
S. Li, Purple Mountain Observatory (China), Key Lab. of Radio Astronomy (China), and Graduate Univ. of the Chinese Academy of Sciences (China); J.-P. Yang, Purple Mountain Observatory (China) and Key Lab. of Radio Astronomy (China); W.-Y. Duan, Purple Mountain Observatory (China), Key Lab. of Radio Astronomy (China), and Graduate Univ. of the Chinese Academy of Sciences (China); Z.-H. Lin, J. Li, S.-C. Shi, Purple Mountain Observatory (China) and Key Lab. of Radio Astronomy (China)
- 8562 ON **Asymmetric double split-ring metamaterials absorber in the terahertz region** [8562-23]
H. Jun, Q. Li, J. Shen, Capital Normal Univ. (China)

SESSION 6

- 8562 OO **Double channel mechanically tunable terahertz filter based on parallel plate waveguide cavities (Invited Paper)** [8562-24]
L. Chen, Y. Zhu, Univ. of Shanghai for Science and Technology (China)
- 8562 OP **Millimeter-wave imaging with frequency scanning antenna and optical arrayed waveguide gratings (Invited Paper)** [8562-25]
Y. He, G. Yu, X. Fu, Y. Jiang, BeiHang Univ. (China)
- 8562 OQ **A new design of signal processing system for TDI infrared focal plane array** [8562-27]
H. Wang, Z. Wei, N. Lei, X. Wang, W. Zhang, T. Li, Beijing Institute of Space Mechanics and Electricity (China)
- 8562 OR **Flexible PMMA pipe for terahertz propagation** [8562-28]
J. Liu, Capital Normal Univ. (China); M. Xiao, Tsinghua Univ. (China); J. Shen, Capital Normal Univ. (China); W. Zhang, Tsinghua Univ. (China)

SESSION 7

- 8562 OS **Terahertz super thin planar lenses (Invited Paper)** [8562-29]
Y. Zhang, J. Ye, D. Hu, X. Wang, S. Feng, W. Sun, Capital Normal Univ. (China)
- 8562 OT **Atmospheric profiling synthetic observation system at THz (Invited Paper)** [8562-30]
Q. Yao, D. Liu, J. Li, Z. Lin, Z. Lou, S. Shi, Purple Mountain Observatory (China) and Key Lab. of Radio Astronomy (China); H. Maezawa, Osaka Prefectural Univ. (Japan); S. Paine, Harvard-Smithsonian Ctr. for Astrophysics (United States)
- 8562 OU **640×512 InGaAs focal plane array camera for detecting 1.58μm absorption spectra of CO₂** [8562-31]
W. Peng, Shanghai Institute of Technical Physics (China); S. Wu, Vision Engineering Ltd. (China); L. Ding, X. Wang, X. Zhu, Shanghai Institute of Technical Physics (China)

SESSION 8

- 8562 OW **THz radiation properties of silver V-cone antenna arrays (Invited Paper)** [8562-33]
J. Qian, Wuzhou Univ. (China); M. Huang, M. Hu, Guizhou Univ. (China)

- 8562 0X **Near-field thermal radiation characteristics of metamaterials** [8562-34]
Y. Bai, Y. Jiang, Harbin Institute of Technology (China)
- 8562 0Y **Fast angle catching methods for a narrow beam system** [8562-35]
H. Zeng, Y. Huang, Beijing Institute of Tracking and Telecommunication Technology (China); T. Li, EAAF (China); S. You, Beijing Institute of Tracking and Telecommunication Technology (China)
- 8562 0Z **A novel quasi-optical subharmonically pumped GaAs diode mixer at 375 GHz** [8562-36]
J. Hu, Purple Mountain Observatory (China), Key Lab. of Radio Astronomy (China), and Univ. of the Chinese Academy of Science (China); Z. Lou, S.-C. Shi, Purple Mountain Observatory (China) and Key Lab. of Radio Astronomy (China)
- 8562 10 **A low-power SAR ADC for IRFPA ROIC** [8562-80]
L. Gao, R. Ding, J. Zhou, P. Wang, G. Chen, Shanghai Institute of Technical Physics (China) and Graduate Univ. of the Chinese Academy of Sciences (China)

POSTER SESSION

- 8562 11 **Rational design of long-wave infrared band for application of the earth surface temperature observation** [8562-37]
Y. Bao, H. He, F. Zhou, Beijing Institute of Space Mechanics and Electricity (China)
- 8562 12 **The research of remote sensing dust storm with FY-3B three infrared channels** [8562-38]
H. Xu, Institute of Remote Sensing Applications (China), Graduate Univ. of Chinese Academy of Sciences (China), and The Ctr. for National Spaceborne Demonstration (China); ; T. Yu, T. Cheng, J. Li, J. Lai, Institute of Remote Sensing Applications (China); Q. Liu, National Geomatics Ctr. of China (China)
- 8562 14 **Single-scan coherent detection with enhanced time resolution for arbitrarily polarized terahertz wave** [8562-40]
Z. Lv, D. Zhang, C. Meng, L. Sun, Z. Zhou, Z. Zhao, J. Yuan, National Univ. of Defense Technology (China)
- 8562 15 **SBNUC based on constant statistics for VOx uncooled IRFPA and implementation with FPGA** [8562-41]
S. Wei, M. Jin, W. Jin, C. Xu, K. He, Beijing Institute of Technology (China)
- 8562 18 **Thermal denaturation of protein studied by terahertz time-domain spectroscopy** [8562-45]
X. Fu, X. Li, J. Liu, Y. Du, Z. Hong, China Jiliang Univ. (China)
- 8562 19 **Target detection method based on multi-life restrict used in super wide angle infrared staring warning system** [8562-46]
B. Zhou, F. Huang, J. Ying, Shijiazhuang Mechanical Engineering College (China)
- 8562 1A **Performance of portable high-resolution Fourier transform spectrometer for trace gas remote sensing** [8562-47]
H. Wei, Tsinghua Univ. (China) and Beijing Vision Sky Aerospace Technology Co., Ltd. (China); L. Ren, Tsinghua Univ. (China); D. Fan, Beijing Vision Sky Aerospace Technology Co., Ltd. (China); M.-A. Soucy, ABB (Canada)

- 8562 1B **Continuous field measurements of δD in water vapor by open-path Fourier transform infrared spectrometry** [8562-48]
W. Wang, Univ. of Science and Technology of China (China) and Anhui Institute of Optics and Fine Mechanics (China); W. Liu, T. Zhang, Anhui Institute of Optics and Fine Mechanics (China)
- 8562 1D **An experimental 0.2 THz stepped frequency radar system for the target detection** [8562-50]
B. Zeng, M. Liang, C. Zhang, Beijing Institute of Technology (China) and Capital Normal Univ. (China); Y. Zhao, Beijing Institute of Technology (China)
- 8562 1E **A reflection sensor based on the Rayleigh anomaly of metallic grating in terahertz wave band** [8562-51]
L. Yue, J. He, S. Feng, X. Wang, W. Sun, Y. Zhang, Capital Normal Univ. (China)
- 8562 1F **A novel target LOS calibration method for IR scanning sensor based on control points** [8562-52]
Y.-H. Xue, W. An, National Univ. of Defense Technology (China); Y.-S. Zhang, T. Zhang, Beijing Institute of Tracking and Telecommunication Technology (China)
- 8562 1G **Numerical simulation of terahertz transmission of bilayer metallic meshes with different thickness of substrates** [8562-53]
G. Zhang, G. Zhao, S. Zhang, Capital Normal Univ. (China)
- 8562 1I **Denoising to the pulsed laser radar return waves based on pulses accumulation and wavelet filter** [8562-55]
X. Cai, J. Liu, Heilongjiang Univ. (China); Q. Han, Harbin Institute of Technology (China); W. Dai, Heilongjiang Univ. (China)
- 8562 1J **Measurement and analysis of perceivable signal-to-noise ratio for infrared imaging system with human vision** [8562-57]
X. Liu, J. Zhao, H. Chang, L. Ma, Xidian Univ. (China)
- 8562 1L **Plasmonic resonance of bowtie antennas and their geometry dependence** [8562-59]
R. Dong, Y. Nie, S. Yao, Y. Jiang, J. Meng, Y. Yang, Minzu Univ. of China (China)
- 8562 1M **Power-efficient UWB generation based on hybrid of optical fiber link and RF circuits** [8562-60]
J. Dong, Y. Yu, D. Huang, X. Zhang, Huazhong Univ. of Science and Technology (China)
- 8562 1N **Image processing system design for microcantilever-based optical readout infrared arrays** [8562-63]
Q. Tong, L. Dong, Y. Zhao, C. Gong, X. Liu, Beijing Institute of Technology (China); X. Yu, Peking Univ. (China); L. Yang, W. Liu, Beijing Institute of Technology (China)
- 8562 1O **An optical readout method based on reflective filter for infrared imaging system** [8562-64]
W. Wang, M. Hui, C. Gong, L. Dong, M. Liu, X. Liu, Y. Zhao, Beijing Institute of Technology (China)
- 8562 1P **Optimal design of high frequency readout IC for short-wave IRFPA** [8562-65]
P. Wang, G. Chen, L. Gao, J. Zhou, Shanghai Institute of Technical Physics (China) and Graduate Univ. of the Chinese Academy of Sciences (China); R. Ding, Shanghai Institute of Technical Physics (China)

- 8562 1Q **Infrared and color visible image fusion system based on luminance-contrast transfer technique** [8562-66]
B. Wang, W. Gong, C. Wang, Wuhan National Labs. for Optoelectronics (China)
- 8562 1R **Theoretical and experimental research on recovering line shape with wavelength modulation spectroscopy** [8562-67]
L. Lan, Y. Ding, Z. Peng, Tsinghua Univ. (China)
- 8562 1S **Terahertz polarizing beam splitter based on copper grating on polyimide substrate** [8562-68]
M. Zhang, X. Li, W. Wang, J. Liu, Z. Hong, China Jiliang Univ. (China)
- 8562 1T **The design of infrared spaceborne remote sensing signal processing circuit for multi-spectral and multi-focal plane** [8562-69]
T. Liu, H. Wang, Beijing Institute of Space Mechanics and Electricity (China)
- 8562 1X **High-frequency analysis on RCS from terahertz conductive targets in free space** [8562-74]
H. Hua, Y. Jiang, BeiHang Univ. (China); L. Su, Institute of Remote Sensing Applications (China); D. Wen, R. Yu, Z. Cheng, G. Yu, BeiHang Univ. (China)
- 8562 1Y **Low frequency collective vibrational spectra of zwitterionic glycine studied by DFT** [8562-75]
M. S. Ma, C. Hua, C. Y. Ping, Southeast Univ. (China)
- 8562 1Z **Removal of complex-conjugate ambiguity in SD-OCT by using phase shifting** [8562-76]
W. Cai, Z. Jiang, H. Huang, Beijing Univ. of Technology (China)
- 8562 20 **Infrared image quality assessment based on fractal dimension method** [8562-77]
Z. Zhang, J. Zhang, S. Yue, C. Wang, Wuhan National Labs. for Optoelectronics (China)
- 8562 21 **Optimization for the heating pulse used in infrared thermography non-destructive testing technology** [8562-79]
G. Li, L. Feng, C. Zhang, Capital Normal Univ. (China)
- 8562 22 **An improved algorithm based on ROMP used in TH imaging** [8562-81]
Z. Li, Beijing Institute of Technology (China) and Capital Normal Univ. (China); X. Liu, Y. Zhao, Beijing Institute of Technology (China); C. Zhang, Capital Normal Univ. (China)
- 8562 23 **A signal processing system of remote sensing infrared camera based on oversample and comb filter** [8562-82]
N. Lei, Z. Wei, H. Wang, T. Li, Beijing Institute of Space Mechanics and Electricity (China)
- 8562 24 **One dimension high range resolution profile of terahertz radar** [8562-83]
M. Liang, B. Zeng, C. Zhang, Beijing Institute of Technology (China) and Capital Normal Univ. (China); Y. Zhao, Beijing Institute of Technology (China)
- 8562 25 **A novel 32×1 readout integrated circuit with high dynamic range for IRFPA** [8562-85]
Z. Miao, N. Li, Z. Li, Shanghai Institute of Technical Physics (China)

- 8562 26 **A new ROIC with high-voltage protection circuit of HgCdTe e-APD FPA for passive and active imaging** [8562-86]
G. Chen, Shanghai Institute of Technical Physics (China) and Graduate Univ. of the Chinese Academy of Sciences (China); J. Zhang, Shanghai Institute of Technical Physics (China); P. Wang, J. Zhou, L. Gao, Shanghai Institute of Technical Physics (China) and Graduate Univ. of the Chinese Academy of Sciences (China); R. Ding, Shanghai Institute of Technical Physics (China)

Author Index

Symposium Committees

General Chairs

Eustace L. Dereniak, College of Optical Sciences, The University of Arizona (United States)

Bingkun Zhou, Tsinghua University (China)

General Cochairs

Arthur Chiou, National Yang-Ming University (Taiwan, China)

Zhizhan Xu, Shanghai Institute of Optics and Fine Mechanics (China)

Jianlin Cao, China Ministry of Science and Technology (China)

Junhao Chu, Shanghai Institute of Technical Physics (China)

Technical Program Chairs

Songlin Zhuang, Shanghai University of Science and Technology (China)

Xingde Li, Johns Hopkins University (United States)

Technical Program Cochairs

Qiming Wang, Institute of Semiconductors (China)

Xu Liu, Zhejiang University (China)

Daoyin Yu, Tianjin University (China)

Qihuang Gong, Peking University (China)

Tianchu Li, National Institute of Metrology (China)

Wei Huang, Nanjing University of Posts and Telecommunications (China)

Local Organizing Committee Chair

Guangcan Guo, University of Science and Technology of China (China)

Local Organizing Committee Cochairs

Guoqiang Ni, Beijing Institute of Technology (China)
Shusen Xie, Fujian Normal University (China)
Xiaomin Ren, Beijing University of Posts and Telecommunications
(China)
Ying Gu, PLA General Hospital (China)
Huilin Jiang, Changchun University of Science and Technology
(China)

General Secretary

Qihuang Gong, Peking University (China)

Local Organizing Committee

Yan Li, Chinese Optical Society/Peking University (China)
Zhiping Zhou, Peking University (China)
Changhe Zhou, Shanghai Institute of Optics and Fine Mechanics
(China)
Qingming Luo, Huazhong University of Science and Technology
(China)
Chongxiu Yu, Beijing University of Posts and Telecommunications
(China)
Hongda Chen, Institute of Semiconductors (China)
Yongtian Wang, Beijing Institute of Technology (China)
Yiping Cui, Southeast University (China)
Xuping Zhang, Nanjing University (China)
Feijun Song, Daheng Corporation (China)
Cunlin Zhang, Capital Normal University (China)
Yanting Lu, Nanjing University (China)
Yuejin Zhao, Beijing Institute of Technology (China)
Chunqing Gao, Beijing Institute of Technology (China)
Tiegen Liu, Tianjin University (China)
Xiaocong Yuan, Nankai University (China)
Weimin Chen, Chongqing University (China)
Zhongwei Fan, Academy of Optoelectronics (China)
Hanyi Zhang, Tsinghua University (China)
Lan Wu, Zhejiang University (China)
Yongsheng Zhang, University of Science and Technology of China
(China)
Hong Yang, Peking University (China)
Xiaoying Li, Tianjin University (China)
Lin Zhai, Chinese Optical Society (China)

Conference Committee

Conference Chairs

Cunlin Zhang, Capital Normal University (China)
Xi-Cheng Zhang, University of Rochester (United States)
He Li, Shanghai Institute of Technical Physics (China)
Sheng-Cai Shi, Purple Mountain Observatory (China)

Conference Program Committee

Peter A. Ade, Cardiff University (United Kingdom)
Yi Cai, Kunming Institute of Physics (China)
Hou-Tong Chen, The Center for Integrated Nanotechnologies
(United States)
Yuping Cui, Jinhang Institute of Technical Physics (China)
Haewook Han, Pohang University of Science and Technology
(Korea, Republic of)
Weiqi Jin, Beijing Institute of Technology (China)
Ci-Ling Pan, National Tsing Hua University (Taiwan, China)
Jiancheng Shi, Institute of Remote Sensing Applications (China)
Alexander Pavlovich Shkurinov, Lomonosov Moscow State University
(Russian Federation)
Masahiko Tani, University of Fukui (Japan)
Chao Zhang, University of Wollongong (Australia)
Yan Zhang, Capital Normal University (China)

Session Chairs

- 1 Session 1
Cunlin Zhang, Capital Normal University (China)
- 2 Session 2
Cunlin Zhang, Capital Normal University (China)
- 3 Session 3
Xi-Cheng Zhang, University of Rochester (United States)
- 4 Session 4
Xi-Cheng Zhang, University of Rochester (United States)
- 5 Session 5
Sheng-Cai Shi, Purple Mountain Observatory (China)

- 6 Session 6
Guozhong Zhao, Capital Normal University (China)
- 7 Session 7
Jingling Shen, Capital Normal University (China)
- 8 Session 8
Jingling Shen, Capital Normal University (China)

Quantum dot lasers and relevant nanoheterostructures

Alexey E. Zhukov^{*a}, Natalia V. Kryzhanovskaya^a, Artem V. Savelyev^a, Alexey M. Nadtochiy^a, Ekaterina M. Arakcheeva^a, Fedor I. Zubov^a, Vladimir V. Korenev^a, Mikhail V. Maximov^b, Yuri M. Shernyakov^b, Marina M. Kulagina^b, Ilia A. Slovinskiy^b, Daniil A. Livshits^c, Alexandros Kapsalis^d, Charis Mesaritis^d, Dimitris Syvridis^d, Alexander Mintairov^c

^aSt. Petersburg Academic University, Khlopina 8(3), St Petersburg, Russia 194021; ^bIoffe Physical-Technical Institute, Politekhnikeskaya 26, St Petersburg, Russia 194021; ^cInnolume GmbH, Konrad-Adenauer-Allee 11, Dortmund, Germany 44263; ^dUniversity of Athens, Athens, Greece 15784;

^eUniversity of Notre Dame, 275 Fitzpatrick Hall, Notre Dame, IN 46556, USA

ABSTRACT

Spectral and power characteristics of QD stripe lasers operating in two-state lasing regime have been studied in a wide range of operation conditions. It was demonstrated that neither self-heating nor increase of the homogeneous broadening are responsible for quenching of the ground-state lasing beyond the two-state lasing threshold. It was found that difference in electron and hole capture rates strongly affects light-current curve. Modulation *p*-type doping is shown to enhance the peak power of GS lasing transition. Microring and microdisk structures ($D = 4\text{--}9\ \mu\text{m}$) comprising $1.3\ \mu\text{m}$ InAs/InGaAs quantum dots have been fabricated and studied by μ -PL and NSOM. Ground-state lasing was achieved well above room temperature (up to 380 K). Effect of inner diameter on threshold characteristics was evaluated.

Keywords: Quantum dots, semiconductor laser, microring resonator, two-state lasing

1. INTRODUCTION

For various applications, including optical data transmission, pumping of Raman amplifiers, aesthetic laser surgery, etc, efficient lasers operating around $1.3\ \mu\text{m}$ are requested. Lasers based on self-organized InAs/InGaAs quantum dots (QDs) offer an attractive combination of the required wavelength with extremely low threshold current density and high characteristic temperature. However, at sufficiently high currents a shorter-wavelength ($\lambda \sim 1.2\ \mu\text{m}$) band caused by the first excited-state (ES1) transition appears in the spectrum¹. Such a behavior is now referred to as two-state lasing. For a majority of applications two-state lasing has to be suppressed whereas the GS spectral component of the lasing spectrum has to be maximized. Analysis of QD laser behavior based on rate² and master³ equations predicts that optical power of the GS component reaches its maximal value at threshold of the two-state lasing and then persists. However a number of experimental facts revealed that the GS component declines down to its complete quenching^{4,5} due probably to laser self-heating in CW regime⁴ and/or increase of homogeneous broadening⁵ have been proposed. To clarify possible reasons of the GS lasing quenching we studied spectral and light-current characteristics of broad-area QD lasers.

Microdisks and microrings optical resonators comprising a III-V active region are promising candidates for light emitters to be integrated with silicon photonic circuits. Owing to a combination of a compact size and a high Q-factor, which can be achieved in such structures, ultralow threshold operation is expected. Although the majority of whispering gallery mode (WGM) resonators has been contained quantum-well active region composed of InP-based materials⁶, QDs may have certain advantages. These include attainability of $1.3\ \mu\text{m}$ emission in GaAs-based structures with high refractive index contrast, low temperature sensitivity, suppressed sidewall recombination rates⁷, making it possible to achieve lasing in resonators of small diameter. Since the first report⁸ on QD microdisk laser capable of operating at 77K, significant progress has been made toward high-temperature lasing. In particular, room-temperature lasing has been reported to date for microdisks of few microns in diameter⁹, whereas for relatively large microrings ($35\text{--}85\ \mu\text{m}$) lasing has been recently extended up to 50°C ¹⁰. In the present work we demonstrate ground-state lasing up to 107°C for optically pumped microring lasers (MRLs) having an outer diameter as small as $6\text{--}7\ \mu\text{m}$.

*zhukale@gmail.com; phone 7 812 4488594; fax 7 812 4486994; www.spbau.ru

2. TWO-STATE LASING AND ITS SUPPRESSION IN QD LASERS

2.1 Quenching of GS spectral component

Epitaxial structures comprising a single plane or multiple planes of InAs/InGaAs QDs were grown by molecular beam epitaxy. Stripe lasers of various cavity lengths were tested in pulse regime (300ns @ 2 kHz) on temperature-stabilized heatsink. An evolution of the lasing spectrum with increasing the pump current is shown in Figure 1,a for a 4-mm-long single-QD-plane laser at 17°C. The corresponding light-current characteristics (total output power and optical power of GS and ES1 spectral components of the spectrum) are presented in Figure 1,b. The ES1 band (around 1.18 μm) appears in the spectrum at approximately 3 A whereas the GS component reaches its maximum at 5A, well beyond the onset of two-state lasing. A complete quenching of the GS lasing is observed at 12 A.

Figure 1. Lasing spectra at different currents (a); laser power (b): dashed-dotted curve – total (GS+ES1), solid curve – ground-state component (GS), dashed curve – first excited-state component (ES1).

As it is seen in Figure 1,a the GS band is split into two peaks (~ 1.254 and ~ 1.262 nm). According to M. Sugawara et al⁵ this splitting can be attributed to the homogenous broadening of the QD optical transition. They also suggested that the GS lasing quenching at high currents could be explained by increase of the homogenous broadening. In spite of this we found that the splitting is practically unchanged (6.5 ± 0.4 meV) as current increases up to 12 A. Therefore, the quenching can not be associated with the aforementioned reason. Moreover, spectral positions of the both GS peaks also remain very stable so that the current-induced red shift is only 0.4 nm. Such a shift corresponds to a negligible temperature increment of about 1°C which can not itself lead to suppression of the GS lasing because in this particular laser diode the GS lasing at low currents can be observed up to 68°C. Thus, the GS lasing quenching at high currents can not be attributed to self-heating of the active region as well.

2.2 Effect of difference in electron and hole relaxation rates

More sophisticated model that does not imply either the homogeneous broadening or self-heating effect is based on assumption of the asymmetry in charge carrier distribution in a QD¹¹. Energy separation of ground- and excited-state energy levels of holes is much smaller than kT that leads to a nearly equal probability of occupation of the hole levels. As a result, there is a competition for the “joint holes” between electrons of the ground-state and the excited-state levels. Because the ES1 electron level has a higher degeneracy as compared to the GS level, in the regime of two-state lasing the holes are effectively swept out from QDs because of their recombination with ES1 electrons. In its turn this leads to the quenching of the GS lasing as the pump current grows.

Figure 2. L - I curves for ground-state component (a): circles – experiment; lines – calculation for different ratio of hole-to-electron relaxation rates (h). Operation diagram of QD laser: heavy lines separates regions of different lasing regimes (NL – no lasing, GS – pure ground-state lasing, GS+ES1 – two-state lasing, ES1 – pure excited-state lasing); thin lines correspond to different h values.

However, we found that the observed experimental data can not be quantitatively described if one takes into account only the above-mentioned asymmetry. Reasonable agreement between modeling results and experiment was achieved under assumption that electron and hole relaxation rates into QDs are different. More precisely, we assumed that the hole capture is slower than the electron one which makes the competition for holes more pronounced and leads to complete quenching of the GS lasing at lower pumps. Figure 2,a shows the calculated evolution of the GS power with the pump current. The results are shown for different ratio of the hole-to-electron relaxation rates h which is assumed to be independent of the injection rate. The best agreement of the model results with the experiment is found for $h = 0.75$. Lower rate of the hole relaxation is probably associated with their slower velocity in the matrix/wetting layer. Using the

extracted value of h we can also reproduce fairly well temperature dependences of the two-state lasing threshold and the current of the GS-lasing quenching.

Using the proposed model we are capable of calculating the operation diagram of QD laser as shown in Figure 2,b. The diagram depicts different regimes of the laser operation as a function of electron (g_{ec}) and hole (g_{hc}) capture rates: subthreshold regime of no lasing (NL), regime of lasing via GS optical transition (GS), two-state lasing regime (GS+ES1), regime of lasing via ES1 transition only (ES1). Depending on the ratio of hole-to-electron relaxation rates ($h = g_{hc}/g_{ec}$) and the total optical loss various scenarios of laser behavior can be realized. In particular, in case of sufficiently fast hole capture ($h = 1$ in Figure 2,b) the two-state lasing can persist so that the GS lasing peak is not completely suppressed even at very high injection levels.

2.3 Effect of p -type doping

Modulation p -type doping of QDs may noticeably improve temperature stability of the threshold current¹². We found that p -doping affects the two-state lasing behavior as well. Temperature dependences of the two-state lasing threshold current as well as the ground-state lasing threshold current are presented in Figure 3 for two 0.6-mm-long diodes of similar design (10 planes of InAs/InGaAs QDs): one with undoped active region and another with modulation doping (~ 10 acceptors per QD). The GS-lasing thresholds measured at room temperature are nearly equal in both structures (~ 0.35 A). At the same time, the onset of the two-state lasing is significantly shifted to higher currents in the p -type doped laser (~ 5.5 A) as compared to its undoped analogue (~ 1.1 A). Light-current curve (insert of Figure 3) demonstrates that the maximum optical power of the GS spectral component reaches 3.6 W in the laser with p -type doping, while it is about 2.4 W in the undoped counterpart. Another finding is that the temperature interval, where GS lasing can be achieved, extends to higher temperatures in the p -doped structure (from 55 to 100°C).

Figure 3. Threshold vs temperature for ground-state lasing (solid symbols) and two-state lasing (open symbols) in lasers with undoped (circles) and p -type doped (squares) QDs. Insert: power of the GS-line vs current.

2.4 Comparison of lasing and spontaneous emission spectra

Spontaneous emission spectra may provide additional information on peculiarities of the two-state lasing. We studied QD lasers having 4 cleaved facets where both lasing and spontaneous emission can be simultaneously detected as shown in Figure 4. At least five peaks of different origin are easily resolved: two narrow peaks of lasing emission via ground-state (1264.3 nm) and first excited-state (1179.8 nm) transitions and three broad peaks of spontaneous emission via ground-state (1264.0 nm), first excited (1172.0 nm) and second excited-state (1108.4 nm) transitions. The characteristic feature is that the GS lasing peak nearly coincides with the peak position of GS spontaneous emission. This implies that the GS lasing arises from QDs of the most probable (mean) size. At the same time ES1 lasing peak is noticeably red-shifted with respect to the peak position of ES1 spontaneous emission indicating that QDs, which size is larger than the mean one, are chiefly responsible for the ES lasing. Similar behavior was observed in a wide interval of current density.

Figure 4. Emission spectrum: squares – experiment, solid curves – lasing emission, dotted curves – spontaneous emission. Insert: peak position vs current density: solid circles – GS lasing, open circles – ES1 lasing, solid curve – GS spontaneous emission, dotted curve – ES1 spontaneous emission.

3. MICRORING STRUCTURES

3.1 Experiment

An epitaxial structure was grown by molecular beam epitaxy on semi-insulating GaAs(100) substrate. An active region comprises five layers of InAs/In_{0.15}Ga_{0.85}As QDs separated by 30-nm-thick GaAs spacers. The active region was inserted into a 220-nm-thick GaAs waveguiding layer confined by 20-nm-thick Al_{0.3}Ga_{0.7}As barriers. A 400-nm-thick Al_{0.98}Ga_{0.02}As cladding layer was grown beneath the waveguiding layer. Microrings were defined by photolithography and Ar⁺-etching. The outer diameter was varied in different structures from $D = 4$ to $9\ \mu\text{m}$. The inner diameter ranges from $d = 0$ (microdisks) to $d \approx 0.8D$. Finally, the cladding layer was selectively oxidized into (AlGa)_xO_y. Typical microphotograph of the resonator structure is shown in Figure 5.

Figure 5. SEM image of QD microring laser ($D = 6\ \mu\text{m}$, $d = 2\ \mu\text{m}$).

For optical experiments a CW-operating YAG:Nd laser ($\lambda = 532\text{nm}$) was used together with a cooled Ge *pin*-diode. Measurements at elevated temperatures were performed with the structures mounted onto a heated holder equipped with a temperature controller. Low temperature measurements were done in a flow cryostat.

3.2 Low-temperature measurements

An example of luminescence spectrum taken at 77 K from 6 μm -ring with 2 μm inner diameter is shown in Figure 6. Four series of whispering gallery modes of different radial order are clearly observed. All modes presented in the optical spectrum were identified by means of 2D-axisymmetric analysis. The dominant modes are of $n = 2$ and 3 order. Significant overlap of many modes exists (e.g. around 1190.8 nm where 3 modes are close together).

Figure 6. Low-temperature luminescence spectrum of the microring. Estimated mode orders $\text{TE}_{m,n}$ are indicated near the peaks.

3.3 Near-field scanning optical microscopy.

Spatial distribution of light intensity inside the microresonators was studied by means of near-field scanning optical microscopy (NSOM). Several typical NSOM images are presented in Figure 7. Characteristic WGM patterns are clearly seen. Depending on spectral position of the luminescence peaks, NSOM images reveal modes of different radial and azimuthal order.

Figure 7. NSOM images demonstrating WGM modes of different orders in the microring resonator.

3.4 Room-temperature measurements.

A representative room-temperature $\mu\text{-PL}$ spectrum taken under low excitation is shown in the left insert of Figure 8. Full width at half maximum for resonant peaks varies from 0.143 to 0.234 nm giving the quality factor of about 9000.

The threshold power for the microring/microdisk structures was estimated from a light-light curve of the dominant mode. An example is presented in Figure 8 where a characteristic knee is clearly seen. In this particular case ($D = 7 \mu\text{m}$,

$d = 3.4 \mu\text{m}$) the threshold power is 0.37 mW. No correction was made to take into account partial light reflection from the surface or waste of the excitation power in the inner area of microring structures. Overall the threshold power at room temperature in different structures ranges from few tenths of mW to few mW. From one to three modes were usually observed in room-temperature lasing spectra (see right insert of Figure 8).

Figure 8. Intensity of the dominant mode against excitation power (symbols). Curve is a guide to the eye. Insert: luminescence spectrum below threshold (left) and above threshold (right).

Room-temperature threshold characteristics of the microstructures with different inner diameters were compared. In most cases the threshold power (absolute value) decreases by approximately 30-40% as the inner diameter increases from 0 (disk) to $0.3-0.6 D$, see Figure 9. Further ring thinning results in rapid growth of the threshold. As for the effect of the outer diameter, the lowest threshold of 0.37-0.4 mW was found in microrings having an outer diameter of 6–7 μm . Both larger and smaller microrings demonstrate higher threshold power as shown in the insert of Figure 9.

Figure 9. Room-temperature threshold (normalized to the threshold of the microdisk structure) as a function of inner diameter. Insert: the lowest threshold against the outer diameter.

3.5 High-temperature measurements

Threshold power increases super-exponentially with temperature. Around room temperature the characteristic temperature was estimated to be $\sim 60-75 \text{ K}$. In most cases, lasing can be observed up to $80-90^\circ\text{C}$ whereas the highest temperature of lasing was found to be as high as 107°C , Figure 10. To the best of our knowledge this is the highest

temperature ever reported for 1.3 μm QD MRLs. Below room temperature the threshold is nearly unchanged or even slightly increases. Temperature variation of the lasing wavelength is summarized in Figure 10. Spectral position of the ground-state optical transition of quantum-dot luminescence is also shown for comparison. It is seen that the lasing wavelength is quite stable (~ 0.05 nm/K) within relatively wide temperature intervals (e.g. from 20 to 40°C and then from 50 to 90°C) where a certain WGM mode remains the dominant one. Abrupt changes of the lasing wavelength (e.g. around 40-50°C) are due to hopping of the dominant mode.

Figure 10. Temperature dependences of the threshold power (solid symbols) and wavelengths of the dominant mode (open symbols). QD ground-state optical transition against temperature (dashed curve) is also shown. Solid curve is exponential fit with $T_0=65$ K.

4. CONCLUSIONS

Quantum dot lasing structures of two sorts both emitting around 1.3 μm were studied: broad-area diode lasers and optically pumped microresonators.

Broad-area lasers were used for detailed investigation of the two-state lasing phenomenon and, in particular, quenching of the ground-state lasing emission that observed at high currents. It was demonstrated that the most probable reason for the GS lasing quenching is asymmetry of electrons and holes carrier distributions. Additionally, difference in capture rates of electrons and holes has to be taken into consideration. We also found that the GS-component reaches its maximum beyond the threshold of the two-state lasing and that different groups of QDs are responsible for GS- and ES1-lasing in the two-state lasing regime. Finally, we demonstrated that *p*-type modulation doping of QDs leads to noticeable suppression of the ES1-lasing thereby resulting in enhancement of peak power of the GS spectral component.

Microrings and microdisks of few micrometers in diameter were made by ion etching and selective oxidation with Q-factor of about 9000. Whispering gallery modes of second and third radial orders dominate the luminescence spectrum. Nearly single-mode lasing was observed at elevated temperatures. The lowest threshold (around 0.4 mW at RT) was found in microdisks of intermediate diameter (6-7 μm) with approximately 50% inner aperture. The highest temperature was found to be 107°C and the threshold was in mW-range.

ACKNOWLEDGEMENTS

The work is supported in different parts by Russian Ministry of Science and Education, Russian Foundation for Basic Research, Programs of Fundamental Studies of the Russian Academy of Sciences. NVK is thankful for support to Saint-Petersburg's Committee on Science and Higher School.

REFERENCES

- [1] Zhukov, A. E., Kovsh, A. R., Livshits, D. A., Ustinov, V. M. and Alferov, Zh. I., "Output power and its limitation in ridge-waveguide 1.3 μm wavelength quantum-dot lasers," *Semicond. Sci. Technol.* 18(8), 774-781 (2003).
- [2] Markus, A., Chen, J. X., Gauthier-Lafaye, O., Provost, J.-G., Paranthoën, C. and Fiore, A., "Impact of intraband relaxation on the performance of a quantum-dot laser," *IEEE J. Select. Topics Quantum Electron.* 9(5), 1308-1314 (2003).
- [3] Markus, A. and Fiore, A., "Modeling carrier dynamics in quantum-dot lasers," *phys. stat. sol. (a)* 201(2), 338-344 (2004).
- [4] Ji, H.-M., Yang, T., Cao, Y.-L., Xu, P.-F., Gu, Y.-X. and Wang, Zh.-G., "Self-heating effect on the two-state lasing behaviors in 1.3- μm InAs-GaAs quantum-dot lasers," *Jpn. J. Appl. Phys.* 49(7), 072103 (2010).
- [5] Sugawara, M., Hatori, N., Ebe, H., Ishida, M., Arakawa, Y., Akiyama, T., Otsubo, K. and Nakata, Y., "Modeling room-temperature lasing spectra of 1.3- μm self-assembled InAs/GaAs quantum-dot lasers: Homogeneous broadening of optical gain under current injection," *J. Appl. Phys.* 97(4), 043523 (2005).
- [6] Liang, D., Fiorentino, M., Srinivasan, S., Bowers, J. E. and Beausoleil, R. G., "Low threshold electrically-pumped hybrid silicon microring laser," *IEEE J. Selected Topics Quantum Electron.*, 17(6), 1528 - 1533 (2011).
- [7] Ouyang, D., Ledentsov, N. N., Bimberg, D., Kovsh, A. R., Zhukov, A. E., Mikhlin, S. S. and Ustinov, V. M., "High performance narrow stripe quantum-dot lasers with etched waveguide," *Semicond. Sci. Technol.* 18(12) L53-L54 (2003).
- [8] Cao, H., Xu, J. Y., Xiang, W. H., Ma, Y., Chang, S.-H., Ho, S. T. and Solomon, G. S., "Optically pumped InAs quantum dot microdisk lasers," *Appl. Phys. Lett.* 76(24), 3519-3521 (2000).
- [9] Ide, T., Baba, T., Tatebayashi, J., Iwamoto, S., Nakaoka, T. and Arakawa, Y., "Room temperature continuous wave lasing in InAs quantum-dot microdisks with air cladding," *Opt. Express* 13(5), 1615-1620 (2005).
- [10] Munsch, M., Claudon, J., Malik, N. S., Gilbert, K., Grosse, P., Gerard, J.-M., Albert, F., Langer, F., Schlereth, T., Pieczarka, M. M., Hofling, S., Kamp, M., Forchel, A. and Reitzenstein, S., "Room temperature, continuous wave lasing in microcylinder and microring quantum dot laser diodes," *Appl. Phys. Lett.* 100(3), 031111 (2012).
- [11] Viktorov, E. A., Mandel, P., Tanguy, Y., Houlihan, J. and Huyet, G., "Electron-hole asymmetry and two-state lasing in quantum dot lasers," *Appl. Phys. Lett.* 87(5), 053113 (2005).
- [12] Fathpour, S., Mi, Z., Bhattacharya, P., Kovsh, A. R., Mikhlin, S. S., Krestnikov, I. L., Kozhukhov, A. V., and Ledentsov, N. N., "The role of Auger recombination in the temperature-dependent output characteristics ($T_0=\infty$) of p-doped 1.3 μm quantum dot lasers," *Appl. Phys. Lett.* 85(2), 5164-5166 (2004).