PROCEEDINGS OF SPIE

[SPIDigitalLibrary.org/conference-proceedings-of-spie](https://spiedigitallibrary.org/conference-proceedings-of-spie)

Front Matter: Volume 9859

, "Front Matter: Volume 9859," Proc. SPIE 9859, Sensors for Next-Generation Robotics III, 985901 (22 June 2016); doi: 10.1117/12.2231218

SPIE.

Event: SPIE Commercial + Scientific Sensing and Imaging, 2016, Baltimore, MD, United States

PROCEEDINGS OF SPIE

Sensors for Next-Generation Robotics III

Dan Popa
Muthu B. J. Wijesundara
Editors

20-21 April 2016
Baltimore, Maryland, United States

Sponsored and Published by
SPIE

Volume 9859

Proceedings of SPIE 0277-786X, V. 9859

SPIE is an international society advancing an interdisciplinary approach to the science and application of light.

Sensors for Next-Generation Robotics III, edited by Dan Popa, Muthu B. J. Wijesundara,
Proc. of SPIE Vol. 9859, 985901 · © 2016 SPIE · CCC code: 0277-786X/16/\$18 · doi: 10.1117/12.2231218

Proc. of SPIE Vol. 9859 985901-1

The papers in this volume were part of the technical conference cited on the cover and title page. Papers were selected and subject to review by the editors and conference program committee. Some conference presentations may not be available for publication. Additional papers and presentation recordings may be available online in the SPIE Digital Library at SPIEDigitalLibrary.org.

The papers reflect the work and thoughts of the authors and are published herein as submitted. The publisher is not responsible for the validity of the information or for any outcomes resulting from reliance thereon.

Please use the following format to cite material from these proceedings:

Author(s), "Title of Paper," in *Sensors for Next-Generation Robotics III*, edited by Dan Popa, Muthu B. J. Wijesundara, Proceedings of SPIE Vol. 9859 (SPIE, Bellingham, WA, 2016) Six-digit Article CID Number.

ISSN: 0277-786X

ISSN: 1996-756X (electronic)

ISBN: 9781510601000

Published by

SPIE

P.O. Box 10, Bellingham, Washington 98227-0010 USA

Telephone +1 360 676 3290 (Pacific Time) • Fax +1 360 647 1445

SPIE.org

Copyright © 2016, Society of Photo-Optical Instrumentation Engineers.

Copying of material in this book for internal or personal use, or for the internal or personal use of specific clients, beyond the fair use provisions granted by the U.S. Copyright Law is authorized by SPIE subject to payment of copying fees. The Transactional Reporting Service base fee for this volume is \$18.00 per article (or portion thereof), which should be paid directly to the Copyright Clearance Center (CCC), 222 Rosewood Drive, Danvers, MA 01923. Payment may also be made electronically through CCC Online at copyright.com. Other copying for republication, resale, advertising or promotion, or any form of systematic or multiple reproduction of any material in this book is prohibited except with permission in writing from the publisher. The CCC fee code is 0277-786X/16/\$18.00.

Printed in the United States of America.

Publication of record for individual papers is online in the SPIE Digital Library.

**SPIE. DIGITAL
LIBRARY**
SPIEDigitalLibrary.org

Paper Numbering: *Proceedings of SPIE* follow an e-First publication model. A unique citation identifier (CID) number is assigned to each article at the time of publication. Utilization of CIDs allows articles to be fully citable as soon as they are published online, and connects the same identifier to all online and print versions of the publication. SPIE uses a six-digit CID article numbering system structured as follows:

- The first four digits correspond to the SPIE volume number.
- The last two digits indicate publication order within the volume using a Base 36 numbering system employing both numerals and letters. These two-number sets start with 00, 01, 02, 03, 04, 05, 06, 07, 08, 09, 0A, 0B ... 0Z, followed by 10-1Z, 20-2Z, etc. The CID Number appears on each page of the manuscript.

Contents

v	<i>Authors</i>
vii	<i>Conference Committee</i>
ix	<i>Introduction</i>

SESSION 1   SENSORS FOR NEXT-GENERATION ROBOTICS I

9859 02	Results and conclusions: perception sensor study for high speed autonomous operations [9859-1]
9859 03	Analysis of laser return pulse from multilayered objects [9859-2]
9859 04	Investigation of human-robot interface performance in household environments [9859-3]
9859 05	Package analysis of 3D-printed piezoresistive strain gauge sensors [9859-4]
9859 06	Human-like object tracking and gaze estimation with PKD android [9859-5]
9859 08	Electrical design and simulation of kinetic piezoelectric harvester for distributed control cells [9859-7]
9859 09	Comparison study of input shaping techniques to control an underactuated flexible link system [9859-8]
9859 0A	Design, static modeling and simulation of a 5-DOF precise piezoelectric positioner [9859-9]

SESSION 2   KEYNOTE SESSION

9859 0B	Ultraflexible nanostructures and implications for future nanorobots (Keynote Paper) [9859-20]

SESSION 3   SENSORS FOR NEXT-GENERATION ROBOTICS II

9859 0C	A flexible microchannel electrode array for peripheral nerves to interface with neural prosthetics [9859-10]
9859 0D	Feedforward and output feedback control of a highly oscillating and nonlinear 2-DOF piezoelectric actuator by using input shaping compensator and a linear quadratic regulator [9859-11]
9859 0E	Application requirements for Robotic Nursing Assistants in hospital environments [9859-12]

- 9859 OF **Design, modeling and simulation of a three-layer piezoelectric cantilevered actuator with collocated sensor** [9859-13]
- 9859 OH **Next force sensing technology for robots: multi-axis resonant sensors** [9859-17]
- 9859 OI **Flexible circuits with integrated switches for robotic shape sensing** [9859-18]
- 9859 OJ **An extremely lightweight fingernail worn prosthetic interface device** [9859-19]

POSTER SESSION

- 9859 OK **Piezoresistive pressure sensor array for robotic skin** [9859-15]

Authors

Numbers in the index correspond to the last two digits of the six-digit citation identifier (CID) article numbering system used in Proceedings of SPIE. The first four digits reflect the volume number. Base 36 numbering is employed for the last two digits and indicates the order of articles within the volume. Numbers start with 00, 01, 02, 03, 04, 05, 06, 07, 08, 09, 0A, 0B...0Z, followed by 10-1Z, 20-2Z, etc.

Ahluwalia, Simranjit, 0J	Wijesundara, Muthu B. J., 0C, 0K
Al Hamidi, Yasser, 09, 0D	Williams, Kathryn, 03
Alonzo, Rommel, 04	Yetkin, Oguz, 0J
Baptist, Joshua R., 05, 0J, 0K	
Barcola, Essodong, 08	
Bartasyte, Ausrine, 08	
Bugnariu, Nicoleta L., 06	
Castano-Cano, Davinson, 0H	
Close, Ryan, 02, 03	
Cohn, Robert W., 0B	
Cremer, Sven, 04, 0E	
Das, Sumit Kumar, 05, 06	
Doelling, Kris, 0E	
Gendreau, Dominique, 0A, 0F	
Grossard, Mathieu, 0H	
Hammouche, Mounir, 0F	
Harnett, C. K., 0I	
Hingeley, Anthony, 04	
Hollinger, Jim, 03	
Hubert, Arnaud, 0H	
Kasi-Okonye, Isioma, 0J	
Kim, Young-tae, 0C	
Lacaze, Alberto, 02	
LaCelle, Zachary, 02	
Landrith, Ryan, 0C	
Lee, Woo H., 05, 0K	
Lundberg, Cody L., 0E	
McNair, Mike, 0E	
Middleton, Seth, 03	
Miller, Haylie L., 06	
Mirza, Fahad, 04, 0K	
Mohand-Ousaid, Abdenbi, 0A, 0F	
Murphy, Karl, 02	
Nguyen, Son, 03	
Nothnagle, Caleb, 0C	
Ouisse, Morvan, 08	
Panchapakesan, Balaji, 0B	
Popa, Dan O., 04, 05, 06, 0E, 0J, 0K	
Rakotondrabe, Micky, 08, 09, 0A, 0D, 0F	
Rougeot, Patrick, 0A, 0F	
Rupp, Ronald, 03	
Sahasrabuddhe, Ritvij R., 05, 0K	
Schneider, Anne, 02	
Shin, Jeongsik, 0E	
Silva, Dinithi, 0J	
Tuladhar, Yathartha, 04	
Vessey, Alyssa, 03	
Volker, Rachael, 0J	
Wijayasinghe, Indika B., 06	

Conference Committee

Symposium Chair

Ming C. Wu, University of California, Berkeley (United States)

Symposium Co-chair

Majid Rabbani, Eastman Kodak Company (United States)

Conference Chairs

Dan Popa, University of Louisville (United States)

Muthu B. J. Wijesundara, The University of Texas at Arlington Research Institute (United States)

Conference Program Committee

Ashis G. Banerjee, University of Washington (United States)

Ryan R. Close, U.S. Army Night Vision and Electronic Sensors Directorate (United States)

Yong-Lae Park, Carnegie Mellon University (United States)

Micky Rakotondrabe, FEMTO-ST (France)

Veronica J. Santos, University of California, Los Angeles (United States)

Session Chairs

- 1 Sensors for Next-Generation Robotics I
Dan Popa, University of Louisville (United States)
Muthu B. J. Wijesundara, The University of Texas at Arlington Research Institute (United States)
- 2 Keynote Session
Dan Popa, University of Louisville (United States)
Muthu B. J. Wijesundara, The University of Texas at Arlington Research Institute (United States)
- 3 Sensors for Next-Generation Robotics II
Dan Popa, University of Louisville (United States)
Muthu B. J. Wijesundara, The University of Texas at Arlington Research Institute (United States)

Introduction

Goals of this Conference

Due to the proliferation of mass-produced, miniaturized sensors, it is now possible to envision massively distributed sensors being used to enhance perception, cognition, and control capabilities of next-generation robots. In fact, applications where new, more intelligent robots are needed cut across all dimensional scales and industrial sectors. Examples include assisted living environments, search and rescue in disaster areas, neural and vision prosthetics, nano-manufacturing, self-driving vehicles, human-friendly industrial assembly and smart material handling, and so on. One exciting next-generation application is endowing humanoid robots with perception comparable with those of humans: including not only distributed touch through robotic skin, hearing, and vision, but also super-human perception, such as the ability to see in the dark or through objects. Using off-the-shelf sensors that have not been designed specifically for robotics is fraught with challenges that must be mitigated by consideration of power, weight, form factor, and interconnections early in the design process.

This conference focuses on new sensors and sensor arrays for robotics and autonomous vehicles, new form factors and packaging schemes to help integrate robots and sensors, new applications of robots enabled by increased perception capabilities, and challenges in sensor fusion, networking and control brought about by massive amounts of sensor data available to the robot. The conference promotes technical scientific papers related to robot sensors that push beyond the state-of-the-art in industry and new robotics applications, including those with dual uses (e.g., military-defense and commercial-industrial).

Summary of the Third Conference

The third Sensors for Next-Generation Robotics conference was held at the SPIE Defense+Commercial Sensing (DCS) symposium in Baltimore, Maryland, United States on April 20-21, 2016. The poster entitled "Piezoresistive pressure sensor array for robotic skin" was presented by Fahad Mirza, a graduate student at the University of Texas at Arlington (United States), and Mirza discussed the experimental results with printed arrays of piezo-resistive strain gauges and embedded silicone polymers. These sensors have applications, such as touch sensitive whole body robot skin for the next-generation service and assistive robots that are soft, safe and collaborate with humans. The work was documented in proceedings paper 98590K [9859-15].

On April 21st, presentations were organized in three tracks dedicated to small-scale robotics, human-size assistive robots, and autonomous vehicles. The morning session consisted of the following speakers:

- Anne Schneider of Robotics Research, LLC (United States) spoke of perception sensor studies for ground vehicles. This was a very important experimental study evaluating three commercially available lidar units for figures of merit relevant to their use in robotic ground vehicles. This study was a continuation of their work presented at the SPIE STA 2015 conference, and was documented in paper 985902 [9859-1].
- Jim Hollinger of Land Sea Air Autonomy, LLC (United States) spoke of evaluating the return signals of lidars due to secondary reflections from objects covered in foliage. Unlike airborne imaging, the reflections considered in this study came from objects considerably closer together than the tree canopy to ground, therefore measurement resolutions will be considerably different. Eventually, this study will be important when deploying this technology on ground autonomous vehicles. This presentation continued work presented at SPIE STA 2015, and was documented in paper 985903 [9859-2].
- Sven Cremer, a graduate student at the University of Texas at Arlington (United States), presented his work on evaluating the performance of a human-robot interface with a mobile manipulator. Such manipulators consist of a mobile base and a multi-degrees of freedom arm, which can be operated remotely from a tablet or with direct contact using pressure-sensitive robot skin. This study is important to future applications of this technology in service robots for homes, and it is a continuation of work presented at SPIE STA 2015, which was documented in paper 985904 [9859-3].
- Sumit Das, a graduate student at the University of Louisville (United States), presented his work on creating and validating a Finite Element Model for packaged pressure sensitive skin sensors. These models are important for designing and evaluating application specific sensors and sensor arrays prior to fabrication. The work was documented in paper 985905 [9859-4].
- Indika Wijayasinghe, research associate at the University of Louisville (United States), presented his work on calibrating optical sensing systems measuring the eye gaze and head pose of humans and humanoid robots. His work synchronized data from three separate motion capture systems and used it to develop advanced controllers for android robots that resemble human capabilities. This work was documented in paper 985906 [9859-5].
- Jeremy Straub, a graduate student at the University of North Dakota (United States), presented his work on using a multi-camera system to retrofit 3-D printers in order to reduce defects and improve the quality of manufactured objects.
- Micky Rakotondrabe, Professor at FEMTO-ST Institute in Besancon, France, presented his work on the improved circuit design for piezo-electric energy

harvesters. This work can lead to very exciting applications, as harvesters can be placed on vibrating/moving machinery, robots, and vehicles to power remote sensors. This work was documented in paper 985908 [9859-7].

- Yasser Al Hamidi, a graduate student at Texas A&M University of Qatar (Qatar), presented his work on comparing input shaping methods for control of flexible structures. This technique is particularly useful when controlling next generation robots that are flexible. Furthermore, they can be very useful whenever adding feedback sensors is not possible, such as in the case of micro and nano robots. This work was documented in paper 985909 [9859-8].
- Abdenbi Mohand Ousaid, Professor at FEMTO-ST Institute in Besancon, France, presented his work on a 5 Degrees of Freedom piezoelectric positioner. His research will lead to novel, 3D-printed stages for nanopositioning applications, such as inside SEM and AFM. This work was documented in paper 98590A [9859-9].

Professor Robert Cohn from University of Louisville (United States) gave the exciting keynote presentation entitled "Ultraflexible nanostructures and implications for future nanorobots," which is documented in paper 98590B [9859-20]. His presentation offered an intriguing perspective on types of actuators that are physically realizable at the nanoscale, in particular polymeric nanoactuators that experience contraction under laser irradiation or "cable-like" nanorods that are flexible and amplify motion. Numerous examples of nanostructures from Professor Cohn's laboratory were provided along with representative figures of merit, such as force output, displacement, and bandwidth. This presentation spurred discussion and perhaps future collaborations between robotics, MEMS, and nanotechnology researchers to create the next-generation nanoscale robots with applications in biology and manufacturing.

The afternoon session of the conference focused on new sensors for multiscale robotics applications from the micro scale to the human scale. Speakers included:

- Ryan Landrith, Research Scientist at the University of Texas at Arlington Research Institute (United States), who gave a talk about fabrication and evaluation of microchannel electrode arrays for neural interfaces. MEMS fabricated electrodes can be implanted and electrically connected with peripheral nerves for recording and stimulation, as demonstrated in animal trials, and they will be used by amputees to control prosthetic devices. This work was documented in paper 98590C [9859-10].
- Yasser Al Hamidi, a graduate student at Texas A&M University of Qatar (Qatar), who presented his ongoing work on using input shaping techniques to improve the control of 2 Degrees of Freedom piezoelectric tube actuators. These actuators are used in precision instruments like Atomic

Force Microscopes, and they currently require electronic control and optical feedback sensors to achieve high positioning accuracy. Input shaping can improve the performance of these positioners, and this was documented in paper 98590D [9859-11].

- Jeongsik Shin, Senior Research Scientist at the University of Texas at Arlington Research Institute (United States), who presented his work on design requirements for Adaptive Robotic Nurse Assistants (ARNA), a next-generation robot that will be able to assist nurses and patients with mundane tasks, such as taking vital signs, fetching objects, and rehabilitation exercises. Paper 98590E [9859-12] focused on robot hardware, software, and sensor requirements to fulfill the roles of patient sitter and patient walker.
- Micky Rakotondrabe of FEMTO-ST Institute in Besancon, France, presented the work of his colleagues on design modeling and simulation of three layers piezoelectric cantilevers. Advanced cantilever structures contain two actuation layers utilizing PZT laminates and one sensing layer utilizing PVDF. As a result, the structure can be controlled using feedback with a sensor co-located with the actuator, possibly replacing large, external optical or capacitive transducers. This work was documented in paper 98590F [9859-13].
- Professor Abdenby Mohand Ousaid of FEMTO-ST Institute in Besancon, France, presented the work of his colleagues aimed at creating the next force sensing technology for robots. The novel multi-axis force sensor uses piezoelectric resonance as a transducer, and it is intended to replace commonly used strain-gauge sensors currently used in robot end-effectors. This work was documented in paper 98590H [9859-17].
- Professor Cindy Harnett from the University of Louisville (United States), who presented her pioneering work in creating flexible circuits for shape sensing, which are manufactured by “weaving” them into electronic fabrics. Applications include smart garments for next-generation flexible or soft robots and digital actuation systems that exploit bi-stable microstructures. Her work was documented in paper 98590I [9859-18].
- Oguz Yetkin, a graduate student at the University of Texas at Arlington (United States), who presented his work on a novel fingernail optical sensor to detect “pinch” gestures and drive prosthetic devices from an amputee’s sound hand. Paper 98590J [9859-19] detailed experimental results to classify eight different pinch gestures with users evaluating the system.

We hope that readers find our 2016 conference proceedings interesting and will join us at next year’s edition of the conference.

Dan Popa
Muthu B. J. Wijesundara