

Bibliography

- Adam, J.-L. and X. Zhang, Eds., *Chalcogenide Glasses: Preparation, Properties and Applications*, Woodhead Publishing, Cambridge, UK (2014).
- ASME Y14.5-2009, *Dimensioning and Tolerancing*, American Society of Mechanical Engineers, New York (2009).
- Bansal, N. P. and R. H. Doremus, *Handbook of Glass Properties*, Academic Press, Orlando (1986).
- Baumer, S., *Handbook of Plastic Optics*, Wiley-VCH, Weinheim (2005).
- Braunecker, B., R. Hentschel, and H. J. Tiziani, *Advanced Optics Using Aspherical Elements*, SPIE Press, Bellingham, Washington (2008) [doi: 10.1117/3.741689].
- Brinksmeier, E., O. Riemer, and R. Gläbe, *Fabrication of Complex Optical Components*, Springer, New York (2013).
- Foster, L. W., *Geo-Metrics III: The Application of Geometric Dimensioning and Tolerancing Techniques*, Addison Wesley, Reading (1994).
- Hartmann, P., *Optical Glass*, SPIE Press, Bellingham, Washington (2014) [doi: 10.1117/3.1002595].
- Hilton, A. R., *Chalcogenide Glasses for Infrared Optics*, McGraw Hill, New York (2010).
- ISO 10110, *Optics and Optical Instruments – preparation of drawings for optical elements and systems – part 1-12*, International Organization for Standardization, Geneva (2010).
- ISO 1101:2013, *Geometrical product specifications (GPS) – Geometrical tolerancing – Tolerances of form, orientation, location and run-out*, International Organization for Standardization, Geneva (2013).
- Kimmel, K. and R. E. Parks, *ISO 10110 Optics and Optical Instruments – A User's Guide*, 2nd Edition, OSA, Washington, D.C. (2002).

Bibliography

MIL-PRF-13830B, *Performance Specification – Optical Components for Fire Control Instruments; General Specification governing the manufacture, assembly and inspection of*, U.S Army Armament Research, Development and Engineering Center (ARDEC) (1997).

REACH, *Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)*, Regulation (EC) No. 1907/2006, European Chemicals Agency (2006).

RoHS Directive, *Restriction of Hazardous Substances Directive*, 2002/95/EC, European Union (2002).

RoHS 2 Directive, *Restriction of Hazardous Substances Directive*, 2011/65/EU, European Union (2011).

Schaub, M. P., *The Design of Plastic Optical Systems*, SPIE Press, Bellingham, Washington (2009) [doi: 10.1117/3.796330].

Schaub, M. P., J. Schwiegerling, E. C. Fest, A. Symmons, and R. H. Shepard, *Molded Optics: Design and Manufacture*, CRC Press, Taylor and Francis Group, London (2011).

Scherer, G. W., *Relaxation in Glass and Composites*, Wiley-Interscience, New York (1986).

Schwiegerling, J., *Optical Specification, Fabrication, and Testing*, SPIE Press, Bellingham, Washington (2015) [doi: 10.1117/3.796330].

Shelby, J. E., *Introduction to Glass Science and Technology*, 2nd Edition, The Royal Society of Chemistry, London (2005).

Tkaczyk, T., “Miniature Optics for Diode Lasers and Beam Shaping,” SPIE Short Course, SC012, Bellingham, Washington (2013).

U.S. Precision Lens, *The Handbook of Plastic Optics*, 2nd Edition, U.S. Precision Lens, Cincinnati (1983).

Whitehouse, D., *Surfaces and Their Measurement*, Kogan Page Science, Taylor Hobson Ltd., London, Sterling, Virginia (2002).

Index

- 3D printing, 123
 45-deg grinding, 82

 Abbe diagram, 9, 23, 124
 Abbe number, 8, 9, 20, 28, 144
 absorption, 11, 28
 achromatization, 104
 additive manufacturing, 123
 amorphous carbon, 59
 annealing coefficients, 20, 46, 48
 annealing point, 14
 annealing range, 14
 annealing rate, 8, 42, 45–48
 antireflection coating, 113, 117, 118
 apertures, 109
 array molding, 60
 aspect ratios, 60, 91, 145
 aspheres, 6, 97
 aspheric equation, 6, 94, 144
 aspheric metrology, 84
 aspheric surface, 6, 78, 84, 126, 144–145
 aspherical lens, 32
 assembly, 109, 126
 athermalization, 18, 26, 105, 132

B axis, 80, 82
 backing plate, 67
 baffles, 109
 ball preforms, 39–40
 bandpass coatings, 118
 bi-concave shape, 89
 bi-convex shape, 89
 birefringence, 10, 21–22, 61, 90
 blank, 124
 blank molding, 1, 15, 34
 blend radius, 81, 88, 91–92
 bosses, 109

 camcorders, 131
 camera lenses, 131–132
 carbide molds, 75, 86
 cast plastic optics, 1
 casting, 36
 cavitation, 53, 71
 cavity plate, 67
 cavity sets, 67–68, 71, 72, 124
 cellphone camera lenses, 132
 center thickness, 35, 56, 88, 90–91, 101, 126, 130
 centering feature, 99
 centration, 107
 ceramic tooling, 58
 chalcogenide glasses, 2, 3, 11, 16–18, 29, 47, 132, 142
 chalcogenide molding, 51
 chamfer callouts, 113
 clamping capacity, 71
 clear aperture, 10, 88, 91, 93, 103
 coating interactions, 59
 coefficient of thermal expansion, 14, 26
 compensation iterations, 78

Index

- component-specific tooling, 51
- compression molding, 36
- computerized numeric control, 79
- condenser lens, 35, 128
- conductive coatings, 118
- conic equation, 6
- conic surface, 6
- contact profilometer, 127
- control system, 51
- cooling channels, 67
- cooling time, 63
- copper nickel, 70
- core plate, 67
- corner radius, 88, 92
- cost-critical mold life, 62
- critical thickness, 102
- cross-axis grinding, 81
- crown glass, 9
- CTE mismatch, 61
- cycle time, 73

- d-line, 7
- decentration, 107
- deflection temperature, 118
- degating, 100
- deposition temperature, 118
- depth of focus, 129
- deterministic process, 58
- dew point, 63
- diametral clearances, 119
- diamond turning, 18, 36, 57, 70, 124
- diamond turning machine, 70, 79
- dicing, 113, 120
- differential thermal expansion, 86
- diffractive efficiency, 85
- diffractive elements, 106
- diffractive height, 85, 146
- diffractive optical elements, 85
- diffractive power, 105
- diffractive surface, 32, 85, 97, 104–105
- dilatometric glass transition temperature, 14
- dilatometric softening point, 14
- dilatometry, 14, 43
- dimensional control, 40
- diode collimation, 113, 129
- disc preforms, 39, 54
- dispersion, 8–9, 20, 23, 30, 45–47, 104, 132, 147
- divergence, 129
- dn/dT , 26, 105
- draft, 99
- draft angles, 116
- draft zones, 116
- drawings, 110, 126

- edge blackening, 113
- edge break, 103
- edge chipping, 120
- edge radius, 88, 92, 113
- edge relief, 103
- edge thickness, 88, 90–91, 102, 145
- edging, 120
- effective diameter, 88, 91
- effective focal length, 130, 146

Index

- ejection, 63
- ejection mechanism, 67
- ejection pin mark, 116
- electroless nickel-plated
 - stainless steel, 76
- embossing, 36
- environmental
 - regulations, 29, 30
- f* /#, 147
- family molds, 72, 125
- fiber coupling, 130
- filters, 109
- fine annealing, 45
- finite element analysis, 44, 77
- fixed-die configuration, 49
- flange, 68, 88, 91–92, 98, 102, 109, 113, 125, 127
- flat, 88, 92
- flatness, 111
- flint glass, 9
- flow line, 101
- Forbes asphere, 147
- free molding, 56
- freeform surfaces, 32
- Fresnel lenses, 24
- Fresnel losses, 11
- frictional behavior, 44
- fused silica, 59
- gas entrapment, 54
- gas transfer system, 51
- gate, 10, 63, 68, 100, 102, 127
- gate flat, 100, 116
- gate vestige, 100, 116
- gate/runner
 - configurations, 125
- geometrical dimensioning
 - and tolerancing, 111
- glass code, 7, 20
- glass datasheets, 11, 19, 43, 46
- glass map, 9
- glass molding, 1, 3, 15, 35, 76, 128
- glass preform, 37
- glass replication, 1, 33, 60
- glass transition
 - temperature, 16
- glass type, 20
- glass viscosity, 15, 42, 43
- gob preform, 39, 41
- grating equation, 85
- grind and polish
 - manufacturing, 5, 35
- grinding, 113
- hand molding, 34
- hardened steel, 70
- heat expansion, 14, 20
- heater bands, 65
- heating stations, 52
- heating system, 51
- high dispersion, 22
- high stress birefringence, 90
- high-NA lenses, 128
- high-reflectance coatings, 118
- high- T_g glass, 59
- hopper, 63, 65
- hybrid surface, 85
- hyperspectral
 - chalcogenides, 11

Index

- image quality, 119
 imaging systems, 109
 index drop, 7, 42, 45–48,
 147
 index of refraction, 7–9,
 20, 30, 42, 45–48, 57,
 90
 index tolerance, 48
 inert environment, 54, 59
 infrared optical systems,
 131
 infrared transmission, 24
 injection, 63
 injection molding, 1, 10,
 36, 63, 106, 116
 injection molding
 machines, 65
 injection screws, 63, 65
 injection system, 65
 injection-compression
 molding, 62
 injection-molded plastic
 optics, 2–3, 38
 ink stamping, 106
 inking, 116
 inline tooling
 configuration, 49
 insert, 61, 68
 insert material, 61
 insert precision glass
 molding, 61, 96, 130
 insertion, 119
 interface diameter, 96
 interferences, 119
 internal transmission, 11,
 20
 irregularity, PV or RMS
 147
 ISO 10110, 110, 113, 115,
 148
 laser diodes, 129
 lens baffle, 109
 lens slope, 94
 linear polarizers, 10
 liquidus, 14
 Littleton softening point,
 14
 low dispersion, 22
 low-NA lenses, 129

 master mold, 32
 material color, 31
 material grade, 31
 material manufacturer, 31
 material selection, 27, 30,
 49, 59, 86, 134, 142
 material specifications, 31,
 113, 116
 melt-spun aluminum, 76
 meniscus shape, 89
 micro-grinding, 80
 minimum cross-sectional
 thickness, 102
 modulation transfer
 function, 127
 mold cavitation, 52, 53, 71
 mold coatings, 16, 44, 59,
 83
 mold compensation, 77, 84,
 95
 mold life, 62
 mold materials, 16
 mold processing, 72, 73,
 100, 125
 mold setting station, 52

Index

- 86
- molded plastic mirrors, 118
- molded plastic optics, 1
- molding vendors, 121
- molding-induced
 - birefringence, 10
- mounting, 98

- near-net-shaped preforms, 39
- no draft zone, 99
- nonlinear shrinkage, 78
- nonvolumetric molding, 39, 55–56, 120
- numerical aperture, 129, 147

- off-axis machining, 60
- opaque annuli, 106
- optic insertion tool, 126
- optic pin, 68, 70, 78
- optical coatings, 108
- optical mold pins, 79
- optical plastics, 11, 21–24, 28, 104
- optical scattering, 12
- optical surface, 75, 78
- optical testing criteria, 113
- optomechanical design, 90
- orientation features, 109
- outside diameter, 88, 90–91
- oxidation, 54, 95

- pad printing, 116, 119
- partial dispersions, 8, 20
- parting line, 65, 67

- passive athermalization, 132
- pellet, 63
- PGM mold designs, 77
- PGM simulation, 44
- physical aperture, 88, 93
- pixels per detector, 133
- plano-concave shape, 89
- plano-convex shape, 89
- plastic molded optics, 1
- plastic optic materials, 12, 21–23, 25
- plastic optic molders, 25
- plastic optics, 75
- plastic shrinkage, 78
- platens, 65
- post-annealing, 45
- post-processing, 120
- precision diamond
 - grinding, 81
- preforms, 39, 90
- principal dispersion, 8
- profile scans, 127
- progressive molding, 52
- prototype machining, 124
- prototype molding, 125
- prototypes, 122
- pull-ahead tool, 71

- quartz, 59

- REACH, 29
- refractivity, 8
- reheat molding, 34
- relative partial dispersion ratio, 8, 147
- relative partial dispersions, 20
- reprocessed material, 31

Index

- Restrictions on Hazardous Substances, 29, 57–58, 113
- rounded features, 98
- runners, 67
- sag depth, 93
- sag diameter, 88, 93
- sag height, 93
- scratch resistance, 118
- secondary operations, 74, 100, 108, 119–120
- sensitivity studies, 73
- service temperature, 26
- sharp features, 98
- shear deformation, 15
- shrinkage, 60, 77, 78, 86, 103
- side holes, 69
- silicon carbide, 75
- silicon nitride, 75
- single-axis machine, 38
- single-point diamond turning, 38, 79
- slides, 69
- slump molding, 34
- snap features, 69
- solidus, 14
- specific heat capacity, 13
- spherical preforms, 40
- split radius tools, 85
- statistical process control, 116, 127
- stick grinding wheel, 82
- stitching, 84, 94
- stock molds, 125
- straight draw molds, 69
- strain point, 14
- stray light, 116–117, 119–120, 127
- stray light analysis, 106
- stress relaxation, 44
- structural relaxation, 44
- surface finish, 116
- surface profilometer, 84, 94
- surface quality, 40
- surface roughness, 60
- tangent transition zone, 94
- taper interlocks, 67
- thermal conductivity, 13
- thermal cycling, 61
- thermal diffusivity, 13
- thermal history, 7
- thermal imaging, 132
- thermal mismatch, 59
- thermal properties, 13, 19, 20, 26, 42–43
- thermal shock, 86
- thermal shrinkage, 77
- threads, 69
- tilted vertical grinding, 82
- tolerances, 40, 73, 107–108, 123, 128
- tool blend radius, 81
- total indicated runout, 111
- transfer molding, 49, 52–53
- transfer molding machine, 38
- transition radii, 106
- transition zones, 93, 103
- transmission, 12, 22, 30, 117, 132
- tungsten carbide, 75

Index

- ultraprecision grinding,
 - 58, 80
- ultraviolet light, 122
- ultraviolet-curable
 - polymer, 32
- undercuts, 69
- uniform flow front, 101

- vacuum molding, 39, 51,
 - 54, 94
- vents, 68
- vertical grinding, 80–82
- very low- T_g glasses, 57
- vestige, 100
- viscoelastic behavior, 44
- VLT glass molding, 75
- volumetric molding, 55,
 - 61, 92, 96
- volumetric relief
 - points, 55

- wafer-level cameras, 33
- wafer-level glass
 - replication, 33
- wafer-level molding, 39,
 - 51, 60
- wafer-level optics, 32–33,
 - 60
- wafer-level precision glass
 - molding, 60
- wavelength cutoff, 12
- wavelength dispersion,
 - 132
- wavelength of light, 7
- welding, 119
- wheel-normal grinding, 80,
 - 82

- yield factor, 74

- zoom configuration, 105



Alan Symmons is the Executive Vice President of Operations at LightPath Technologies, a worldwide leader in precision glass molding (NASDAQ: LPTH). He previously held the titles of Vice President of Corporate Engineering and Director of Engineering. Prior to joining LightPath in 2006, he was Engineering Manager at Aurora Optical, a cellphone camera module manufacturer, and held various engineering positions in injection-molded plastic optics at both Applied Image Group – Optics and Donnelly Optics.

Alan has 20 years of experience in molded optics with over a dozen published papers in the field. He is a Senior Member of SPIE and OSA, a member of ASPE, and is active in the Florida Photonics Cluster. Alan has a B.S. in mechanical engineering from Rensselaer Polytechnic Institute and an MBA from the Eller School of Management at the University of Arizona.



Michael Schaub is a Senior Principal Optical Engineer at Raytheon Missile Systems. In addition, he is the founder of Schaub Optical LLC, an optical design and engineering consulting firm. Prior to joining Raytheon, he worked at Donnelly Optics, where he designed and developed multiple high-volume plastic optic designs.

Mike has over 20 years of experience in plastic optics, with two books and several papers published. He is a member of SPIE and OSA. He has a B.S. in optics from the Institute of Optics at the University of Rochester, an M.Sc. in engineering science from the University of Oxford, and an M.S. and Ph.D. in optical sciences from the Optical Sciences Center at the University of Arizona.