Index

3D interference lithography, 231
3D lithography, 223
3D mask effects, *see* mask topography effects
3D microprinting, 232
5-bar test, 259

A

Abbe method, 24, 33 Abbe-Rayleigh criteria, 35, 129, 218 aberration astigmatism, 254, 257, 263 coma, 254, 257, 263 measurement, 264 power, 254, 257 spherical, 254, 262, 263 trefoil, 254, 263, 263 absorbance modulation optical lithography (AMOL), 227 address grid, 215 Airy disk, 37 alternating PSM, see phase shift mask, alternating AltPSM, see phase shift mask, alternating AMOL, see absorbance modulation optical lithography annular illumination, see illumination annular antireflective coating, 286 Arrhenius dependency, 63 assist features, 96, 302, 308

assist lines, *see* assist features astigmatism aberration, 254 attenuated PSM, *see* phase shift mask, attenuated AttPSM, *see* phase shift mask, attenuated

B

bananicity, 261 bandwidth, see illumination bandwidth BARC, see bottom antireflective coating best focus shift, 303 BEUV, see beyond EUV lithography beyond EUV lithography, 180 black border effect, 168 bleaching, 52, 130, 135 block copolymer, 142 Bossung curves, 16 bottom antireflective coating (BARC), 61, 286, 312 bottom-up nanofabrication, 3 boundary layer model, 311 box-in-box test, 259 Bragg's law, 162 Brewster angle, 274 bull's eye illumination, see bump defect, 176

С

capping layer, 163

CAR, see chemically amplified resist CARL, see chemically amplified resist lines CD, see critical dimension (CD) CD uniformity (CDU), 13 CEL, see contrast enhancement laver chalcogenide glasses, 51 chemical contrast, see contrast chemical chemical noise, 328 chemically amplified resist (CAR), 49, 51, 53, 64 chemically amplified resist lines (CARL), 149 chemoepitaxy, 144 chief ray angle at the object (CRAO), 170 chromeless phase shift lithography (CPL), see phase shift mask, chromeless chromeless PSM, see phase shift mask, chromeless circular illumination, see illumination, circular coarse-grained models, 146, 332 coherence, 32, 210 spatial, 32, 88, 202, 207 temporal, 32 coma aberration, 254 compact model, 102 compact resist model, 71 contact hole arrays, 90 contact printing, 198 contrast chemical, 9, 63 enhancement layer (CEL), 135 fading, 306 image, 9 photoresist, 54 conventional illumination, see illumination, conventional

CPL, *see* phase shift mask, chromeless CQuad illumination, 13, *see* illumination, CQuad CRAO, *see* chief ray angle at the object critical dimension (CD), 8, 12 critical ionization model, 68, 332 cross linking, 50 cross section, 9 cutlines, 15

D

dark field imaging, 94 deep-ultraviolet (DUV) lithography, 41 defocus, 7, 13, 15, 27, 40 degree of polarization (DoP), 270 demagnification, 4 deprotection, 53, 64 depth of focus (DoF), 17, 39 DESIRE, see diffusion enhanced sylilated resist development puddle, 58 spray, 58 diazonaphthoquinone (DNQ) photoresist, 49, 51, 62 diffraction, 25 angle, 28, 36 efficiency, 27, 270, 296 equation, 36, 90 Fraunhofer, 26 Fresnel, 26 limitation, 13, 28, 252 limited imaging, see diffraction limitation order, 7, 35, 271, 296 spectrum, 27-28, 30 diffractive optical element (DOE), 208 diffusion coefficient, 62

length, 63 diffusion enhanced sylilated resist (DESIRE), 148 digital mirror display (DMD), 217, 229 Dill model, 58 dipole illumination, see illumination, dipole directed self-assembly (DSA), 142 discharge-produced plasma (DPP) source, 159 dissolution inhibitor, 51 DMD, see digital mirror display, see digital mirror display DNQ photoresist, 49, 51, 62 DOE, see diffractive optical element domain-decomposition technique (DDT), 311 DoP, see degree of polarization dose latitude, 17 dose-to-clear, 55 double exposure, 133 double patterning, 137 DPP source, see discharge-produced plasma source DSA, see directed self-assembly DTD, see dual-tone development dual-tone development (DTD), 140 DUV lithography, see deepultraviolet (DUV) lithography dyed photoresist, 62

E

e-beam lithography, 236 edge placement error, 15 electromagnetic field simulation, 287–288 EMF simulation, *see* electromagnetic field simulation EPE, *see* edge placement error EUV lithography, *see* extremeultraviolet lithography evanescent order, 36 wave, 36, 137, 213, 219, 296 excimer laser ArF, 42 F₂, 42 KrF, 42 exposure, 11, 48 exposure slit, 171 extreme-ultraviolet (EUV) lithography, 157 high-NA, 180 light sources, 159 mask, 164 mask defects, 175 mask shadowing, 165 resist, 173

F

fast marching method, 69 FDTD, see finite-difference time-domain method FEM, see finite element method Fickian diffusion, 62 finite element method, 288 finite integral technique, 288 finite-difference time-domain (FDTD) method, 288, 289 FIT, see finite integral technique flare, 172, 265 FLEX, see focus latitude enhancement exposure flood exposure, 55 Flory-Huggins parameter, 143 FMM, see Fourier modal method focus drilling, 121, 280 focus latitude, 17 focus latitude enhancement exposure (FLEX), 121, 280 footprint, 8, 13-15, 304 Fourier modal method (FMM), 292 Fourier optics, 44 fraction of polarization, 297

fragmentation, 99 Fraunhofer diffraction, 26 free-form illumination, 93 Fresnel diffraction, 26, 198 equations, 274 zone, 198

G

g-line, 201 Gillespie algorithm, 333 graphoepitaxy, 144 grating equation, 90, 296 grayscale lithography, 70, 229 graytone lithography, *see* grayscale lithography grazing incidence mirrors, 162 guiding pattern, 144

Η

h-line, 201 hammerhad, 97 hardmask, 137 HEBS, see high-energybeamsensitive glass Helmholtz equation, 25, 293 high-energy-beam-sensitive (HEBS) glass, 230 holographic lithography, 208 Hopkins approach, 30, 300 imaging equations, 34 method, 34 Hopkins assumption, see Hopkins approach horizontal line-space patterns, 165 hotspot, 101 HSQ, see hydrogen silsesquioxane photoresist Huygens-Fresnel principle, 26 hybrid lithography, 211 hydrogen silsesquioxane (HSQ) photoresist, 50

I

i-line, 201 IDEAL, see innovative double exposure by advanced lithography illumination annular, 89 bandwidth, 32, 172, 280 bull's eye, 88 circular, 88 conventional, 88 CQuad, 88 dipole, 88 free-form, 93 off-axis. 87 quadrupole, 89 system, 6 ILT, see inverse lithography technology, see inverse lithography technology image aerial, 7 bulk, 7 field, 4, 23 formation, 24 imbalancing, 302 image contrast, see contrast image immersion lithography, 7 inhibitor, see dissolution inhibitor innovative double exposure by advanced lithography (IDEAL), 121 intensity imbalancing, 300 interference lithography (technology), 209 interferometric lithography, see interference lithography intermediate state two-photon (ISTP) materials, 134 inverse lithography technology (ILT), 95, 100, 116 iso-dense bias, 95

ISTP, *see* intermediate state two-photon materials

J

Jones pupil, 170, 277

K

Kirchhoff approach, 24, 295, 303 boundary condition, 26, 285 Köhler illumination, 31, 169, 199 integrator, 202 Kramers–Kronig relation, 130

L

Lambert-Beer law, 59 laser direct write lithography (LDWL), 213 laser direct write material processing (LDWP), 213 laser-produced plasma (LPP) source, 159 LCD, see liquid crystal display, see liquid crystal display LDWL, see laser direct write lithography LDWP, see laser direct write material processing LELE, see litho-etch-litho-etch lensless EUV lithography, 206 LER, see line edge roughness level-set algorithm, 118 LFLE, see litho-freeze-litho-etch light-emitting diode, 203 light-induced refractive index change, 130 line edge roughness (LER), 145, 328 line width roughness (LWR), 328 line-end shortening, 97 line-space pattern, 9, 15, 296 liquid crystal display (LCD), 217, 229

litho-cure-litho-etch (LCLE), see litho-freeze-litho-etch litho-etch-litho-etch (LELE), 137 litho-freeze-litho-etch (LFLE), 138 litho-litho-etch (LLE), see litho-freeze-litho-etch Littrow mounting, 90 LPP source, see laser-produced plasma source lumped parameter model, 56 LWR, see line width roughness

M

Mack development model, 66 mandrel, 140 mask. 6 aligner, 198 defect, 14, 304 diffraction analysis, 296 mask 3D effects, see mask topography effects mask diffraction spectrum, see diffraction spectrum mask error enhancement factor (MEEF), 18, 184 mask topography effects, 168, 286-287, 295, 300, 305 mask-induced aberration, 298–299, 303 - 304mask-induced best focus shift, 303-304, 307 mask-induced phase effects, 298 maskless lithography, 211, 217 Maxwell's equations, 287 MEEF, see mask error enhancement factor mercury lamp, 41, 201 Mo/Si multilayer, see molybdenum/ silicon multilayer model-based OPC, 94, 99 molecular dynamical models, 146 molecular photoresist models, 332

molybdenum/silicon (Mo/Si) multilayer, 163 multi-objective optimization, 118 multicolor lithography, 228 multilayer coating, 161 defect, 176 multiple exposure, 120, 133 multiple patterning, 137

Ν

NA, see numerical aperture nanosphere lithography, 221 near-field lithography, 219 negative index superlens, 222 negative tone photoresist, 75 NILS, see normalized image log slope NOK, see not OK metric for stochastic printing failures non-Fickian diffusion, 65 non-telecentricity, 171 normalized image log slope (NILS), 9, 40, 56 not OK metric for stochastic printing failures, 331 numerical aperture (NA), 7, 27-28, 42

0

off-axis illumination, 31, 87 OOB, *see* out-of-band radiation OPC, *see* optical proximity correction OPD, *see* optical path difference OPE, *see* optical proximity effect optical nonlinearity, 130, 223 optical path difference (OPD), 39, 106 optical proximity correction, 94 optical proximity effect, 13, 43, 302 optical proximity effect (OPE) curves, 18 optical threshold materials, 134 organically modified ceramic microresist (ORMOCER), 235 ORMOCER, *see* organically modified ceramic microresist out-of-band (OOB) radiation, 159, 172 outgassing, 175 overlay, 13, 141, 257

P

PAG, see photoacid generator pattern integrated interference lithography, 212 pattern multiplication, 145 pattern rectification, 145 PEB, see post-exposure bake pellicle, 6, 114, 168 percolation model, 68 phase conflicts, 106 phase shift mask alternating, 103 attenuated, 110 chromeless, 108 strong, 108 phase shift mask (PSM), 103 phase shift mask, alternating, 185 phase shift mask, attenuated, 185 photoacid, 53, 64 photoacid generator (PAG), 53, 59 photoactive component (PAC), 52 photobase generator, 77 photodoping, 51 photoisomerization, 50 photomask, see mask photon noise, 325 photoresist, 6 classification, 48 contrast, 55 contrast curve, 54 development, 66 polarity, 49 shrinkage, 78

tonality, 48, 75 photosensitivity, 59 pit defect, 176 pitch, 9, 15 pitch walking, 140 pixelated mask, 116, 230 placement error, 261 PMMA (polymethylmethacrylate) photoresist, 50 Poisson distribution, 326 polarization effects, 270, 298 illumination, 279 polymerization, 50 post-exposure bake (PEB), 11, 57, 62 power aberration, 254, 257 power spectral density (PSD), 255, 267, 330 pre-bake, 10, 57 pre-pulse technology, 160 process flow, 10 linearity, 18 variation (PV) band, 13 window, 17 programmable mask, 217 projection imaging, 23 lens, 7 scanner, 4, 23 stepper, 4 system, 7, 42 propagating waves, 219 proximity effect, see proximity effect proximity gap, 199 proximity printing, 198 **PS-***b***-PMMA**, 144 PSD, *see* power spectral density pseudo-spectral time-domain (PSTD), 288 PSM, see phase shift mask

pupil filter, 113 pupil function, 28, 252 PV band, *see* process variation band

Q

quadrupole illumination, 89 quantum imaging, 226 quencher, 59, 64

R

raster scan, 215 ray tracing, 23 Rayleigh criteria, see Abbe-Rayleigh criteria RCEL, see reversible contrast enhancement layer RCWA, see rigorous coupled wave analysis reduction, see demagnification reflective notching, 313 resolution, 2, 35, 47, 200, 210, 215, 218, 336 reversible contrast enhancement layer (RCEL), 135, 228 rigorous coupled wave analysis (RCWA), 292 rigorous EMF modeling, 296 RLS trade-off, 336 roadrunner resist model, 72 rule based OPC, 94, 98

S

SADP, see self-aligned double patterning
scanning electron microscopy (SEM), 12
Schwarzschild optics, 169
SDDP, see spacer-defined double patterning
self-aligned double patterning (SADP), 139
serif, 97

shadowing effect, see extremeultraviolet lithography mask shadowing shrinkage, see photoresist shrinkage sidelobe, 113, 260 sidewall angle, 12 SLA, see stereolithography apparatus SMO, see source mask optimization Snell's law, 274 SOCS, see sum of coherent systems decomposition soft X-ray radiation, 157 solid immersion lithography, 220 source maps, 93 source mask optimization, 31, 115 spacer-defined double patterning (SDDP), 139 spatial coherence, see coherence spatial frequency, 27, 330 spherical aberration, 254, 303 spin coating, 57 SPP, see surface plasmon polaritons standing-wave pattern, 60 STED, see stimulated emission depletion STED inspired lithography, 226, 235 STED microscopy, 226 stereolithography, 232 stereolithography apparatus, 232 stimulated emission depletion, 226stochastic printing failures, 331 stray light, 265 SU-8 photoresist, 50 subresolution assist features, see assist features sum of coherent systems (SOCS), 34 surface plasmon polaritons (SPP), 219swing effects, 61

Т

Talbot displacement lithography, 207 distance, 206 effect, 206 images, 206 TARC, see top antireflective coating TE polarization, 270, 288–289 technology factor k_1 , 38, 43 telecentricity error, 88, 171, 306 thin film imaging, 148 thin mask, 24 threshold, 8 threshold model, 8, 71 threshold-to-size (THRS), 9 TIS, see total integrated scatter TM polarization, 270, 288–289 tonality, see photoresist tonality top antireflective coating (TARC), 62 top-down nanofabrication, 3 top-surface imaging, 148 total integrated scatter (TIS), 267 TPA, see two-photon absorption, see two-photon absorption TPP, see two-photon polymerization transfer matrix method, 274, 293 transmission cross coefficients (TCC), 34 trefoil aberration, 254, 263 trim exposure, 107, 211 trim mask, 107 TSI, see top-surface imaging two-photon absorption (TPA), 133, 223 two-photon polymerization, 233

U

underlayer, 175

V

variable threshold model, 71 vector scan, 215 vertical line-space patterns, 165

W

wafer topography effects, 287, 312 wafer track, 58 wave aberration, 251, 304 vector, 26 wavefront tilt, 256 waveguide method, 292 order, 293 Weiss rate model, 68 Wolff rearrangement, 51

Х

X-ray proximity lithography, 203–204

Ζ

Zernike polynomial, 252



Andreas Erdmann is the head of the Fraunhofer IISB Computational Lithography and Optics group and teaches as "Privatdozent" at the University of Erlangen. He has more than 25 years of experience in optical and EUV lithography. He chaired SPIE conferences on Optical Microlithography and Optical Design, and is an organizer of the International Fraunhofer Lithography Simulation Workshop. He contributed to the development of several

advanced lithography simulators, including the development and research lithography simulator Dr.LiTHO. He is Fellow of SPIE.