

Index

A

- aberration. *See* lenses.
- acquisition, 547, 908
- add drop, 147, 149, 193
- additive white Gaussian noise (AWGN), 564
- adjacent channel, 137, 140, 402, 688, 691
- ALC. *See* control loops.
- algorithms, 8, 34, 524, 650, 672, 681, 698, 699, 732, 946, 950
 - decision directed, 698, 731, 732
 - least mean square (LMS), 696, 697, 698, 699
 - maximum likelihood, 682, 701
 - Viterbi, 682
 - zero forcing, 696
- AM to AM polynomial, 371, 397, 765
- amplitude modulation (AM), 562
 - noise, 293, 294, 296, 297
 - residual, 517, 519, 525, 650, 651, 663
 - vestigial side band (VSB), 561, 808, 835, 854
- amplifiers
 - bias class, 493
 - distributed, 209, 219, 472, 473, 478, 509, 999
 - feedback, 209, 255, 261, 464, 467, 468, 469, 470, 535, 755
 - load line, 492, 493
 - matching, 994
 - noise figure, 478, 508, 556, 560
 - operational, 450, 477, 479, 518, 594, 904
 - PIN TIA, 49, 479, 920
 - push pull, 41, 336, 494, 760, 764, 765, 768, 769
- analog baseband (ABB), 569, 587, 726
- analog-to-digital converter (ADC), 587, 726, 730, 739, 742–743
- analog-to-digital converter (ADC) error function, 726
- analog-to-digital converter (ADC) NTF, 736
- analog-to-digital
 - quantization noise, 719, 733
- analog return path, 44, 45, 46, 192, 413
 - return path receiver, 43, 44, 46
 - return path transmitter, 13, 44, 45, 46, 246
- application specific integrated circuit (ASIC), 20, 48
- architectures, 8, 17, 31, 53, 132, 789
- arrayed waveguide gratings (AWG), 8, 142, 143, 146, 172
- audio
 - AC2
 - AC3, 80, 90, 111
 - aural, 57
- automatic current control (ACC). *See* control loops.
- automatic gain control (AGC). *See* control loops.
- automatic offset control, 936
- automatic power control (APC). *See* control loops.
- avalanche photo detector (APD). *See* photo detectors.

B

- back facet monitor, 592, 622, 781, 948, 950, 953, 955, 961, 963, 973
- back off power, 568

- balanced bridge interferometer, 301, 743
 - band gap reference, 496
 - band pass filter, 696
 - back-to-back diodes linearizer, 787
 - Barkhausen criterion
 - base-band (BB), 567
 - bias methods
 - bias class, 493
 - current control loop, 495, 622, 623, 624
 - current starving, 495, 510
 - gate bias, 496
 - load line, 492, 493
 - stack bias, 494, 495
 - birefringent crystal, 173
 - bit error rate (BER), 290, 654, 656, 659, 723, 819, 829, 837, 847, 886, 887, 890, 896, 905, 920
 - on-off keying bit error rate (OOK BER)
 - probability of error, 643, 654, 655, 656, 657, 721, 886, 887, 888, 932, 933, 934, 939
 - quadrature amplitude modulation (QAM), 629, 632, 633, 654, 662, 683, 685, 686, 699, 710, 712, 716, 724, 738, 740, 839, 845, 855
 - blanking signal. *See* composite video or TV.
 - blind equalizer. *See* equalizers.
 - Bode fano limit, 485
 - Bode plots, 499, 536, 611
 - dominant pole, 534, 550
 - gain margin, 479, 524, 534, 535, 599, 923
 - phase margin, 534, 535
 - poles, 535, 537, 538, 547, 584, 696, 1030
 - zeros, 154, 667, 693, 908, 912
 - bulk optics, 179, 180, 188, 189, 192, 201, 203, 204, 205
 - bidirectional (BiDi), 50, 51, 182, 184, 185, 187
 - diplexer, 5
 - full service access network (FSAN)
 - wavelengths, 189, 192
 - optical dual port (ODP), 164, 407
 - optical trap, 190, 191, 192, 205
 - optical triple port (OTP), 164, 407
 - tracking error, 179, 187, 188, 200, 201, 205
 - triplexer, 51, 183, 188, 190, 198, 201
 - Bragg grating, 118, 148, 149, 155, 173, 967
 - fiber, 118, 149, 173, 956
 - filters, 137
 - Bragg wavelength, 150, 157, 159
 - brick wall filter. *See* filters.
 - burst mode transceiver, 927–965
 - burst mode, 927–965
 - burst mode AGC, 946–953
 - burst mode tester, 945
 - loud soft ratio, 982
 - burst noise, 840
 - bursty nonlinear distortions (NLD), 806, 838
 - butterfly, 685
- ## C
- cable
 - coax, 39–43, 42
 - coax loss, 386
 - fiber bundle, 32
 - capacitance, junction capacitance, 247, 327
 - carrier recovery, 711, 722
 - clock data recovery (CDR), 913, 915, 916, 917, 918, 920, 922, 923, 928, 929, 934, 955, 981
 - costas loop, 711, 712, 713, 741, 912
 - phase locked loop (PLL), 715, 717, 721, 912, 913, 914, 916, 923
 - carrier-to-noise ratio (CNR), 12, 41, 98, 99, 101, 290, 384, 386, 413, 414, 415, 416, 420, 421, 422, 423, 424, 425, 449, 555, 560, 719, 720, 845, 846, 867
 - dark CNR, 557, 1022, 1024, 1038, 1039
 - E_b/N_0 vs. CNR
 - noise factor (NF), 382, 384, 553
 - P1dB, 397
 - quantum limit, 295, 423, 888
 - relative intensity noise (RIN), 293, 294, 295, 296, 307, 421, 424, 809, 825, 843, 844, 846, 900, 902, 921
 - signal-to-noise ratio (SNR), 98, 123, 427, 659, 705, 706
 - system performance, 101, 120, 319, 366, 547, 799, 858
 - third-order intercept point (IP3), 343, 366, 371, 377, 397, 700
 - cascades, 787
 - cathode ray tube (CRT), 74, 94
 - horizontal scanning, 59
 - image orthicon, 57, 58

- tubes, 57, 58, 64, 72, 411
 - vertical, 60
- CDMA–optical, 173
- chirp, 261, 274, 275, 276, 297, 301, 303, 304, 305, 306, 307
- chromatic dispersion, 122, 894, 921
- circulator, 169, 173
- clipping, 806, 810–837, 814, 817, 820, 821
 - clipping noise, 817–825, 833, 873
 - clipping statistics, 812, 825–830
 - preclipping, 834
- clock data recovery (CDR)
- CNR carrier to noise, 561
- codes
 - Manchester, 911, 922
 - nonreturn to zero (NRZ), 667, 909, 911, 922, 994, 997
 - return to zero (RZ), 910, 911, 922
- coding
 - concatenated coding, 672, 673
 - convolution, 381
 - deinterleaver, 677, 678, 739
 - forward error correction (FEC), 8
 - galois field, 675
 - interleaver, 139, 677, 678, 739
 - parity, 673
 - pseudo-random beat sequence (PRBS)
 - generator, 669, 670, 672
 - puncturing, 680, 681, 742
 - randomizer, 90, 111, 739
 - Reed–Solomon, 667, 674
 - Trellis, 679, 680, 681
 - Trellis decoder, 739
 - Trellis diagram, 681
 - Trellis encoder, 90, 92, 668
 - Viterbi algorithm, 682
- coefficient of performance (COP), 597
- coexistence, 16, 806, 868, 928, 993, 987
- coherent, 262, 355, 708, 720, 1023
 - coherent tones, 811
 - detection, 354–355, 358
- coma. *See* lenses.
- community access TV (CATV), 3, 39, 561, 581
 - frequency plan, 97, 103
 - integrated triplexer, 190
 - node, 932
 - optical receiver, 436, 936, 1027
 - receiver, 98, 147, 434, 700, 710, 721, 805
- Society of Cable Telecommunications Engineers (SCTE), 99, 1024, 1025
- tap, 704
- composite distortions, 877
 - beat count, 389, 407
 - coherent CSO, 1023
 - composite second order (CSO), 12, 41, 98, 100, 101, 284, 285, 336, 377, 378, 381, 391, 398, 522, 699, 752, 824, 850, 852, 857, 867, 995
 - composite triple beat (CTB), 12, 41, 98, 100, 101, 111, 336, 372, 377, 378, 379, 381, 386, 391, 397, 398, 522, 699, 752, 754, 824, 852, 867, 995, 1123
 - convolution, 381
- composite second-order (CSO), 561
- composite triple beat (CTB), 561
- composite video, 70
 - aspect ratio, 61, 62, 77, 79
 - aural, 57
 - blanking signal, 63
 - chrominance, 73
 - color burst, 67, 68, 72, 74, 76, 101, 110, 242
 - field, 76
 - frame, 56
 - horizontal, 110
 - image orthicon, 57, 58
 - interlaced, 57
 - luminance, 73
 - picture, 561
 - vertical, 59, 60, 102, 110, 209, 226
- connectors
 - automatic power control (APC), 20, 126
 - face contact (FC), 126, 127, 1035
 - subcarrier connector (SC), 20, 126
 - super physical contact (SPC), 126
 - straight transfer function (ST), 125, 172
- constraint of pattern length, 685
- continuous wave (CW), 561, 563, 581, 586
- control loops
 - automatic current control (ACC), 495
 - automatic gain control (AGC) burst, 526
 - feedback, 530, 599
 - feed forward, 557–560
 - automatic power control (APC), 45, 587, 928
 - burst, 941, 963

- control loops (*continued*)
 - close loop, 584, 914
 - current starving, 495
 - gain margin, 479, 524, 535, 923
 - open loop, 534, 550, 551, 710, 711
 - phase locked loop (PLL), 715, 716, 717, 722, 912, 913, 914, 916, 923
 - phase margin, 534, 535
 - pulse width modulation (PWM) control loop, 524
 - synthesizer, 699, 700
 - thermo electric cooler (TEC) control loop, 594–622, 968
 - wavelength locking. *See* wavelength locking.
 - constellation
 - additive white gaussian noise (AWGN), 652, 655
 - AM to phase modulation (PM), 376, 398, 652, 663, 774
 - calibration, 821, 660
 - carrier leakage, 93, 253, 262, 636, 638, 640, 641, 642, 644, 663
 - cross talk, 147, 190, 191, 205
 - decision zone, 638
 - E_b/N_0 , 307, 401, 912, 932, 933, 935
 - error vector magnitude (EVM), 638, 650, 653, 660, 661, 664
 - I/Q mismatch, 567
 - jitter, 645, 712, 716, 719, 720, 915, 916
 - modulation error ration (MER), 653, 661, 664, 720
 - origin offset, 638, 645, 663
 - peak to average/rms, 541, 634, 635
 - convolution, 568
 - convolution code, 679, 685
 - coplanar waveguide. *See* transmission lines.
 - copper lines, 3
 - correlation coefficient, 448
 - coupled charge device (CCD), 58
 - coupler/coupling
 - capacitive, 459, 1003
 - coupled mode equations, 221
 - directional coupler, 183, 184, 586
 - even mode, 760
 - odd mode, 760
 - star, 130, 131, 1002, 1003
 - Y branch, 184, 185
 - cross coupled differential pair (CCDP), 764
 - cross modulation, 398, 1027
 - cross phase modulation XPM, 806, 861–863, 876
 - crosstalk–electrical, 1013
 - analog ground (GND), 1003
 - compartments, 1005, 1012
 - coupling capacitance, 1004
 - current loop, 1002, 1003, 1005, 1008, 1012
 - digital GND, 1003
 - PRBS, 669, 672, 906, 922, 955, 994, 998
 - Series length, 569, 570, 905, 929, 954, 998
 - star point, 1002, 1003, 1011
 - crosstalk–optical
 - optical trap, 190, 191, 192, 205
 - crystals
 - birefringence, 173
 - extra ordinary wave, 166, 174
 - ordinary wave, 167, 173
 - X-cut, 300
 - Y-cut
 - cumulative distribution function (CDF), 564, 587
- ## D
- damping factor
 - electrical, 606
 - optical, 123, 155, 190, 191, 192, 344
 - dark current. *See* CNR.
 - dark CNR, 414, 416, 433, 557, 1022, 1024, 1038, 1039
 - direct broadcast satellite (DBS) TV, 4
 - distributed Bragg reflector (DBR). *See* lasers.
 - dc offset. *See* constellation.
 - decimation, 81
 - decision directed (DD). *See* equalizers and algorithms.
 - defocusing, 343, 345
 - delay flip flop (D-FF), 732
 - delta theta root mean square (rms) $\delta\theta_{\text{rms}}$. *See* jitter.
 - dense wavelength division multiplexing (DWDM), 135, 159, 172, 231, 870, 871, 984
 - dense WDM, 176, 260
 - depletion capacitance, 318, 328, 432, 481
 - depletion region, 322

desensitization, 994–996
 detection, 694, 712
 detector RF
 average (true rms), 561, 582, 583, 584, 586, 1040
 coefficient, constant, 814
 detector log video amplifier (DLVA), 541, 542, 561, 584
 tangent delta
 differential gain (DG), 101
 differential lines, 1007
 differential phase, 101, 102–103, 112, 779
 diffraction grating, 137
 digital controlled attenuator (DCA), 45, 382, 517, 601
 digital GND. *See* crosstalk electrical.
 digital loop carrier (DLC) system, 31
 digital signal processing (DSP), 587
 digital subscriber line (DSL) system
 digital transceivers. *See* transceivers.
 direct modulation, 261, 274, 285, 297, 307, 830, 850, 875
 direct recombination, 214
 discrete cosine transform (DCT).
 See MPEG.
 dispersion, 122, 855, 893
 dispersion shifted fiber (DSF), 846, 848
 distributed amplifier. *See* amplifiers.
 distributed element, 1009
 distributed feedback (DFB). *See* laser.
 dual parallel linearization.
 see linearization.
 dynamic range
 automatic gain control (AGC), 585
 optical, 938, 1019, 1021, 1035
 receiver, 430, 546
 saturation, 336
 spurious free dynamic range (SFDR), 366
 threshold, 932

E

E_b/N_0 vs. CNR. *See* CNR.
 electron ionization coefficient, 350, 351, 427
 electron mobility
 elliptic filter. *See* filters.
 end of life (EOL), 957, 966

error vector magnitude (EVM).
 See constellation.
 equalizers
 adaptive, 701, 704–707, 714, 715, 717
 blind, 741
 decision directed, 706
 decision feedback, 707–708, 711
 feed forward, 707
 linear transversal equalizer (LTE), 701
 radio frequency (RF) RLC, 499, 501, 502, 503
 RF up tilt RC, 498
 zero forcing equalizer (ZFE), 704
 equivalent input noise current (EIN).
 See noise.
 equivalent noise BW. *See* noise.
 ethernet passive optical network (EPON).
 See PON.
 excess noise ratio (ENR), 838
 excitation, 209, 216, 255, 292, 480, 784
 external modulators, 301, 755
 balanced bridge interferometer, 301
 electro absorption, 303–304
 ethernet, 6, 22
 external phase modulation (EPM), 851
 Mach–Zehnder interferometer, 132, 180, 298, 767
 traveling wave modulator, 301
 extinction ratio (ER), 246, 246–249, 257, 592, 888–891
 eye diagram, 288, 307, 472, 888, 889, 959

F

Fabry–Perot (FP) laser. *See* lasers.
 fano limit, 485
 Faraday effect, 164
 Faraday rotator, 164, 165
 fast attack slow release, 586
 fast Fourier transform (FFT), 568
 federal communication commission (FCC), 587
 feedback
 AGC, 521–584, 599
 amplifier, 464, 467, 469, 470, 496
 linearization, 791–798
 stability, 232, 599

- feed forward
 - AGC, 518–521, 557–560
 - linearization optical, 748, 784–791
 - linearization RF, 780–782
 - FF-AGC, 585, 560
 - fiber Bragg grating, 118, 148–163, 149, 173, 967
 - equalizer, 501, 502, 503, 510, 711
 - filters, 137, 173
 - optical CDMA, 173
 - fiber in the loop (FITL), 19, 225
 - fiber to the home, curb, building,
 - business, premises (FTTx), 6, 17, 185, 1038
 - fiber to the curb (FTTC), 4, 6, 31, 32, 34, 51
 - fiber to the home (FTTH), 4, 6, 7, 10
 - fiber to the premises (FTTP), 4, 18, 19, 20, 50
 - filters
 - band pass, 155, 201, 699, 766, 825, 967, 984, 1022
 - bessel, 905
 - duplexer, 44, 50, 994
 - elliptic, 44, 45, 406, 993
 - finite impulse factor (FIR), 696
 - first-order sigma delta, 734, 735
 - free spectral range (FSR), 139, 967
 - high pass, 43, 44, 650, 712, 906, 919, 930
 - infinite impulse fitter (IIR), 587
 - low pass, 14, 33, 42, 71, 75, 81, 264, 521, 699, 705, 712, 836, 905, 930, 993
 - optical, 64, 135, 137, 236, 1019, 1035
 - surface acoustic wave (SAW), 696–697, 701
- flatness, 464, 471, 499, 502, 524, 771, 1027
 - flip flop (FF), 731
 - FM noise, 742
 - frame by frame decoding, 687
 - frequency division multiplexing (FDM), 4, 819
 - frequency modulation (FM), 561
 - front end
 - receiver front end, 314, 410, 416, 419, 429–442, 517, 993
 - RF front end, 382, 431, 434, 699
 - full service access network (FSAN)
 - service, 18, 929
 - triplexer, 51, 180
 - wavelengths, 189, 192
- ## G
- gailos field (GF), 675
 - gain BW product, 349
 - gain compression, 278, 280, 282, 370
 - AM to AM polynomial coefficients, 397, 775
 - laser, 306
 - laser coefficients, 263, 282
 - RF, 44, 497
 - gain constant, 213, 544, 545, 546, 912
 - detector
 - negative temperature coefficient (NTC), 52, 102, 600, 601, 602, 603, 605, 610
 - voltage variable attenuator (VVA), 504, 517, 519, 531, 540, 542
 - gain control circuit, 949, 950
 - gain margin. *See* control loop, feedback.
 - gate bias. *See* bias.
 - gigabit interface converter (GBIC). *See* transceivers.
 - gigabit passive optical network (GPON). *See* PON.
 - grated index GRIN, 226
 - grating-assisted codirectional coupler with sampled reflector (GCSR) lasers. *See* lasers.
 - ground. *See* crosstalk electrical.
 - group delay, 701, 855
- ## H
- hamming distance, 685
 - hard decision, 687
 - harmonics, 279, 771, 772, 998
 - heterodyne, 343, 354, 358
 - heterojunction bipolar transistor (HBT), 371, 420, 461, 496, 770
 - high definition television (HDTV), 76, 78, 80, 111, 112, 564
 - high impedance, 331, 358, 443, 472, 487, 906, 1004, 1005, 1012
 - high pass filter (HPF), 43, 650, 712, 906, 930, 1034

high pass filter (HPF) response, 734
 Hilbert transform, 75
 home phone networking alliance (HPNA),
 6, 7, 33
 housing
 long carbon filter (LCF), 974
 continuous carbon filter
 (CCF), 975
 crosstalk. *See* optical or electrical
 crosstalk.
 multisource agreement (MSA), 47, 594,
 595, 979, 981
 shielding, 974–975
 hybrid fiber coax (HFC), 6, 10–13, 42,
 55, 226, 386, 517, 667, 699, 851

I

image reject, 662
 index guided. *See* lasers.
 infinite impulse response filter
 (IIR), 587
 integrated solution, 698
 integrated triplexer (ITR), 49, 50,
 54, 179
 integrated triplexer to the curb
 (ITC), 54
 integrated telecommunication union
 (ITU), 6, 692
 inter symbol interference (ISI), 905
 intercept point, 366, 367
 IP_n, 367, 368, 369
 second-order intercept point (IP₂), 366,
 377, 397, 700
 third-order intercept point (IP₃), 343,
 366, 371, 377, 397, 700
 interferometer, 132, 157, 180, 298,
 301, 767
 interleaver/deinterleaver, 677–679
 intermodulation, 98, 209, 277, 285, 343,
 365, 366, 379, 387, 496, 641, 698,
 757, 824, 993, 1018
 internet protocol (IP), 23
 intrinsic region, 314
 inverse fast Fourier transform
 (IFFT), 568
 ion exchange, 180
 ionization coefficient, 904
 isolation, 1000, 1004
 isolator, 165, 173

J

jitter, 645, 712, 716, 720, 721, 915,
 916, 917
 delta theta rms $\Delta\theta_{\text{rms}}$, 712, 722, 727,
 742, 896
 phase noise, 293, 294, 296, 649, 663,
 712, 720, 724, 742
 timing jitter, 896–899, 899, 921
 junction, 324
 PN, 322, 323, 324
 PIN, 49, 320, 327, 328, 336, 343, 477,
 481, 504, 930
 junction capacitance, 327

K

Kirchoff current law (KCL), 612
 Kirchoff voltage law (KVL), 612, 762

L

Laplace transform, 731
 lasers
 buried heterostructure (BH), 216, 265
 distributed Bragg reflector (DBR), 219,
 220, 221, 223, 224, 227, 228, 231,
 232, 233, 234, 240, 241, 242, 255
 distributed feedback (DFB), 209, 210,
 219, 220, 221, 222, 223, 224, 231,
 232, 233, 237, 240, 241, 255, 256,
 261, 262, 266, 282, 283, 297
 dynamics, 261–312
 Fabry–Perot (FP), 209, 210, 213,
 216–218
 gain guided, 209, 214, 215, 216,
 229, 254
 grating-assisted codirectional coupler
 with sampled reflector (GCSR),
 240, 242, 243, 244, 245
 index guided, 209, 214, 216, 254
 large signal model, 264, 272, 273
 line width, 232, 275, 296, 297
 mode hopping, 849
 multiple quantum well (MQW), 225
 Nd yttrium aluminum garnet
 (YAG), 781
 phase noise, 293, 294, 295–297, 296,
 307, 663, 712, 724, 742
 population inversion, 212, 214, 254
 quantum well, 209
 radio frequency (RF) model, 209

- lasers (*continued*)
- rate equations, 262, 263, 264, 266, 282, 291, 292, 293, 306
 - relative intensity noise (RIN), 293–297, 307, 421, 424, 809, 825, 843, 844, 846, 873, 900, 902, 921
 - relaxation oscillation, 261, 264, 267, 268, 269, 270, 271, 275, 277, 278, 279, 282, 295, 296, 297, 306, 307
 - side mode suppression, 241
 - slope efficiency, 246–249, 250, 251, 253, 257
 - small signal model, 271, 357, 462
 - stimulated emission, 209, 210, 211, 214, 253, 262, 264, 273, 282, 294
 - vertical cavity surface emitting laser (VCSEL), 209, 210, 227, 228, 229, 230, 231, 234, 236, 240, 241, 256
- lasers–tunable, 209
- distributed Bragg reflector (DBR), 219–224, 227, 228, 231, 232–234, 240, 241, 242, 255, 256
 - grating-assisted codirectional coupler with sampled reflector (GCSR), 240–246
 - open architecture, 256
 - wavelength locker, 52, 53, 966–970, 984
- layers model, 24
- first layer protocol (L1P), 24
- least mean square (LMS). *See* algorithms.
- lenses, 191, 192, 193, 200, 201
- aberration, 190, 191, 195, 198, 200–201, 205, 343
 - coma, 201
 - spherical lense, 191, 192
- limiter, 835
- linearization, 264, 748, 755, 759, 780–782, 784–791, 791–798
- back to back, 797
 - dual cascade, 784–791
 - dual parallel, 782, 784
 - feedback, 209, 255, 261, 461, 464, 467–471, 509, 535, 586, 602, 671, 679, 702, 765–769, 791–798, 930, 931, 951
 - feed forward RF, 780
 - feed forward optical, 711
 - preclipping, 834
 - predistortion, 755, 756, 759–765, 770, 835
 - push pull, 41, 336, 494, 770, 774, 775, 778, 779
 - reflective transmission line (RFL), 779
- link, 46, 807, 808, 873
- budget, 873
 - carrier-to-noise ratio (CNR), 12, 41, 98, 99, 101, 290, 384, 386, 413, 414, 416, 420, 422, 423, 425, 449, 559, 873
 - distortions, 261, 386, 759–765, 806, 848
 - minimum detectable signal (MDS), 902
 - noise, 808–810, 817
- lithium niobate modulator. *See* external modulator.
- load line. *See* bias.
- local oscillator, 72, 354, 630, 667, 699
- loop transmission. *See* control loop.
- low-pass filter (LPF), 732
- low side band (LSB) toggling, 585
- lumped elements, 302
- ## M
- Mach-Zehnder interferometer (MZI), 132, 180, 298, 308, 767
- Manchester. *See* codes.
- matched PIN VVA, 504–507
- MathCAD, 566, 765
- MATLAB, 566, 569, 570
- MATLAB code for PAR, 570
- MATLAB code for SAR, 576
- max likelihood, 682
- Maxwell equations, 1000
- metal shield, 975
- micro electro mechanical system (MEMS), 232, 234–236, 238, 256
- minimum detectable signal. *See* link and crosstalk.
- mismatch, 389
- I/Q mismatch, 567
 - impedance, 247, 404
 - mismatch effects, 389–391
- mode partition noise, 290, 293, 893
- mode suppression ratio (MSR), 220, 255
- modulation, 87, 227, 230, 246, 250, 261, 271, 279, 375, 650, 818
- amplitude (HUM), 101
 - amplitude modulation (AM), 562

- bit error rate (BER), 290, 654, 656, 659, 724, 819, 829, 836, 847, 886, 887
 - constant envelope, 561, 652
 - cross phase modulation (XPM), 806, 876
 - direct modulated laser (DML), 261
 - error vector magnitude (EVM), 638, 650, 653, 660, 661, 664
 - external modulated, 233
 - extinction ratio (ER), 246–249, 257, 592, 891, 938
 - frequency modulation, 261, 967
 - M ary QAM. *See* QAM.
 - modulation error ratio (MER), 653, 661, 664, 720
 - multitone, 812, 1023
 - on–off keying (OOK), 8, 342, 859, 933
 - optical modulation index (OMI), 246, 271
 - quadrature amplitude modulation (QAM), 80, 111, 629, 632, 633, 651, 654, 692, 845
 - vestigial side band (VSB), 59, 68, 71, 95, 111, 667, 818, 874
 - modulation error ratio (MER). *See* constellation or QAM.
 - modulator, 69, 72, 301, 303–304, 305, 308, 630, 641, 698, 755, 785
 - balanced bridge interferometer, 301
 - external modulator. *See* external modulator.
 - quadrature phase shift keying (QPSK), 44, 72, 629, 641, 667, 694, 698, 700
 - modulator/demodulator (MODEM), 587
 - moving picture experts group (MPEG), 80, 81, 83, 86, 87, 90, 667, 668–669
 - decimation, 81
 - discrete cosine transform (DCT), 83
 - intra, 84
 - MPEG1, 80, 81, 83, 86, 87
 - MPEG2, 86, 87, 88, 89, 90, 91, 92, 93, 101, 675
 - picture element (PEL), 61
 - multi source agreement (MSA), 47, 594
 - multichannel multipoint distribution system (MMDS), 29, 277
 - multiple quantum well (MQW). *See* lasers.
 - multiple reflections, 210, 613, 849, 863, 978
 - multiplexer/demultiplexer (MUX/deMUX), 147, 869
 - FDD
 - frequency division multiplexing (FDM), 4, 819
 - time division multiplexing (TDM), 927
 - wavelength division multiplexing (WDM), 4, 17, 23, 25, 32, 131, 132, 150, 172, 871, 978, 984
- N**
- national television systems committee (NTSC), 561, 564, 587
 - negative feedback, 602
 - network analyzer, 442, 1033, 1034, 1040
 - noise
 - bipolar junction transistor (BJT), 760
 - complementary metal oxide semiconductor (CMOS), 766, 960
 - correlation coefficient, 448
 - Flicker 1/f, 411, 412
 - metal-semiconductor field effect transistor (MESFET), 413, 456, 467
 - mode partition, modal, 286, 287, 290, 292, 891–895, 921
 - noise burst, 80, 679
 - noise equivalent BW, 405, 409, 443
 - noise figure, 478, 508, 548, 556, 560
 - noise over gain (NOG), 737
 - noise power ratio (NPR), 44
 - noise rejection vs. over sampling ratio (OSR), 739
 - noise resistance, 448, 459
 - Nyquist, 534, 535, 696, 740
 - quantization, 728, 743
 - receiver, 215, 994
 - relative intensity noise (RIN). *See* lasers.
 - shot, 410–411, 414
 - thermal, 408, 414, 428
 - noise transfer function (NTF), 731, 733, 739, 743
 - nonlinear distortions (NLD), 98, 261, 341, 810–837
 - number of levels (NOL), 726, 727
 - number of steps (NOS), 726, 727
 - numerical aperture, 867
 - numerical example, 40, 436–437, 774–778

numerically controlled oscillator
(NCO), 701
Nyquist sampling criterion, 702

O

on–off keying (OOK), 8, 342, 859, 933
open architecture. *See* tunable lasers.
open loop (loop transmission (LT)), 534
operational amplifier PIN TIA, 479
optical cross talk. *See* cross talk optics.
optical fiber non linearities
optical loss, 119, 210, 214, 806, 807
optical modulation index. *See* modulation.
optical modules
 bulk optics. *See* bulk optics.
 planar lightwave circuits (PLC), 180,
 181, 182, 183, 186, 187, 203,
 204, 967
 receiver optical subassembly (ROSA),
 46, 48, 49, 54, 927, 971–980,
 1005, 1006
 transmitter optical subassembly
 (TOSA), 46, 48, 49, 54, 927, 971,
 973, 975, 977, 978, 980, 984, 1006
 triplexer. *See also* bulk optics.
optical signal-to-noise ratio (OSNR), 973
orthogonal frequency division multiplexing
(OFDM), 569
over sampling ratio (OSR), 729, 739, 743

P

packaging
 butterfly, 47, 970
 gigabit interface converter (GBIC), 47
 10 gigabit small form pluggable (XFP),
 47, 979
 multisource agreement (MSA), 47, 594,
 595, 981
 small form factor (SFF), 47, 972, 976
 small form pluggable (SFP), 47, 973,
 975, 977, 978, 984
parity, 91, 674, 675, 740
peak envelope power (PEP), 561
peak to average (PAR), 541, 564, 565, 568,
 570, 587, 634, 635
peak to rms, 586
phase locked loop (PLL), 737
 phase noise, 734

 phase noise, 220, 293, 294, 295–297, 307,
 646, 649, 663, 712, 720, 724, 742
 optical, 297
 radio frequency (RF), xxix
photodetector (PD), 40, 41
 avalanche photo detector (APD), 320,
 346, 347, 348, 349, 350, 351, 352,
 358, 426, 427, 428, 973
 junction capacitance, 327
 linearity, 397
 matching, 1003–1004
 noise model, 426–429
 pickup inductor, 41, 331, 332, 335,
 438, 510
 PIN junction, 322, 324, 325
 PN junction, 322, 324
 quantum efficiency, 253
 responsivity, 316, 344, 356
 small signal, 226, 264, 266, 269, 271,
 282, 306
 stray capacitance, 430, 437
 transport time, 270, 318, 324
 wavelength selective photodetector,
 609–623, 971
operation and maintenance
 (PLOAM), 945
power spectral density (PSD) 728, 729
power supply rejection ratio
 (PSRR), 961
preamble, 741, 930, 932, 981
pseudo-random beat sequence (PRBS),
 922, 955, 994
pulse repetition frequency (PRF), 63
pulse repetition interval (PRI), 63
preclipping. *See* linearization.
predistortion. *See* linearization.
probability density function (PDF), 587,
 564, 565
processing gain, 691
protocol
 internet, 23, 25
 model, 22–25
 stack, 24, 510
pulse coded modulator (PCM), 732
 block diagram, 734
puncture convolutional code, 744
push pull receiver, 336, 778
 amplitude balance, 637

balanced to unbalanced (BALUN),
41, 774
phase balance, 638, 641, 772, 774

Q

Q function
quadrature amplitude modulation (QAM),
586, 587, 564, 565, 568, 569, 570
quadrature phase shift keying
(QPSK), 567
quadrature phase shift keying (QPSK)
modulator, 72, 697
M ary QAM, 629, 654, 657, 659, 662,
675, 817
pulse-amplitude modulated (PAM), 654
quantization noise, 728, 742
quantization process, 729
quantum efficiency, 213, 253
quantum limit. *See* CNR.
quasi static regime

R

radio frequency back off, 587, 568
detector, 586
front end, 382, 431, 434, 699
Raman scattering, 858, 875
randomizer, 90, 111, 667, 739
rate equation, 262, 263, 264, 266, 270, 280,
282, 291, 292, 293, 306
Rayleigh scattering, 119, 842
receiver
analog, 40, 41
digital, 46, 189, 190, 477, 714, 885,
1034, 1035
noise. *See* noise.
return path, 43, 44, 46
recombination
augar, 213, 244, 253
direct, 214
indirect, 214
Reed–Solomon, 667, 674
reflective transmission line (RFL), 799
refraction index, 120
relative intensity noise (RIN), 809
relaxation oscillation, 261, 264, 267, 268,
269, 270, 271, 275, 277, 278, 279,
282, 295, 296, 297, 306
residual AM, 585

resistor inductor capacitor network (RLC),
269, 306, 499, 501, 502, 503
responsivity. *See* photo detector.
resistance capacitance (RC), 510
retardation locked loop (RLL), 765
return to zero. *See* codes.
root mean square (rms), 563, 586, 730

S

sample-to-average ratio (SAR) 587, 569,
570
saturation
current, 230, 234, 319, 320, 353, 411,
416, 425, 508, 770
power, 7, 45, 123, 245, 248, 420, 560,
581, 808, 833, 871, 899
state (AGC), 830
scattering parameters (S parameters), 442,
451, 453, 466
Schotkey noise (shot noise).
See noise.
second order sigma delta, 737
semiconductor laser. *See* laser.
SFE, 564
SFU, 564
small form factor (SFF).
See packaging.
small form pluggable (SFP).
See packaging.
sigma delta ($\Sigma\Delta$), 729, 731, 736
sigma delta NTF, 732
sigma delta demodulator, 732
sigma delta modulator, 731
 $\Sigma\Delta$ noise shaping, 736
sigma delta loop ($\Sigma\Delta$ loop) 737
sigma delta order ($\Sigma\Delta$ order) 737
signal constellation, 689
signal to noise ratio (SNR). *See* CNR.
signal transfer function (STF) 731, 733
silicon optical bench, 980
slope efficiency. *See* laser.
Smith chart, 246, 247, 331, 332, 333,
358, 442
smoothing low-pass filter (LPF), 732
soft decision, 686, 687, 688
spatial hole burning (SHB), 279, 280,
281, 282
spectral hole burning (SHB), 226

spurious free dynamic range (SFDR).
See dynamic range.
 square root raised cosine (SRRC)
 567, 568
 star coupler. *See* coupler.
 state diagram, 683, 684
 stimulated Brillouin scattering (SBS).
See laser.
 stimulated emission, 209, 210, 211,
 214, 253, 262, 263, 264, 273,
 282, 294
 stimulated Raman scattering (SRS),
 858, 875
 super heterodyne receiver, 73, 668, 689
 symbol by symbol, 688, 709
 sync peak, 587
 synchronous digital hierarchy (SDH),
 25, 26
 synchronous optical network (SONET),
 11, 25, 26, 27

T

take over gain (TOG), 738
 tangent delta. *See* detector RF.
 thermal equilibrium, 409, 410
 thermal noise. *See* noise.
 thermistor NTC, 603, 609
 thermo-electric cooler (TEC), 165, 166,
 226, 248, 591, 592, 594, 595, 596,
 598, 599, 602, 603, 604, 605, 607,
 608, 609, 614, 620, 622, 624
 threshold, 217, 585
 time division multiplexing access
 (TDMA), 8, 12, 649, 927, 962
 timing jitter. *See* jitter.
 timing recovery, 707, 715
 traceback, 687, 690
 transceiver, 46, 48, 50, 929, 980, 1006
 10 gigabit small form pluggable
 (XFP), 47
 gigabit interface converter
 (GBIC), 47
 integrated triplexer (ITR)/integrated
 triplexer to the curb (ITC), 54
 small form factor (SFF),
 972, 976
 small form pluggable (SFP), 47, 973,
 975, 984

multisource agreement (MSA),
 594, 595
 transfer function, 525, 527, 528, 538,
 764, 914
 transmitter, 43, 44, 45, 46, 243,
 246, 798
 analog CATV, 12
 digital, 46, 48, 710, 945
 return path, 43, 44, 46,
 51, 54
 transponder, 52, 53, 971, 984
 transport time. *See* photodetector.
 traveling wave modulator.
See external modulator.
 Trellis code. *See* coding.
 Trellis diagram, 684, 687
 two tone test, 342, 1018

U

up link, 4, 5, 11
 up stream, 11, 46, 51

V

vertical cavity surface emitting laser
 (VCSEL). *See* lasers.
 video signals, 11, 63, 97, 101
 aural, 56, 57, 562, 631
 blank, 63, 232, 840
 horizontal, 59, 110
 moving picture experts group (MPEG).
 See MPEG.
 National Television Systems Committee
 (NTSC), 55, 56, 61, 67, 68, 70, 92,
 94, 110, 393
 phase altered line (PAL), 55,
 68, 110
 sequential color with memory in french
 sequentiel couleur avec memoire
 (SECAM), 55, 68, 110
 vertical, 58, 59, 102, 209, 226
 vestigial side band (VSB).
See modulation.
 Viterbi algorithm, 682
 voltage controlled oscillator (VCO), 711,
 715, 734, 737, 913, 920
 voltage variable attenuator
 (VVA), 586

W

watchdog, 53
waveguide, 142, 236, 1010
wavelength, 6, 9, 52, 189, 255, 261, 611,
856, 861, 872, 967, 970–971
wavelength division multiplexing (WDM).
 See multiplexing.
wavelength locker. *See* tunable
 lasers.
wavelength selective photodetector.
 See photodetector.

X

10 gigabit small form pluggable (XFP).
 See packaging or transceivers.

Y

Y branch. *See* couplers.
YAG laser. *See* lasers.

Z

zero forcing (ZF). *See* algorithms.

Avigdor Brilliant is a senior staff engineer at Qualcomm in Israel. He is involved with wireless video IC architecture and system design for DVB-H / DVB-T / T-DMB ISDB-T / FLO standards. Prior to joining Qualcomm, he served as a senior technical contributor in Marvell – DSPC, previously Intel–DSPC in Petach Tikva, Israel, where he was involved with advanced architectures of CMOS RF ICs solutions for cellular applications for 2.5G and 3G. During his role in DSPC, Mr. Brilliant was involved with PMIC (power management integrated circuit) architectures as well. From 1999–2005, he was with LuminentOIC (known today as Source–Photonics) a subsidiary company of MRV Communications in Chatsworth, California, USA. During this time he was the senior FTTx RF architect. He established a strong RF and FTTx team and led the analog RF group. Mr. Brilliant was the designer and architect of the LuminentOIC integrated triplexer (ITR) and the ITC solution for higher RF power to the curb, bringing it from concept to mass production. This product was employed by Verizon in their largest FTTx deployment with Tell–Labs, AFC, and by Motorola. He also helped to drive LuminentOIC to ISO process. From 1995–1999, Mr. Brilliant was with Optomic Microwaves (known as Belcom today) in Migdal Ha'Emek, Israel, in a position of a senior engineer in the fields of VSAT and cellular design, and was in the management staff. He is currently on the advisory board of Belcom. From 1993 to 1995, Mr. Brilliant was with MTI Technology and Engineering at Tel -Aviv in a position of system engineer, where he was involved with WLL (wireless local loop) designs as well as COMINT and ELINT systems. Between 1986 and 1993, he was with MicroKim Ltd. (previously a subsidiary of M/A-COM) of Haifa, Israel, where he was in charge of the MIC amplification group, a member of the frequency sources group, and was the head of the Short Range Hunter RPV (remote platform vehicle) C-Band up-down-link program for the U.S. Naval Air branch. Mr. Brilliant received his Electrical Engineering degree from the Technion Israel Institute of Technology in 1986. He is a Senior Member of the IEEE, and published several papers on related subjects. He is also an adjunct instructor in the Electrical Engineering Department Communication Laboratory of the Technion.