

Index

A

- acceptor, 62
- acoustic measurement method, 468
- adding process, 267
- alignment and exposure, 194
- aluminum, 49, 455, 471
- ammonium chloride, 166
- annealing, 156, 170, 281, 282
 - alloy, 157
- antipunch-through implantation, 295
- arithmetic-logic unit (ALU), 78
- arriving angle, 377
- Atalla, M. M., 73
- automatic diameter control (ADC)
 - system, 103

B

- bandgap, 59
- Bardeen, John, 2
- barrier materials, 499
- batch process
 - tools, 39
- batch reactors, 112
- beam line system, 285
- beam stop, 294
- Bell Laboratories, 2, 73
- bird's beak, 134, 552
- Boltzmann distribution, 248
- bonding pad, 49, 53
 - etching, 80
- borophosphosilicate glass (BPSG), 87
- Brattain, Walter, 2

C

- capacitance, 66, 67, 299

- capacitor, 66
- carbon fluoride gases, 44
- central processing unit (CPU), 78, 285
- channeling effect, 278
- chemical mechanical polishing (CMP), 44, 55, 507
 - advantages, 515
 - applications, 516
 - copper, 537
 - endpoint detection, 538
 - hardware, 519
 - oxide, 534
 - tungsten, 535
- chemical mechanical polishing (CMP) process, 107
- chemical vapor deposition (CVD), 42, 110, 159, 254, 371
 - aluminum, 457, 483
 - atmospheric pressure CVD (APCVD), 374
 - copper, 502
 - dielectrics, 370
 - high-density plasma CVD (HDP-CVD), 426
 - low-pressure CVD (LPCVD), 164, 254, 375
 - metal, 475
 - plasma etch CVD (PECVD), 242, 258
 - plasma-enhanced CVD (PECVD), 164, 254, 377
 - rapid thermal CVD (RTCVD), 173
- chemisorption, 382
- chip

- packaging, 47
- cleanroom, 12, 24, 28, 29, 32, 33, 35, 45, 212
- cobalt, 464
- color chart, 402
- complementary metal-oxide semiconductor (CMOS), 85, 87, 89
 - inverter, 14, 17
 - process flow, 581, 582, 598, 616
- conducting band, 61
- contact printer, 194
- contamination, 29, 33, 35, 195
 - control, 30
 - elemental, 304
 - particle, 31, 303
- contamination control, 542
- copper, 65, 462, 501
 - chemical vapor deposition (CVD), 502
 - deposition, 464
 - electrochemical plating (ECP), 500
 - interconnection, 574
 - metallization, 89, 497, 498
 - seed layer, 499
 - slurry, 527
- copper metallization, 19
- crystal, 97, 103
 - defects, 99
 - orientation, 105
- crystal pulling, 104
- Czochralski (CZ) method, 102, 103

D

- damaging mechanism, 333
- dangling bonds, 141
- dc bias, 238, 250
- defects, 114, 530
- degowning, 35
- deposition, 111, 188
 - polysilicon, 39, 161
 - rate, 467
 - silicon nitride, 164
 - silicon oxide, 43
 - thin-film, 79
- deposition rate, 405

- depth of focus (DOF), 213
- design fault, 47
- development process, 203
- diborane, 39, 153
- die
 - testing, 46, 47
 - yield, 25, 26, 53
- dielectric
 - low- κ , 576, 612
- dies
 - test, 28
- diffusion, 150, 151, 168, 268, 271, 282
 - bay, 38
 - doping, 38
 - process, 153
- diode, 69, 70
- dioxide
 - silicon, 279
- discrete device, 3
- dishing effect, 16, 530
- dissociation collision, 241
- dopant, 168, 174, 285, 296
 - concentration, 154, 155, 305
 - diffusion, 174
- dopants, 61
 - concentration, 63
 - n-type, 62, 72
 - p-type, 63
- doping, 150
- drive-in, 153
- dual damascene, 439, 497, 537, 574
 - process, 19
- dynamic dispense, 189
- dynamic random access memory (DRAM), 41, 66, 75, 345, 349, 479, 625, 627

E

- E-chuck, 339
- edge-bead removal (EBR), 190, 191
- electric erasable programmable read-only memory (EEPROM), 76
- electrochemical plating (ECP), 500

electrochemical plating deposition (EPD)
 tools, 43
electromigration, 456
electron, 208, 238, 240
 free, 238
electron cyclotron resonance (ECR), 264
electronic design automation (EDA), 16
electronic-grade silicon (EGS), 101, 103
ellipsometry, 40, 146, 399
epitaxial silicon deposition, 109
epitaxial silicon growth, 80, 110, 111
epitaxial silicon layer, 110
epitaxy
 low-temperature (LTE), 115
 selective, 116
epitaxy process, 114
epitaxy systems, 112
equipment area, 45
erasable programmable read-only memory (EPROM), 76
etch, 315
 dielectric, 342
 dry (plasma), 330, 340
 main, 322
 mechanisms, 333
 metal, 329, 357
 oxide, 344
 polysilicon gate, 353
 profile, 320
 rate, 317
 reactive ion (RIE), 320, 332
 single-crystal silicon, 349, 351
 wet, 325, 340
etch bay, 40
etch pits, 97
etch process, 42
etching, 40
evaporation
 electron beam, 486
excitation-relaxation, 240

exhaust system, 129
exposure control, 199

F

facility area, 45
Fairchild Semiconductor, 4
feature size, 6, 8, 11, 31, 53, 78, 89, 199, 201, 218
field effect transistor (FET), 72, 73
film
 thickness, 539
flip-chip technology, 49
floating zone (FZ) method, 102
foundry company, 16
four-point probe, 305, 474
free radicals, 241, 242, 257, 260, 333
Frenkel defect, 99
fumed silica, 524
furnace, 39, 126, 167, 282
 horizontal, 129
 vertical, 129

G

gap fill, 256, 380
gas delivery system, 128
gas system, 284
gases
 processing, 128
gate, 10, 72, 76
 capacitance, 445
germanium, 2
 bar, 4
 single-crystal, 3, 62, 73, 96
glass transition, 202
gowning, 33, 35
graphics processing unit (GPU), 78
gyrofrequency, 248
gyromotion, 247, 286
gyroradius, 248, 288

H

hard bake, 205
heating process, 80, 187
Horni, Jean, 4
hot electron effect, 297

hydrofluoric acid (HF), 35, 37, 107, 325

hydrogen, 39, 114, 144

I

I-V curve, 70

implant bay, 42

implantation, 564

in-situ process, 173

insulator, 59

integrated circuit (IC)

 application-specific (ASIC), 79

 design, 16

 first, 3

 processing, 53

 technology, 1

Intel Corporation, 5

interconnection, 42, 67, 89, 570

 copper, 574

 early, 572

 local, 570

interlayer dielectric (ILD) film, 347

intermetal dielectric (IMD), 88, 370

interstitial defect, 99

ion bombardment, 248, 249, 255, 257–259, 330, 331, 333

ion implantation, 42, 79, 82, 151, 206, 267, 270, 279, 291, 294, 299, 305

 advantages, 270

 applications, 271

ion implanter, 247

ionization, 238, 240

J

junction depth, 150, 174

junction spiking, 456

K

Kilby, Jack, 3

killer defect density, 27

L

laminar flow, 33

light sources, 199, 215

lightly doped drain (LDD), 297, 561

line resistance, 452

lithography

 electron-beam (e-beam), 231

 extreme ultraviolet (EUV), 80, 226

 nanoimprint (NIL), 228

 next-generation (NGL), 216

 x-ray, 229

loading effect, 16, 321

loading system, 128

local oxidation of silicon (LOCOS), 87, 89, 133, 552, 554

logic design, 14

low-pressure chemical vapor deposition (LPCVD), 38

M

magnetic field, 247, 288, 294, 489

mask, 16, 18, 23, 194, 196, 223, 227, 230

mass-transport-limited regime, 111, 389

material structure, 95

 amorphous, 95

 polycrystalline, 95

 single-crystal, 95

mean free path (MFP), 244, 330

memory, 75, 76

 chip, 75, 625

 flash, 77, 78, 636

metal-insulator-semiconductor (MIS), 96

metal-oxide semiconductor (MOS), 269

metal-oxide-semiconductor field effect transistor (MOSFET), 42, 72, 73, 81, 85, 120, 564

metallization, 345, 451

 copper, 497, 498

metrology tools, 40, 42, 43

microprocessor, 78

microscope

 scanning electron (SEM), 40

Moore's law, 5

Moore, Gordon, 5

N

n-channel metal-oxide semiconductor (nMOS), 72, 296
n-type region, 69
nickel, 465
nitric acid (HNO_3), 37, 107
nitrogen, 39, 46, 114
Noyce, Robert, 4
nucleation step, 478

O

orientation
 crystal, 97
overhangs, 378
oxidation, 129–131, 137
 dry, 139, 140
 high-pressure, 145
 rapid thermal (RTO), 171
 trends, 149
 wet, 138, 142
oxide
 blanket-field, 82, 88, 132, 551
 gate, 134
 growth rate, 137
oxygen, 39
ozonator, 422
ozone, 421
 concentration, 422

P

p-channel metal-oxide semiconductor (pMOS), 72, 81, 296
p–n junction, 69
p-type region, 69
p-well implantation, 288
packaging, 46, 53
 ceramic, 51
 plastic, 51
 yield, 25, 26
particle, 30
 killer, 31
passivation, 413, 577, 614
patterning process, 8, 80, 179, 301
pellicle, 17
phase shift mask (PSM), 217

phosphine, 39
phosphorus silicate glass (PSG), 82
photo bay, 40
photolithography, 80, 82, 179, 199, 215
 optical, 9, 89
 process, 19, 31, 40, 184
photomask, 230
photoresist, 23, 181, 183
 coating, 188
 negative, 31
 positive, 31
 strip, 260, 358
photoresist etchback, 514
photoresist strip, 41
photoresist stripping, 80
physical vapor deposition (PVD), 43, 374, 483
 aluminum–copper, 495
 titanium, 493
 titanium nitride, 494
physisorption, 383
planar technology, 4
planarization, 511
plasma, 237, 239, 248, 330
 definition of, 237
 high-density, 238, 262, 331, 340
 inductively coupled (ICP), 263
 potential, 250
 radio frequency (rf), 238
plasma etch, 256
 remote, 261
plasma-enhanced chemical vapor deposition (PECVD), 42
polishing head, 521
polishing pad, 519
polymer, 182
polysilicon, 65, 66, 82, 101, 296, 297, 320, 454, 603
postacceleration, 289
postexposure bake (PEB), 202
Pourbaix diagram, 526
preclean, 492
predeposition, 152

premetal dielectric (PMD), 370
Preston equation, 528
prism coupler, 401
process gases, 45
processing tools, 45
profilometer, 467
profit margin, 26, 30
projection exposure system, 195

Q

quartz sand, 96, 100

R

rapid thermal annealing (RTA), 168
rapid thermal annealing (RTA)
 systems, 42
rapid thermal processing (RTP), 80,
 157, 167, 169, 174, 283
RC time delay, 67
reflectivity, 472
reflow, 159
refractive index, 146, 398
remote plasma CVD (RPCVD), 262
removal process, 40, 44, 79
removal rate, 528
resistance, 65, 70, 154
 sheet, 155, 305, 472
resistivity, 60, 63
resistor, 64
resolution, 180, 199, 213, 215, 221
reticle, 18, 197, 201
rf power, 433

S

safety, 232, 308, 503
scanning electron microscope (SEM),
 209, 467
Schottky defect, 99
selective epitaxial growth (SEG), 116
selectivity, 320, 322, 529
self-aligned contact (SAC), 345
SEMATECH, 5
semiconductor, 59
 manufacturing, 12, 36, 80
 materials, 59

 processing, 12
sensitizer, 183
shadowing effect, 279
shallow trench isolation (STI), 41, 89,
 349, 391, 554, 617
 self-aligned (SA-STI), 557, 639
sheath potential, 249
Shockley, William, 2, 269
shrinkage, 407
sidewall spacer, 164, 391
silane, 39, 111, 383, 411, 435
silicide, 570
silicon, 24, 96, 137
 crude, 101
 dioxide, 96, 100, 125, 130, 132,
 135, 140
 epitaxial, 159
 etch process, 41
 metallurgical-grade (MGS), 100
 nitride, 166
 on isolator (SOI), 600
 oxide, 255, 390
 polycrystalline, 104
 single-crystal, 3, 13, 62, 95, 97,
 102, 103, 267, 327
 substrate, 125, 300
silicon oxide, 55
silicon-oxide surface, 72
single-crystal
 semiconductor materials, 61
 structure, 61
single-crystal structure, 281
single-wafer implantation, 293
slurry, 107, 522, 524
 aluminum, 527
 copper, 527
 metal polishing, 525
 oxide, 523
soft bake, 193
solvent, 183
spectroreflectometry, 404
spin, 204
 disk, 293
spin-on glass (SOG), 396, 424

sputtering, 418, 487
 reactive, 460
sputtering etch process, 43
standing wave effect, 201
static dispense, 189
static random access memory
 (SRAM), 75
step coverage, 377
step-and-repeat, 18
step-and-repeat system, 196
stepper, 197
sticking coefficient, 386
stopping mechanisms, 272
 electronic stopping, 272
 nuclear stopping, 272
stress, 408, 470
surface mobility, 374, 379
surface-reaction-limited regime, 111,
 388
system ground potential, 288

T

tantalum, 464
test, 52
tetraethyl-orthosilicate (TEOS), 43,
 384, 386
 plasma-enhanced (PE-TEOS), 434
tetraethylorthosilicate (TEOS), 347
tetramethyl ammonium hydroxide,
 203
Texas Instruments, 3
thermal
 evaporation, 485
thermal budget, 151, 281
thermal expansion, 409
thermal processing, 125
thermal stress, 53
thermal velocity, 245
thermal wave, 306
thickness, 402
thin films
 metal, 465
thin-film bay, 42
threshold adjustment, 563
titanium, 458, 481

 nitride, 459, 481
 silicide, 454, 458
track system, 211
transistor
 bipolar, 70, 71, 81
 first, 2, 70
 level design, 14
 npn, 71
 point-contact bipolar, 96
transition region, 69
trench fill, 132
trichlorosilane (TCS), 101
troubleshooting, 437
tungsten, 461, 477, 479
 silicide, 480
 slurry, 526

U

ultraviolet (UV) light, 40, 76, 232
uniformity, 407, 469, 529

V

vacancy, 99
valence shell, 59
void formation, 441

W

wafer, 97, 114, 193, 204
 charging, 302
 cleaning, 185
 finishing, 108
 handler, 292
 manufacturing, 13
 preparation, 550
 processing, 36, 47, 107
 silicon-on-insulator (SOI), 116,
 118, 272
 size, 9
 surface, 40
 temperature, 294, 339
 yield, 25, 26
wafer preparation, 88
wafer processing, 19, 28
wafer-to-wafer (WTW)
 nonuniformity, 156

wafer-to-wafer (WTW) uniformity,
112, 318

well formation, 88, 557
 self-aligned twin well, 88
 single well, 88

wet bay, 37

wet clean processing, 136

wet etch, 536

 process, 107

 rate, 406

wet processes, 37

wire bonding, 49, 50

X

xylene, 232

Y

yield, 25–28, 30



Dr. Hong Xiao is a principal engineer of KLA-Tencor Corp. Previously, he was a technical marketing specialist at Hermes-Microvision, Inc. and a technical manager at Hermes Epitek. Other past positions include a working as a consultant of semiconductor process technology, a senior process engineer at Motorola Semiconductor Production Sector, and an associate professor at Austin Community College. After receiving his Ph.D., Dr. Xiao worked at Applied Materials as a senior technical instructor with expertise in dielectric thin-film deposition, semiconductor process integration, and plasma physics.

Dr. Xiao has authored and co-authored over 30 journal and conference papers. He is the author of *Introduction to Semiconductor Manufacturing Technology*, published by Prentice Hall in 2000. He has six US patents and more than ten patents in the application process. He has been a member of SPIE since 2005.