

Journal of Photonics for Energy

PhotonicsforEnergy.SPIEDigitalLibrary.org

Errata: Transparent electrodes based on two-dimensional Ag nanogrids and double one-dimensional Ag nanogratings for organic photovoltaics

Beibei Zeng
Zakya H. Kafafi
Filbert J. Bartoli

SPIE.

Errata: Transparent electrodes based on two-dimensional Ag nanogrids and double one-dimensional Ag nanogratings for organic photovoltaics

Beibei Zeng, Zakya H. Kafafi, and Filbert J. Bartoli

Lehigh University, Center for Photonics and Nanoelectronics, Department of Electrical and Computer Engineering, Bethlehem, Pennsylvania 18015, United States

[DOI: [10.1117/1.JPE.5.059999](https://doi.org/10.1117/1.JPE.5.059999)]

This article [*J. Photon. Energy* **5**, 057005 (2014)] was originally published on 23 December 2014 with an error in Fig. 6(b). The four lines mistakenly showed the same linewidth $w = 30$; it has been corrected to show different linewidths w of 30, 50, 70, and 90. The corrected figure appears below.




Fig. 6 Total photon absorption A_{photon} and its enhancement $(A_{\text{photon}}/A_{\text{photon-ref}} - 1) \cdot 100\%$ in the OPV active layers as a function of period P , (a) for different thicknesses t_1 of the 2-D Ag nanogrids with the linewidths w fixed at 70 nm; and (b) for different linewidths w , with the thickness t_1 fixed at 30 nm [all other geometric parameters are the same as those in Fig. 3(a)].

The paper was corrected online on 11 February 2015.